

§ 22.573 Use of base transmitters as repeaters.

As an additional function, base transmitters may be used as repeaters. Licensees must be able to turn the base transmitter on or off from the control point regardless of whether a subscriber-operated transmitter is transmitting.

§ 22.575 Use of mobile channel for remote control of station functions.

Carriers may remotely control station functions (e.g. shut down or reactivate base transmitters, turn aviation obstruction warning lights on or off, etc.) using a control transmitter operating on a mobile channel, subject to the conditions in this section and in § 22.567(h).

(a) The control transmitter must be capable of overriding transmissions from subscriber-operated transmitters if necessary. Subscriber-operated transmitters must not be capable of being used to deliberately or accidentally prevent the licensee from controlling the station.

(b) The licensee must implement measures designed to prevent station functions from being controlled by persons not authorized by the licensee to control the station.

(c) The control transmitter location must be within the composite service contour of the licensee's authorized station on the paired base channel.

§ 22.579 Operation of mobile transmitters across U.S.-Canada border.

Mobile stations licensed by Canada may receive two-way service while in the United States from stations licensed under this part, after authorization has been granted by the FCC. Mobile stations that normally operate under the authority of base stations licensed under this part may receive two-way service while in Canada from stations licensed under this part or by Canada, upon authorization by Canada.

§ 22.589 One-way or two-way application requirements.

In addition to information required by subparts B and D and § 22.529, applications for authorization to operate a paging transmitter on the channels listed in § 22.531, other than applica-

tions for a paging geographic area authorization, must contain the applicable supplementary information described in this section.

(a) *Interference exhibit.* Except as provided in paragraph (b) of this section, an exhibit demonstrating compliance with § 22.567 with regard to protected transmitters is required. This exhibit must:

(1) For UHF channels, identify each protected transmitter located within 108 kilometers (67 miles) of the proposed transmitter in directions in which the distance to the interfering contour is 76.4 kilometers (47.5 miles) or less, and within 178 kilometers (111 miles) of the proposed transmitter in directions in which the distance to the interfering contour exceeds 76.4 kilometers (47.5 miles); and identify each protected Basic Exchange Telephone Radio System central office transmitter in the Rural Radiotelephone Service within 231 kilometers (144 miles).

(2) For VHF channels, identify each protected transmitter located within 135 kilometers (84 miles) of the proposed transmitter in directions in which the distance to the interfering contour is 93.3 kilometers (58 miles) or less, and within 178 kilometers (111 miles) of the proposed transmitter in directions in which the distance to the interfering contour exceeds 93.3 kilometers (58 miles).

(3) For each protected transmitter identified, show the results of distance calculations indicating that there would be no overlap of service and interfering contours, or alternatively, indicate that the licensee of or applicant for the protected transmitter and/or the applicant, as required, have agreed in writing to accept any interference resulting from operation of the proposed transmitter.

(b) *Encompassment exhibit.* An exhibit showing that the area within the interfering contour of the proposed transmitter would be totally encompassed by interfering contours of operating co-channel base transmitters controlled by the applicant is required for applications to operate a transmitter with ERP exceeding the basic power and height-power limits of § 22.565. This encompassment exhibit may substitute

§ 22.591

for the interference exhibit required in paragraph (a) of this section.

[59 FR 59507, Nov. 17, 1994, as amended at 62 FR 11636, Mar. 12, 1997]

POINT-TO-POINT OPERATION

§ 22.591 Channels for point-to-point operation.

The following channels are allocated for assignment to fixed transmitters that support other transmitters that provide public mobile service. Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

| VHF Channels | | | |
|--------------|-------|-------|-------|
| 72.02 | 72.36 | 72.80 | 75.66 |
| 72.04 | 72.38 | 72.82 | 75.68 |
| 72.06 | 72.40 | 72.84 | 75.70 |
| 72.08 | 72.42 | 72.86 | 75.72 |
| 72.10 | 72.46 | 72.88 | 75.74 |
| 72.12 | 72.50 | 72.90 | 75.76 |
| 72.14 | 72.54 | 72.92 | 75.78 |
| 72.16 | 72.58 | 72.94 | 75.80 |
| 72.18 | 72.62 | 72.96 | 75.82 |
| 72.20 | 72.64 | 72.98 | 75.84 |
| 72.22 | 72.66 | 75.42 | 75.86 |
| 72.24 | 72.68 | 75.46 | 75.88 |
| 72.26 | 72.70 | 75.50 | 75.90 |
| 72.28 | 72.72 | 75.54 | 75.92 |
| 72.30 | 72.74 | 75.58 | 75.94 |
| 72.32 | 72.76 | 75.62 | 75.96 |
| 72.34 | 72.78 | 75.64 | 75.98 |
| 72.10 | 72.46 | 72.88 | 75.74 |
| 72.12 | 72.50 | 72.90 | 75.76 |
| 72.14 | 72.54 | 72.92 | 75.78 |
| 72.16 | 72.58 | 72.94 | 75.80 |
| 72.18 | 72.62 | 72.96 | 75.82 |
| 72.20 | 72.64 | 72.98 | 75.84 |
| 72.22 | 72.66 | 75.42 | 75.86 |
| 72.24 | 72.68 | 75.46 | 75.88 |
| 72.26 | 72.70 | 75.50 | 75.90 |
| 72.28 | 72.72 | 75.54 | 75.92 |
| 72.30 | 72.74 | 75.58 | 75.94 |
| 72.32 | 72.76 | 75.62 | 75.96 |
| 72.34 | 72.78 | 75.64 | 75.98 |

UHF Channels—State of Hawaii

| | | | | | |
|---------|------|---------|---------|------|---------|
| 488.250 | | 491.250 | 489.750 | | 492.750 |
| 488.750 | | 491.750 | 490.250 | | 493.250 |
| 489.250 | | 492.250 | 490.750 | | 493.750 |

(a) The 72–76 MHz channels may be assigned under developmental authority pursuant to the requirements of § 22.413. The 72–76 MHz channels may also be used in point-to-multipoint configurations. The 72–76 MHz channels are also allocated for assignment in the Private Radio Services (see part 90 of this chapter).

47 CFR Ch. I (10–1–05 Edition)

(b) [Reserved]

(c) Channels in the frequency ranges 488.250–490.750 and 491.250–493.750 MHz may be assigned only to inter-island fixed stations located in the State of Hawaii.

[59 FR 59507, Nov. 17, 1994; 60 FR 9889, Feb. 22, 1995, as amended at 70 FR 19309, Apr. 13, 2005]

§ 22.593 Effective radiated power limits.

The effective radiated power of fixed stations operating on the channels listed in § 22.591 must not exceed 150 Watts. The equivalent isotropically radiated power of existing fixed microwave stations (2110–2130 and 2160–2180 MHz) licensed under this part (pursuant to former rules) must not exceed the applicable limits set forth in § 101.113 of this chapter.

[70 FR 19309, Apr. 13, 2005]

§ 22.599 Assignment of 72–76 MHz channels.

Because of the potential for interference to the reception of TV Channels 4 and 5 by broadcast television sets and video recorders, assignments of the 72–76 MHz channels are subject to the following conditions:

(a) Assignments of 72–76 MHz channels for use within 129 kilometers (80 miles) of a full service TV station transmitting on TV Channel 4 or 5 are subject to the condition that the licensee must eliminate any interference caused to television reception on TV Channels 4 and 5. If the FCC notifies the licensee of an interference problem and the licensee does not resolve the problem within 90 days of such notification, operation of the interfering 72–76 MHz fixed station must be immediately discontinued.

(b) 72–76 MHz channels may be assigned for use within 16 kilometers (10 miles) of a full service TV station transmitting on TV Channel 4 or 5 under a developmental authorization, pursuant to § 22.413. However, for use within 50 meters (164 feet) of a TV station transmitting on TV Channel 4 or 5, 72–76 MHz channels may be assigned under a regular authorization, rather than a developmental authorization.