

TABLE 2.—COORDINATION DISTANCES FOR THE PROTECTED DEPARTMENT OF DEFENSE FACILITIES

1710–1755 MHz transmit operations	Coordination distance (km)
a. EIRP <=100 mW, antenna height <=1.6 m AG	35
b. EIRP <=1 W, antenna height <=10 m AG	55

(b) *Protection of non-DoD operations in the 1710–1755 MHz and 1755–1761 MHz bands.* Until such time as non-DoD systems operating in the 1710–1755 MHz and 1755–1761 MHz bands are relocated to other spectrum, AWS licensees shall protect such systems by satisfying the appropriate provisions of TIA Telecommunications Systems Bulletin 10–F, “Interference Criteria for Microwave Systems,” May, 1994 (TSB 10–F).

(c) *Protection of Federal Government operations below 1710 MHz.* AWS licensees operating fixed stations in the 1710–1755 MHz band, if notified that such stations are causing interference to radiosonde receivers operating in the Meteorological Aids Service in the 1675–1700 MHz band or a meteorological-satellite earth receiver operating in the

Meteorological-Satellite Service in the 1675–1710 MHz band, shall be required to modify the stations’ location and/or technical parameters as necessary to eliminate the interference.

(d) *Recognition of NASA Goldstone facility operations in the 2110–2120 MHz band.* The National Aeronautics and Space Administration (NASA) operates the Deep Space Network (DSN) in the 2110–2120 MHz band at Goldstone, California (see Table 3). NASA will continue its operations of high power transmitters (nominal EIRP of 105.5 dBW with EIRP up to 119.5 dBW used under emergency conditions) in this band at this location. AWS licensees must accept any interference received from the Goldstone DSN facility in this band.

TABLE 3.—LOCATION OF THE NASA GOLDSTONE DEEP SPACE FACILITY

Location	Coordinates	Maximum transmitter output power
Goldstone, California	35°18’ N 116°54’ W	500 kW

§ 27.1135 Protection of non-Federal Government Meteorological-Satellite operations.

AWS licensees operating fixed stations in the 1710–1755 MHz band, if notified that such stations are causing interference to meteorological-satellite earth receivers operating in the Meteorological-Satellite Service in the 1675–1710 MHz band, shall be required to modify the stations’ location and/or technical parameters as necessary to eliminate the interference.

Subpart M—Broadband Radio Service and Educational Broadband Service

SOURCE: 69 FR 72034, Dec. 10, 2004, unless otherwise noted.

§ 27.1200 Change to BRS and EBS.

(a) As of January 10, 2005, licensees assigned to the Multipoint Distribution Service (MDS) and the Multichannel Multipoint Distribution Service (MMDS) shall be reassigned to the Broadband Radio Service (BRS) and licensees in the Instructional Television Fixed Service (ITFS) shall be reassigned to the Educational Broadband Service (EBS).

§ 27.1201 EBS eligibility.

(a) With certain limited exceptions set forth in paragraph (c) of this section, a license for an Educational Broadband Service station will be issued only to an accredited institution