

partitioned area. If a licensee subsequently fails to meet its substantial service requirement, its license will be subject to automatic cancellation without further Commission action. Under the second option, the partitioner certifies that it has met or will meet the substantial service requirement for the entire, pre-partitioned geographic service area. If the partitioner subsequently fails to meet its substantial service requirement, only its license will be subject to automatic cancellation without further Commission action.

(2) *Disaggregation.* Parties to disaggregation agreements have two options for satisfying the construction requirements set forth in §27.14. Under the first option, the disaggregator and disaggregatee each certifies that it will share responsibility for meeting the substantial service requirement for the geographic service area. If the parties choose this option and either party subsequently fails to satisfy its substantial service responsibility, both parties' licenses will be subject to forfeiture without further Commission action. Under the second option, both parties certify either that the disaggregator or the disaggregatee will meet the substantial service requirement for the geographic service area. If the parties choose this option, and the party responsible subsequently fails to meet the substantial service requirement, only that party's license will be subject to forfeiture without further Commission action.

[62 FR 9658, Mar. 3, 1997, as amended at 63 FR 68954, Dec. 14, 1998; 65 FR 3146, Jan. 20, 2000; 65 FR 57268, Sept. 21, 2000; 67 FR 45373, July 9, 2002; 69 FR 5715, Feb. 6, 2004]

Subpart C—Technical Standards

§ 27.50 Power and antenna height limits.

(a) The following power limits apply to the 2305–2320 MHz and 2345–2360 MHz bands:

(1) Fixed, land, and radiolocation land stations transmitting are limited to 2000 watts peak equivalent isotropically radiated power (EIRP).

(2) Mobile and radiolocation mobile stations transmitting are limited to 20 watts EIRP peak power.

(b) The following power and antenna height limits apply to transmitters operating in the 746–764 MHz and 776–794 MHz bands:

(1) Fixed and base stations transmitting in the 746–764 MHz band and the 777–792 MHz band must not exceed an effective radiated power (ERP) of 1000 watts and an antenna height of 305 m height above average terrain (HAAT), except that antenna heights greater than 305 m HAAT are permitted if power levels are reduced below 1000 watts ERP in accordance with Table 1 of this section;

(2) Control stations and mobile stations transmitting in the 747–762 MHz band and the 776–794 MHz band and fixed stations transmitting in the 776–777 MHz band and the 792–794 MHz band are limited to 30 watts ERP;

(3) Portable stations (hand-held devices) transmitting in the 747–762 MHz band and the 776–794 MHz band are limited to 3 watts ERP;

(4) Maximum composite transmit power shall be measured over any interval of continuous transmission using instrumentation calibrated in terms of RMS-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, etc., so as to obtain a true maximum composite measurement for the emission in question over the full bandwidth of the channel.

(c) The following power and antenna height requirements apply to stations transmitting in the 698–746 MHz band:

(1) Fixed and base stations are limited to a maximum effective radiated power (ERP) of 50 kW, with the limitation on antenna heights as follows:

(i) Fixed and base stations with an ERP of 1000 watts or less must not exceed an antenna height of 305 m height above average terrain (HAAT) except when the power is reduced in accordance with Table 1 of this section;

(ii) The antenna height for fixed and base stations with an ERP greater than 1000 watts but not exceeding 50 kW is limited only to the extent required to satisfy the requirements of §27.55(b).

(2) Control and mobile stations are limited to 30 watts ERP.

(3) Portable stations (hand-held devices) are limited to 3 watts ERP.

(4) Maximum composite transmit power shall be measured over any interval of continuous transmission using instrumentation calibrated in terms of RMS-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, etc., so as to obtain a true maximum composite measurement for the emission in question over the full bandwidth of the channel.

(5) Licensees intending to operate a base or fixed station at a power level greater than 1 kW ERP must provide advanced notice of such operation to the Commission and to licensees authorized in their area of operation. Licensees that must be notified are all licensees authorized under this part to operate a base or fixed station on an adjacent spectrum block at a location within 75 km of the base or fixed station operating at a power level greater than 1 kW ERP. Notices must provide the location and operating parameters of the base or fixed station operating at a power level greater than 1 kW ERP, including the station's ERP, antenna coordinates, antenna height above ground, and vertical antenna pattern, and such notices must be provided at least 90 days prior to the commencement of station operation.

(d) The following power and antenna height requirements apply to stations transmitting in the 1710–1755 MHz and 2110–2155 MHz bands:

(1) The power of each fixed or base station transmitting in the 2110–2155 MHz band and located in any county with population density of 100 or fewer persons per square mile, based upon the most recently available population statistics from the Bureau of the Census, is limited to a peak equivalent isotropically radiated power (EIRP) of 3280 watts and a peak transmitter output power of 200 watts. The power of each fixed or base station transmitting in the 2110–2155 MHz band from any other location is limited to a peak EIRP of 1640 watts and a peak transmitter output power of 100 watts. A licensee operating a base or fixed station

utilizing a power of more than 1640 watts EIRP must coordinate such operations in advance with all Government and non-Government satellite entities in the 2025–2110 MHz band. Operations above 1640 watts EIRP must also be coordinated in advance with the following licensees within 120 kilometers (75 miles) of the base or fixed station: all Multipoint Distribution Service (MDS) licensees authorized under Part 21 in the 2155–2160 MHz band and all AWS licensees in the 2110–2155 MHz band.

(2) Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to a peak EIRP of 1 watt. Fixed stations operating in this band are limited to a maximum antenna height of 10 meters above ground, and mobile and portable stations must employ a means for limiting power to the minimum necessary for successful communications.

(e) The following power limits apply to the paired 1392–1395 MHz and 1432–1435 MHz bands as well as the unpaired 1390–1392 MHz band (1.4 GHz band):

(1) Fixed stations transmitting in the 1390–1392 MHz and 1432–1435 MHz bands are limited to 2000 watts EIRP peak power. Fixed stations transmitting in the 1392–1395 MHz band are limited to 100 watts EIRP peak power.

(2) Mobile stations transmitting in the 1390–1392 MHz and 1432–1435 MHz bands are limited to 4 watts EIRP peak power. Mobile stations transmitting in the 1392–1395 MHz band are limited to 1 watt EIRP peak power.

(f) The following power limits apply to the 1670–1675 MHz band:

(1) Fixed and base stations are limited to 2000 watts EIRP peak power.

(2) Mobile stations are limited to 4 watts EIRP peak power.

(g) [Reserved]

(h) The following power limits shall apply in the BRS and EBS:

(1) *Main, booster and base stations.*

(i) The maximum EIRP of a main, booster or base station shall not exceed 33 dBW + 10log(X/Y) dBW, where X is the actual channel width in MHz and Y is either 6 MHz if prior to transition or the station is in the MBS following transition or 5.5 MHz if the station is

§ 27.51

47 CFR Ch. I (10–1–05 Edition)

in the LBS and UBS following transition, except as provided in paragraph (h)(1)(ii) of this section.

(ii) If a main or booster station sectorizes or otherwise uses one or more transmitting antennas with a non-omnidirectional horizontal plane radiation pattern, the maximum EIRP in dBW in a given direction shall be determined by the following formula: $EIRP = 33 \text{ dBW} + 10 \log(X/Y) \text{ dBW} + 10 \log(360/\text{beamwidth}) \text{ dBW}$, where X is the actual channel width in MHz, Y is either (i) 6 MHz if prior to transition or the station is in the MBS following transition or (ii) 5.5 MHz if the station is in the LBS and UBS following transition, and beamwidth is the total horizontal plane beamwidth of the individual transmitting antenna for the station or any sector measured at the half-power points.

(2) *Mobile and other user stations.* Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

(3) For television transmission, the peak power of the accompanying aural signal must not exceed 10 percent of the peak visual power of the transmitter. The Commission may order a reduction in aural signal power to diminish the potential for harmful interference.

(4) For main, booster and response stations utilizing digital emissions with non-uniform power spectral density (e.g. unfiltered QPSK), the power measured within any 100 kHz resolution bandwidth within the 6 MHz channel occupied by the non-uniform emission cannot exceed the power permitted within any 100 kHz resolution bandwidth within the 6 MHz channel if it were occupied by an emission with uniform power spectral density, i.e., if the maximum permissible power of a station utilizing a perfectly uniform power spectral density across a 6 MHz channel were 2000 watts EIRP, this would result in a maximum permissible power flux density for the station of $2000/60 = 33.3$ watts EIRP per 100 kHz bandwidth. If a non-uniform emission were substituted at the station, station power would still be limited to a maximum of 33.3 watts EIRP within any 100 kHz segment of the 6 MHz channel, irrespective of the fact that this would

result in a total 6 MHz channel power of less than 2000 watts EIRP.

(i) Peak transmit power shall be measured over any interval of continuous transmission using instrumentation calibrated in terms of rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

TABLE 1—PERMISSIBLE POWER AND ANTENNA HEIGHTS FOR BASE AND FIXED STATIONS IN THE 698–764 MHz AND 777–792 MHz BANDS

Antenna height (AAT) in meters (feet)	Effective radiated power (ERP) (watts)
Above 1372 (4500)	65
Above 1220 (4000) To 1372 (4500)	70
Above 1067 (3500) To 1220 (4000)	75
Above 915 (3000) To 1067 (4000)	100
Above 763 (2500) To 915 (3000)	140
Above 610 (2000) To 763 (2500)	200
Above 458 (1500) To 610 (2000)	350
Above 305 (1000) To 458 (1500)	600
Up to 305 (1000)	1000

[62 FR 16497, Apr. 7, 1997, as amended at 65 FR 3147, Jan. 20, 2000; 65 FR 17602, Apr. 4, 2000; 65 FR 42882, July 12, 2000; 65 FR 57267, Sept. 21, 2000; 67 FR 5511, Feb. 6, 2002; 67 FR 41855, June 20, 2002; 69 FR 5715, Feb. 6, 2004; 69 FR 72033, Dec. 10, 2004; 69 FR 75172, Dec. 15, 2004; 69 FR 77950, Dec. 29, 2004; 70 FR 1190, Jan. 6, 2005]

§ 27.51 Equipment authorization.

(a) Each transmitter utilized for operation under this part must be of a type that has been authorized by the Commission under its certification procedure.

(b) Any manufacturer of radio transmitting equipment to be used in these services may request equipment authorization following the procedures set forth in subpart J of part 2 of this chapter. Equipment authorization for an individual transmitter may be requested by an applicant for a station authorization by following the procedures set forth in part 2 of this chapter.

[65 FR 3147, Jan. 20, 2000]