

§ 27.52 RF safety.

Licensees and manufacturers are subject to the radio frequency radiation exposure requirements specified in sections 1.1307(b), 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of mobile or portable devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

§ 27.53 Emission limits.

(a) For operations in the bands 2305–2320 MHz and 2345–2360 MHz, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by the following amounts:

(1) *For fixed, land, and radiolocation land stations:* By a factor not less than $80 + 10 \log (p)$ dB on all frequencies between 2320 and 2345 MHz;

(2) *For mobile and radiolocation mobile stations:* By a factor not less than $110 + 10 \log (p)$ dB on all frequencies between 2320 and 2345 MHz;

(3) *For fixed, land, mobile, radiolocation land and radiolocation mobile stations:* By a factor not less than $70 + 10 \log (p)$ dB on all frequencies below 2300 MHz and on all frequencies above 2370 MHz; and not less than $43 + 10 \log (p)$ dB on all frequencies between 2300 and 2320 MHz and on all frequencies between 2345 and 2370 MHz that are outside the licensed bands of operation;

(4) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or less, but at least one percent of the emission bandwidth of the fundamental emission of the transmitter, provided the measured energy is integrated over a 1 MHz bandwidth;

(5) In complying with the requirements in § 27.53(a)(1) and § 27.53(a)(2), WCS equipment that uses opposite sense circular polarization from that used by Satellite DARS systems in the 2320–2345 MHz band shall be permitted an allowance of 10 dB;

(6) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the edges, both upper and lower, of the licensee's bands of operation as the design permits;

(7) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power;

(8) Waiver requests of any of the out-of-band emission limits in paragraphs (a)(1) through (a)(7) of this section shall be entertained only if interference protection equivalent to that afforded by the limits is shown;

(9) In the 2305–2315 MHz band, if portable devices comply with all of the following requirements, then paragraph (a)(2) of this section shall not apply to portable devices, which instead shall attenuate all emissions into the 2320–2345 MHz band by a factor of not less than $93 + 10 \log (p)$ dB:

(i) The portable device has a duty cycle of 12.5% or less, with at most a 312.5 microsecond pulse every 2.5 milliseconds;

(ii) The portable device must employ time division multiple access (TDMA) technology;

(iii) The nominal peak transmit output power of the portable device is no more than 200 milliwatts (25 milliwatts average power);

(iv) The portable device operates with the minimum power necessary for successful communications;

(v) The nominal average base station transmit output power is no more than 800 milliwatts when the base station antennas is located at a height of at least 8 meters (26.25 feet) above the ground;

(vi) Only fixed and portable devices and services may be provided; vehicle-mounted units are not permitted; and

(vii) Transmitting antennas shall employ linear polarization or another polarization that provides equivalent of better discrimination with respect to a DARS antenna;

(10) The out-of-band emissions limits in paragraphs (a)(1) through (a)(9) of this section may be modified by the private contractual agreement of all affected licensees, who shall maintain a copy of the agreement in their station files and disclose it to prospective