

§ 960.4-2-2

emplacement ground-water travel time from the disturbed zone to the accessible environment is expected to be less than 1,000 years along any pathway of likely and significant radionuclide travel.

§ 960.4-2-2 Geochemistry.

(a) *Qualifying condition.* The present and expected geochemical characteristics of a site shall be compatible with waste containment and isolation. Considering the likely chemical interactions among radionuclides, the host rock, and the ground water, the characteristics of and the processes operating within the geologic setting shall permit compliance with (1) the requirements specified in § 960.4-1 for radionuclide releases to the accessible environment and (2) the requirements specified in 10 CFR 60.113 for radionuclide releases from the engineered-barrier system using reasonably available technology.

(b) *Favorable conditions.* (1) The nature and rates of the geochemical processes operating within the geologic setting during the Quaternary Period would, if continued into the future, not affect or would favorably affect the ability of the geologic repository to isolate the waste during the next 100,000 years.

(2) Geochemical conditions that promote the precipitation, diffusion into the rock matrix, or sorption of radionuclides; inhibit the formation of particulates, colloids, inorganic complexes, or organic complexes that increase the mobility of radionuclides; or inhibit the transport of radionuclides by particulates, colloids, or complexes.

(3) Mineral assemblages that, when subjected to expected repository conditions, would remain unaltered or would alter to mineral assemblages with equal or increased capability to retard radionuclide transport.

(4) A combination of expected geochemical conditions and a volumetric flow rate of water in the host rock that would allow less than 0.001 percent per year of the total radionuclide inventory in the repository at 1,000 years to be dissolved.

(5) Any combination of geochemical and physical retardation processes that would decrease the predicted peak cu-

10 CFR Ch. III (1-1-06 Edition)

mulative releases of radionuclides to the accessible environment by a factor of 10 as compared to those predicted on the basis of ground-water travel time without such retardation.

(c) *Potentially adverse conditions.* (1) Ground-water conditions in the host rock that could affect the solubility or the chemical reactivity of the engineered-barrier system to the extent that the expected repository performance could be compromised.

(2) Geochemical processes or conditions that could reduce the sorption of radionuclides or degrade the rock strength.

(3) Pre-waste-emplacement ground-water conditions in the host rock that are chemically oxidizing.

§ 960.4-2-3 Rock characteristics.

(a) *Qualifying condition.* The present and expected characteristics of the host rock and surrounding units shall be capable of accommodating the thermal, chemical, mechanical, and radiation stresses expected to be induced by repository construction, operation, and closure and by expected interactions among the waste, host rock, ground water, and engineered components. The characteristics of and the processes operating within the geologic setting shall permit compliance with (1) the requirements specified in § 960.4-1 for radionuclide releases to the accessible environment and (2) the requirements set forth in 10 CFR 60.113 for radionuclide releases from the engineered-barrier system using reasonably available technology.

(b) *Favorable Conditions.* (1) A host rock that is sufficiently thick and laterally extensive to allow significant flexibility in selecting the depth, configuration, and location of the underground facility to ensure isolation.

(2) A host rock with a high thermal conductivity, a low coefficient of thermal expansion, or sufficient ductility to seal fractures induced by repository construction, operation, or closure or by interactions among the waste, host rock, ground water, and engineered components.

(c) *Potentially adverse conditions.* (1) Rock conditions that could require engineering measures beyond reasonably

available technology for the construction, operation, and closure of the repository, if such measures are necessary to ensure waste containment or isolation.

(2) Potential for such phenomena as thermally induced fractures, the hydration or dehydration of mineral components, brine migration, or other physical, chemical, or radiation-related phenomena that could be expected to affect waste containment or isolation.

(3) A combination of geologic structure, geochemical and thermal properties, and hydrologic conditions in the host rock and surrounding units such that the heat generated by the waste could significantly decrease the isolation provided by the host rock as compared with pre-waste-emplacment conditions.

§ 960.4-2-4 Climatic changes.

(a) *Qualifying condition.* The site shall be located where future climatic conditions will not be likely to lead to radionuclide releases greater than those allowable under the requirements specified in § 960.4-1. In predicting the likely future climatic conditions at a site, the DOE will consider the global, regional, and site climatic patterns during the Quaternary Period, considering the geomorphic evidence of the climatic conditions in the geologic setting.

(b) *Favorable conditions.* (1) A surface-water system such that expected climatic cycles over the next 100,000 years would not adversely affect waste isolation.

(2) A geologic setting in which climatic changes have had little effect on the hydrologic system throughout the Quaternary Period.

(c) *Potentially adverse conditions.* (1) Evidence that the water table could rise sufficiently over the next 10,000 years to saturate the underground facility in a previously unsaturated host rock.

(2) Evidence that climatic changes over the next 10,000 years could cause perturbations in the hydraulic gradient, the hydraulic conductivity, the effective porosity, or the ground-water flux through the host rock and the surrounding geohydrologic units, sufficient to significantly increase the

transport of radionuclides to the accessible environment.

§ 960.4-2-5 Erosion.

(a) *Qualifying condition.* The site shall allow the underground facility to be placed at a depth such that erosional processes acting upon the surface will not be likely to lead to radionuclide releases greater than those allowable under the requirements specified in § 960.4-1. In predicting the likelihood of potentially disruptive erosional processes, the DOE will consider the climatic, tectonic, and geomorphic evidence of rates and patterns of erosion in the geologic setting during the Quaternary Period.

(b) *Favorable conditions.* (1) Site conditions that permit the emplacement of waste at a depth of at least 300 meters below the directly overlying ground surface.

(2) A geologic setting where the nature and rates of the erosional processes that have been operating during the Quaternary Period are predicted to have less than one chance in 10,000 over the next 10,000 years of leading to releases of radionuclides to the accessible environment.

(3) Site conditions such that waste exhumation would not be expected to occur during the first one million years after repository closure.

(c) *Potentially adverse conditions.* (1) A geologic setting that shows evidence of extreme erosion during the Quaternary Period.

(2) A geologic setting where the nature and rates of geomorphic processes that have been operating during the Quaternary Period could, during the first 10,000 years after closure, adversely affect the ability of the geologic repository to isolate the waste.

(d) *Disqualifying condition.* The site shall be *disqualified* if site conditions do not allow all portions of the underground facility to be situated at least 200 meters below the directly overlying ground surface.

§ 960.4-2-6 Dissolution.

(a) *Qualifying condition.* The site shall be located such that any subsurface rock dissolution will not be likely to lead to radionuclide releases greater