

(d) A certification record of such examinations and tests made in compliance with the requirements of paragraphs (a) and (b) of this section shall be maintained. The certification record shall include the date of examinations and tests, the signature of the person who performed the examinations or tests and the serial number, or other identifier, of the equipment examined and tested.

[47 FR 16986, Apr. 20, 1982, as amended at 51 FR 34562, Sept. 29, 1986; 67 FR 44545, July 3, 2002]

§ 1915.173 Drums and containers.

(a) Shipping drums and containers shall not be pressurized to remove their contents.

(b) A temporarily assembled pressurized piping system conveying hazardous liquids or gases shall be provided with a relief valve and by-pass to prevent rupture of the system and the escape of such hazardous liquids or gases.

(c) Pressure vessels, drums and containers containing toxic or flammable liquids or gases shall not be stored or used where they are subject to open flame, hot metal, or other sources of artificial heat.

(d) Unless pressure vessels, drums and containers of 30 gallon capacity or over containing flammable or toxic liquids or gases are placed in an out-of-the-way area where they will not be subject to physical injury from an outside source, barriers or guards shall be erected to protect them from such physical injury.

(e) Containers of 55 gallons or more capacity containing flammable or toxic liquid shall be surrounded by dikes or pans which enclose a volume equal to at least 35 percent of the total volume of the containers.

(f) Fire extinguishers adequate in number and suitable for the hazard shall be provided. These extinguishers shall be located in the immediate area where pressure vessels, drums and containers containing flammable liquids or gases are stored or in use. Such extinguishers shall be ready for use at all times.

Subpart L—Electrical Machinery

§ 1915.181 Electrical circuits and distribution boards.

(a) The provisions of this section shall apply to ship repairing and shipbuilding and shall not apply to shipbreaking.

(b) Before an employee is permitted to work on an electrical circuit, except when the circuit must remain energized for testing and adjusting, the circuit shall be deenergized and checked at the point at which the work is to be done to insure that it is actually deenergized. When testing or adjusting an energized circuit a rubber mat, duck board, or other suitable insulation shall be used underfoot where an insulated deck does not exist.

(c) Deenergizing the circuit shall be accomplished by opening the circuit breaker, opening the switch, or removing the fuse, whichever method is appropriate. The circuit breaker, switch, or fuse location shall be tagged to indicate that an employee is working on the circuit. Such tags shall not be removed nor the circuit energized until it is definitely determined that the work on the circuit has been completed.

(d) When work is performed immediately adjacent to an open-front energized board or in back of an energized board, the board shall be covered or some other equally safe means shall be used to prevent contact with any of the energized parts.

[47 FR 16986, Apr. 20, 1982, as amended at 67 FR 44545, July 3, 2002]

Subparts M–O [Reserved]

Subpart P—Fire Protection in Shipyard Employment

SOURCE: 69 FR 55702, Sept. 15, 2004, unless otherwise noted.

§ 1915.501 General provisions.

(a) *Purpose.* The purpose of the standard in this subpart is to require employers to protect all employees from fire hazards in shipyard employment, including employees engaged in fire response activities.

(b) *Scope.* This subpart covers employers with employees engaged in