

(4) Railings shall conform to the requirements of §1917.112(c)(1). If balusters are used, there shall be a minimum of one per tread. Handrails shall be a minimum of 1¼ inches (3.18 cm) in outside diameter; and

(5) Vertical clearance shall be at least 6 feet, 6 inches (1.98 m) above the top step.

(c) *Maintenance.* Spiral stairways shall be maintained in safe condition.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997; 65 FR 40942, June 30, 2000]

§ 1917.122 Employee exits.

(a) Employee exits shall be clearly marked.

(b) If an employee exit is not visible from employees' work stations, directional signs indicating routes to the exit shall be posted.

(c) Exits shall be readily accessible and sufficient in number to provide employees with a convenient means of escape in emergencies. A clear passage to the exit shall be maintained.

(d) The minimum width of any employee exit shall be 28 inches (71.12 cm).

[48 FR 30909, July 5, 1983, as amended at 65 FR 40942, June 30, 2000]

§ 1917.123 Illumination.⁹

(a) Working and walking areas shall be illuminated. Unless conditions described in the regulations of the United States Coast Guard (33 CFR 126.15(1) and (n), and 33 CFR 154.570) exist in the case of specific operations, illumination in active work areas (for example, cargo transfer points) shall be of an average minimum light intensity of 5 foot-candles. The illumination in other work areas (for example, farm areas) shall be of an average minimum light intensity of 1 foot-candle except for security purposes when a minimum light intensity of ½ foot-candle shall be maintained. Where occasional work tasks require more light than that which is consistently and permanently provided, supplemental lighting shall be used.

⁹The United States Coast Guard, at 33 CFR 126.15(1) and (n), and 33 CFR 154.570 sets out requirements for illumination at "designated waterfront facilities" and "large oil transfer facilities."

(b) The lighting intensity shall be measured at the task/working surface, in the plane in which the task/working surface is present.

(c) Lights shall, so far as possible, be placed so that they will not shine in the eyes of employees.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.124 Dockboards (car and bridge plates).

(a) *General.* The employer shall provide safe means of passage between different surface levels and across openings.

(b) [Reserved]

(c) *Dockboards (car and bridge plates).*

(1) Dockboards shall be strong enough to support the loads imposed on them.

(2) Portable dockboards shall be anchored in position or be equipped with devices to prevent their movement.

(3) Hand holds or other effective means shall be provided on portable dockboards to permit safe handling.

(4) Positive means shall be used to prevent railcars or highway vehicles from being moved while dockboards or bridge plates are in position.

(5) Be designed, constructed, and maintained to prevent vehicles from running off the edge.¹⁰

(6) Dockboards shall be well maintained.

(d) *Ramps.* (1) Ramps shall be strong enough to support the loads imposed on them and be designed, constructed, and maintained to prevent vehicles from running off the edge.¹¹

(2) Ramps shall be equipped with a guardrail meeting the requirement of §1917.112(c)(1) if the slope is more than 20 degrees to the horizontal or if employees could fall more than 4 feet (1.22 m).

(3) Ramps shall have slip-resistant surfaces.

¹⁰When the gap to be bridged to greater than 36 inches (.91 m), an acceptable means of preventing vehicles from running off the edge is a minimum side board height of two and three-quarter inches.

¹¹When the gap to be bridged is greater than 36 inches (.91 m), an acceptable means of preventing vehicles from running off the edge is a minimum side board height of two and three-quarter inches.

§ 1917.125

(4) When necessary to prevent displacement by vehicle wheels, steel plates or similar devices used to temporarily bridge or cover uneven surfaces or tracks, shall be anchored.

(5) Ramps shall be well maintained.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997; 65 FR 40942, June 30, 2000]

§ 1917.125 Guarding temporary hazards.

Ditches, pits, excavations and surfaces in poor repair shall be guarded by readily visible barricades, rails or other equally effective means.

§ 1917.126 River banks.

(a) This section applies to temporary installations or temporary operations near a river bank.

(b) Where working surfaces at river banks slope so steeply that an employee could slip or fall into the water, the outer perimeter of the working surface shall be protected by posting or other portable protection such as roping off. In these situations, employees must wear a personal flotation device meeting the requirements of § 1917.95(b).

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.127 Sanitation.

(a) *Washing and toilet facilities.* (1) The employer shall provide accessible washing and toilet facilities sufficient for the sanitary requirements of employees. The facilities shall have:

(i) Running water, including hot and cold or tepid water at a minimum of one accessible location (when cargo handling is conducted at locations without permanent facilities, potable water may be provided in lieu of running water);

(ii) Soap;

(iii) Individual hand towels, clean individual sections of continuous towel-eling or warm air blowers; and

(iv) Fixed or portable toilets in separate compartments with latch-equipped doors. Separate toilet facilities shall be provided for male and female employees except when toilet rooms will be occupied by only one person at a time.

29 CFR Ch. XVII (7-1-06 Edition)

(2) Washing and toilet facilities shall be regularly cleaned and maintained in good order.

(b) *Drinking water.* (1) Potable drinking water shall be accessible to employees at all times.

(2) Potable drinking water containers shall be clean, containing only water and ice, and shall be fitted with covers.

(3) Common drinking cups are prohibited.

(c) *Prohibited eating areas.* Consumption of food or beverages in areas where hazardous materials are being stored or handled shall be prohibited.

(d) *Garbage and overboard discharges.* Work shall not be conducted in the immediate vicinity of uncovered garbage or in the way of overboard discharges from the vessel's sanitary lines unless employees are protected from the garbage or discharge by a baffle or splash boards.

§ 1917.128 Signs and marking.

(a) *General.* Signs required by this part shall be clearly worded and legible, and shall contain a key word or legend indicating the reason for the sign.

(1) Key words are such words as Danger, Warning, Caution.

(2) Legends are more specific explanations such as High Voltage, Close Clearance, Pedestrian Crossing.

(b) *Specific.* Every marine terminal shall have conspicuously posted signs as follows:

(1) Locations of first aid facilities;

(2) Locations of telephones;

(3) Telephone numbers of the closest ambulance service, hospital or other source of medical attention, police, fire department, and emergency squad (if any); and

(4) Locations of firefighting and emergency equipment and fire exits.

Subpart G—Related Terminal Operations and Equipment

§ 1917.151 Machine guarding.

(a) *Definition.* “Guarded” means shielded, fenced, or enclosed by covers, casings, shields, troughs, spillways or railings, or guarded by position or location. Examples of guarding methods are guarding by location (positioning