

## § 1917.51

one month early without effect on subsequent due dates.

(2) When certificated equipment is out of service for 6 months or more beyond the due date of a certification inspection, an examination equivalent to an initial certification, including unit proof load test, shall be performed before the equipment re-enters service.

(h) Loose gear obtained after October 3, 1983 shall bear a legible mark indicating that it has been tested (see paragraph(c)(6) of this section). Single sheave blocks shall be marked with safe working loads and proof test loads. Marks relating to testing shall be identifiable on the related certificates, which shall be available.

(i) *Safe working load.* (1) The safe working load of gear as specified in this section shall not be exceeded.

(2) All cargo handling gear provided by the employer with a safe working load greater than five short tons (10,000 lbs. or 4.54 metric tons) shall have its safe working load plainly marked on it.

(j) *Exceptions:* The certification requirements of this section do not apply to the following equipment:

(1) Small industrial crane trucks as described on page 8 and illustrated on page 13 of ASME B56.1, 1959, "Safety Code for Powered Industrial Trucks", and powered industrial trucks;

(2) Any straddle truck not capable of straddling two or more intermodal containers 16 feet (4.88 m) in width; and

(3) Gear used only for handling or holding hoses, handling ship's stores or handling the gangway.

[48 FR 30909, July 5, 1983, as amended at 49 FR 28551, July 13, 1984; 61 FR 5509, Feb. 13, 1996; 62 FR 40200, July 25, 1997; 64 FR 61506, Nov. 12, 1999; 65 FR 40940, June 30, 2000]

### § 1917.51 Hand tools.

(a) Hand tools used by employees shall be maintained in safe operating condition.

(b)(1) Hand-held portable electric tools shall be equipped with switches that must be manually held in a closed position to operate the tool.

(2) Portable power-driven circular saws shall be equipped with guards above and below the base plate or shoe. The upper guard shall cover the saw to the depth of the teeth, except for the minimum arc needed to permit the

## 29 CFR Ch. XVII (7-1-06 Edition)

base to be tilted for bevel cuts. The lower guard shall cover the saw to the depth of the teeth, except for the minimum arc needed to allow proper retraction and contact with the work. When the tool is withdrawn from the work, the lower guard shall automatically and instantly return to the covering position.

(c) Only cutting tools shall be used to cut metal strapping or banding used to secure cargo.

## Subpart D—Specialized Terminals

### § 1917.70 General.

The provisions of this subpart D shall apply to specialized terminals in addition to any other applicable requirements of this part.

### § 1917.71 Terminals handling intermodal containers or roll-on roll-off operations.

(a) Every intermodal container shall be legibly and permanently marked with:

(1) The weight of the container when empty, in pounds;

(2) The maximum cargo weight the container is designed to carry, in pounds; and

(3) The sum of the weight of the container and the cargo, in pounds.

(b) No container shall be hoisted by any crane or derrick unless the following conditions have been met:

(1) The employer shall ascertain from the carrier whether a container to be hoisted is loaded or empty. Empty containers shall be identified before loading or discharge in such a manner as will inform every supervisor and foreman on the site and in charge of loading or discharging, or every crane or other hoisting equipment operator and signalman, if any, that such container is empty. Methods of identification may include cargo plans, manifests or markings on the container.

(2) In the case of a loaded container:

(i) The actual gross weight shall be plainly marked so as to be visible to the crane or other hoisting equipment operator or signalman, or to every supervisor and foreman on the site and in charge of the operation; or

(ii) The cargo stowage plan or equivalent permanently recorded display

servicing the same purpose, containing the actual gross weight and the serial number or other positive identification of that specific container, shall be provided to the crane or other hoisting equipment operator and signalman, if any, and to every supervisor and foreman on the site and in charge of the operation.

(3) Every outbound loaded container which is received at a marine terminal ready to load aboard a vessel without further consolidation or loading shall be weighed to obtain the actual gross weight, either at the terminal or elsewhere, before being hoisted.

(4)(i) When container weighing scales are located at a marine terminal, any outbound container with a load consolidated at that terminal shall be weighed to obtain an actual weight before being hoisted.

(ii) If the terminal has no scales, the actual gross weight may be calculated on the basis of the container's contents and the container's empty weight. The weights used in the calculation shall be posted conspicuously on the container, with the name of the person making the calculation and the date.

(5) Open type vehicle carrying containers and those built specifically and used solely for the carriage of compressed gases are excepted from paragraphs (b)(3) and (b)(4) of this section.

(6) Closed dry van containers carrying vehicles are exempted from paragraph (b)(4) of this section provided that:

(i) The container carries only completely assembled vehicles and no other cargo;

(ii) The container is marked on the outside in such a manner that an employee can readily discern that the container is carrying vehicles; and

(iii) The vehicles were loaded into the container at the marine terminal.

(7) The weight of loaded inbound containers from foreign ports shall be determined by weighing or by the method of calculation described in paragraph (b)(4)(ii) of this section or by shipping documents.

(8) Any scale used within the United States to weigh containers for the purpose of the requirements of this section shall meet the accuracy standards of

the state or local public authority in which the scale is located.

(c) No container or containers shall be hoisted if their actual gross weight exceeds the weight marked as required in paragraph (a)(2) of this section, or if it exceeds the capacity of the crane or other hoisting device intended to be used.

(d)(1) Marked or designated areas shall be set aside within a container or roll-on roll-off terminal for passage of employees to and from active cargo transfer points, except where transportation to and from those points is provided by the employer.

(2) The employer shall direct employees to stay clear of the area beneath a suspended container.

(e) Each employee working in the immediate area of container handling equipment or in the terminal's traffic lanes shall wear a high visibility vest (or equivalent protection).<sup>7</sup>

NOTE TO PARAGRAPH (e): High visibility vests or equivalent protection means high visibility/retro-reflective materials which are intended to make the user clearly visible by day through the use of high visibility (fluorescent) material and in the dark by vehicle headlights through the use of retro-reflective material. For example, an acceptable area of material for a vest or equivalent protection is .5 m<sup>2</sup> (760 in.<sup>2</sup>) for fluorescent (background) material and .13m<sup>2</sup> (197 in.<sup>2</sup>) for retro-reflective material. Vests or equivalent protection, such as high visibility/retro-reflective coveralls, that are available for industrial use, may also be acceptable.

(f) Containers shall be handled using lifting fittings or other arrangements suitable and intended for the purpose as set forth in paragraphs (f)(1) through (f)(4) of this section, unless damage to an intermodal container makes special means of handling necessary.

(1) Loaded intermodal containers of 20 feet (6.1 m) or more in length shall be hoisted as follows:

(i) When hoisting containers by the top fittings, the lifting forces shall be applied vertically from at least four such fittings. A less than vertical lift is permitted only under the following conditions:

<sup>7</sup>Decals on hard hats will not be considered equivalent protection for the purposes of this paragraph.

## § 1917.73

(A) The container being lifted is an ISO closed box container;

(B) The condition of the box is sound;

(C) The speed of hoisting and lowering is moderated when heavily laden containers<sup>8</sup> are encountered;

(D) The lift angle is at 80 to 90 degrees;

(E) The distance between the lifting beam and the load is at least 8 feet and 2.4 inches (2.5 m); and

(F) The length of the spreader beam is at least 16.3 feet (5 m) for a 20-foot container, and at least 36.4 feet (11.1 m) for a 40-foot container.

(ii) If hoisted from bottom fittings, the hoisting connections shall bear on the fittings only, making no other contact with the container. The angles of the four bridle legs shall not be less than 30° to the horizontal in the case of 40 foot (12.2 m) containers, 37° in the case of 30 foot (9.1 m) containers, and 45° in the case of 20 foot (6.1 m) containers.

(iii) Lifting containers by fork lift trucks or by grappling arms from above or from one side may be done only if the container is designed for this type of handling.

(iv) Other means of hoisting may be used only if the containers and hoisting means are designed for such use.

(2)(i) When using intermodal container spreaders that employ lanyards for activation of load disengagement, all possible precautions shall be taken to prevent accidental release of the load.

(ii) Intermodal container spreader twistlock systems shall be designed and used so that a suspended load cannot accidentally be released.

(3) Flat bed trucks or container chassis used to move intermodal containers shall be equipped with pins, flanges, or other means to prevent the container from shifting.

(4) After July 27, 1998, flat bed, low boy trailers (mafis) and other similar equipment used to transport containers shall be marked with their cargo capacities and shall not be overloaded.

(5) Each tractor shall have all brake air lines connected when pulling trail-

<sup>8</sup>A heavily laden container is one that is loaded to within 20 percent of its rated capacity.

## 29 CFR Ch. XVII (7-1-06 Edition)

ers equipped with air brakes and shall have the brakes tested before commencing operations.

(g)(1) Intermodal containers shall be inspected for defects in structural members or fittings before handling.

(2) Any intermodal container found to be unsafe shall be identified as such, promptly removed from service and repaired before being returned to service.

(h) Containers shall not be hoisted unless all engaged chassis twist locks are released.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40200, July 25, 1997; 65 FR 40940, June 30, 2000]

### **§ 1917.73 Terminal facilities handling menhaden and similar species of fish (see also § 1917.2, definition of hazardous cargo, material, substance or atmosphere).**

(a)(1) Tanks in terminal areas used for receiving or storing ballwater for recirculating into vessel holds in discharging operations shall be opened or ventilated to minimize contamination of water circulated to the vessel. Ballwater tanks shall be thoroughly drained upon completion of each day's operations and shall be left open to the air. Drainage is unnecessary when ballwater has been treated to remove hydrogen sulfide-producing contaminants and the efficiency of such treatment has been established by the employer.

(2) Before employees enter a dock tank, it shall first be drained, rinsed and tested for hydrogen sulfide and oxygen deficiency. Employees shall not enter the tank when the hydrogen sulfide level exceeds 20 ppm or oxygen content is less than 19.5 percent, except in emergencies.

(3) Tests shall be conducted by designated personnel with suitable test equipment and respiratory protective equipment complying with the provisions of § 1910.134 of this chapter.

(b) Pipelines and hoses on the dock or terminal used for receiving and circulating used ballwater shall be completely drained upon completion of each day's operation and left open to the air.

(c) At least four units of respiratory protective equipment consisting of supplied-air respirators or self-contained