

breathing apparatus complying with the requirements of §1910.134 of this chapter shall be available in a suitably labeled cabinet for immediate use in case of emergency caused by oxygen deficiency or hydrogen sulfide. Any employee entering a tank in an emergency shall, in addition to respiratory protective equipment, wear a lifeline and safety harness to facilitate rescue. At least two other employees, similarly equipped, shall be continuously stationed outside the tank to observe and to provide rescue services.

(d) The plant superintendent and foremen shall be trained and knowledgeable about the hazards of hydrogen sulfide and oxygen deficiency. They shall be trained in the use of appropriate respiratory and other protective equipment, and in rescue procedures. Other supervisory plant personnel shall be informed of these hazards and instructed in the necessary safety measures, including use of respiratory and rescue equipment.

(e) Supervisory personnel shall be on hand at dockside to supervise discharging of ballwater from vessels.

[48 FR 30909, July 5, 1983, as amended at 65 FR 40940, June 30, 2000]

Subpart E—Personal Protection

§ 1917.91 Eye and face protection.

(a)(1) The employer shall ensure that each affected employee uses appropriate eye and/or face protection where there are exposures to eye and/or face hazards. Such equipment shall comply with American National Standards Institute, ANSI Z-87.1-1989, "Practice for Occupational and Educational Eye and Face Protection."

(2) For employees wearing corrective spectacles, eye protection equipment required by paragraph (a)(1) of this section must be of a type which can be worn over spectacles. Prescription ground safety lenses may be substituted if they provide equivalent protection.

(3) For additional requirements covering eye protection against radiant energy, see §1917.152(h).

(b) Eye protection equipment shall be maintained in good condition.

(c) Used eye protection equipment shall be cleaned and disinfected before reissuance to another employee.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.92 Respiratory protection.

(See § 1917.1(a)(2)(x)).

[65 FR 40941, June 30, 2000]

§ 1917.93 Head protection.

(a) The employer shall ensure that each affected employee wears a protective helmet when working in areas where there is a potential for injury to the head from falling objects.

(b) Such equipment shall comply with American National Standards Institute, ANSI Z-89.1-1986, "Personnel Protection-Protective Headwear for Industrial Workers-Requirements."

(c) Protective hats previously worn shall be cleaned and disinfected before issuance by the employer to another employee.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997]

§ 1917.94 Foot protection.

(a) The employer shall ensure that each affected employee wears protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects or objects piercing the sole.

(b) Such equipment shall comply with American National Standards

Institute, ANSI Z-41-1991, "American National Standard for Personal Protection-Protective Footwear."

[62 FR 40201, July 25, 1997]

§ 1917.95 Other protective measures.

(a) *Protective clothing.* (1) Employees performing work that requires special protective clothing shall be directed by the employer to wear the necessary special protective clothing.

(2) When necessary, protective clothing previously worn shall be cleaned and disinfected before reissuance.

(b) *Personal flotation devices (PFDs).* (1) The employer shall provide, and shall direct the wearing of PFDs for those employees, such as line handlers, who are engaged in work in which they may be pulled into the water:

§ 1917.111

(i) When such employees are working in isolation, or

(ii) Where physical limitations of available working space creates a hazard of falling into the water, or

(iii) Where the work area is obstructed by cargo or other obstacles so as to prevent employees from obtaining safe footing for their work.

(2) PFDs (life preservers, life jackets, or work vests) worn by each affected employee must be United States Coast Guard (USCG) approved pursuant to 46 CFR part 160 (Type I, II, III, or V PFD) and marked for use as a work vest, for commercial use, or for use on vessels.

(3) Personal flotation devices shall be maintained in safe condition and shall be considered unserviceable when damaged so as to affect buoyancy or fastening capability.

(c) *Emergency facilities.* When employees are exposed to hazardous substances which may require emergency bathing, eye washing or other facilities, the employer shall provide such facilities and maintain them in good working order.

[48 FR 30909, July 5, 1983, as amended at 62 FR 40201, July 25, 1997; 65 FR 40941, June 30, 2000]

Subpart F—Terminal Facilities

§ 1917.111 Maintenance and load limits.

(a) The structural integrity of docks, piers, wharves, terminals and working surfaces shall be maintained.

(b) Maximum safe load limits, in pounds per square foot (kilograms per square meter), of floors elevated above ground level, and pier structures over the water shall be conspicuously posted in all cargo areas.

(c) Maximum safe load limits shall not be exceeded.

(d) All walking and working surfaces in the terminal area shall be maintained in good repair.

§ 1917.112 Guarding of edges.

(a) *Vehicle protection.* (1) Vehicle curbs, bull rails, or other effective barriers at least six inches (15.24 cm) in height shall be provided at the water-side edges of aprons and bulkheads, except where vehicles are prohibited. Curbs or bull rails installed after Octo-

29 CFR Ch. XVII (7–1–06 Edition)

ber 3, 1983, shall be at least 10 inches (25.4 cm) in height.

(2) The provisions of paragraph (a)(1) of this section also apply at the edge of any fixed level above the common floor area from which vehicles may fall, except at loading docks, platforms and skids where cargo is moved by vehicles.

(b) *Employee protection.* (1) Guardrails shall be provided at locations where employees are exposed to floor or wall openings or waterside edges, including bridges or gangway-like structures leading to pilings or vessel mooring or berthing installations, which present a hazard of falling more than 4 feet (1.22 m) or into the water, except as specified in paragraph (b)(2) of this section.

(2) Guardrails are not required:

(i) At loading platforms and docks;

(ii) At waterside edges used for cargo handling;

(iii) On the working sides of work platforms, skids or similar workplaces; or

(iv) On railroad rolling stock, highway vehicles, intermodal containers or similar equipment.

(3) Where guardrails are impracticable due to machinery requirements or work processes, an alternate means of protecting employees from falling, such as nets, shall be used.

(c) *Criteria for guardrails.* Guardrails shall meet the following criteria:

(1) They shall be capable of withstanding a force of at least 200 pounds (890 N) applied in any direction at mid-span of the top rail (when used), or at the uppermost point if there is no top rail.

(2) If not of solid baluster, grillwork, slatted or similar construction, guardrails shall consist of top rails and midrails. Midrails, when used, shall be positioned at approximately half the height of the top rail.

(3) The top surface of guardrails installed before October 3, 1983, shall be at least 36 inches (0.91 m) high. Those installed after October 3, 1983, shall be 42 inches (1.07 m), plus or minus 2 inches (5.1 cm), high.

(4) Any non-rigid railing such as chain or wire rope shall have a maximum sag limit at the mid-point between posts of not more than 6 inches (15.24 cm).