

## § 1918.26

(2) Be equipped with a railing meeting the requirements of § 1918.21(b), if the slope is more than 20 degrees to the horizontal or if employees could fall more than four feet (1.22 m);

(3) Be equipped with a slip resistant surface;

(4) Be properly secured; and

(5) Be designed, constructed, and maintained to prevent vehicles from running off the edge.<sup>4</sup>

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

### § 1918.26 Access to barges and river towboats.

(a) With the exception of § 1918.25(b)(2), ramps used solely for vehicle access to or between barges shall meet the requirements of § 1918.25.

(b) When employees cannot step safely to or from the wharf and a float, barge, or river towboat, either a ramp meeting the requirements of paragraph (a) of this section or a safe walkway meeting the requirements of § 1918.22(f) shall be provided. When a ramp or walkway cannot be used, a straight ladder meeting the requirements of § 1918.24 and extending at least three feet (.91 m) above the upper landing surface and adequately secured or held against shifting or slipping shall be provided. When neither a walkway nor a straight ladder can be used, a Jacob's ladder meeting the requirements of § 1918.23 shall be provided. Exception: For barges operating on the Mississippi River System, where the employer shows that these requirements cannot reasonably be met due to local conditions, other safe means of access shall be provided.

(c) When a barge or raft is being worked alongside a larger vessel, a Jacob's ladder meeting the requirements of § 1918.23 shall be provided for each gang working alongside unless other safe means of access is provided. However, no more than two Jacob's ladders are required for any single barge or raft being worked.

<sup>4</sup>When the gap to be bridged is greater than 36 inches (.91m), an acceptable means of preventing vehicles from running off the edge is a minimum side board height of two and three-quarter inches.

## 29 CFR Ch. XVII (7-1-06 Edition)

(d) When longshoring operations are in progress on barges, the barges shall be securely made fast to the vessel, wharf, or dolphins.

### Subpart D—Working Surfaces

#### § 1918.31 Hatch coverings.

(a) No cargo, dunnage, or other material shall be loaded or unloaded by means requiring the services of employees at any partially opened intermediate deck unless either the hatch at that deck is sufficiently covered or an adequate landing area suitable for the prevailing conditions exists. In no event shall such work be done unless the working area available for such employees extends for a distance of 10 feet (3.05 m) or more fore and aft and athwartships.

(b) Cargo shall not be landed on or handled over a covered hatch or 'tween-decks unless all hatch beams are in place under the hatch covers.

(c) Missing, broken, or poorly fitting hatch covers that would not protect employees shall be reported at once to the officer in charge of the vessel. Pending replacement or repairs by the vessel, work shall not be performed in the section containing the unsafe covers or in adjacent sections unless the flooring is made safe.

(d) Hatch covers and hatch beams not of uniform size shall be placed only in the hatch, deck, and section in which they fit properly.

(e) Small trimming hatches in intermediate decks shall be securely covered or guarded while work is going on in the hatch in which they are found, unless they are actually in use.

#### § 1918.32 Stowed cargo and temporary landing surfaces.

(a) Temporary surfaces on which loads are to be landed shall be of sufficient size and strength to permit employees to work safely.

(b) When the edge of a hatch section or of stowed cargo may constitute a fall hazard to an employee, the edge shall be guarded by a vertical safety net, or other means providing equal protection, to prevent an employee from falling. When the employer can demonstrate that vertical nets or other equally effective means of guarding

cannot be used due to the type of cargo, cargo stowage, or other circumstances, a trapeze net shall be rigged at the top edge of the elevation or other means shall be taken to prevent injury if an employee falls. Safety nets shall be maintained in good condition and be of adequate strength for the purpose intended.

(c) When two gangs are working in the same hatch on different levels, a vertical safety net shall be rigged and securely fastened to prevent employees or cargo from falling. Safety nets shall be maintained in good condition and be of adequate strength for the purpose intended.

#### § 1918.33 Deck loads.

(a) Employees shall not be permitted to pass over or around deck loads unless there is a safe route of passage.

(b) Employees giving signals to crane operators shall not be permitted to walk over deck loads from rail to coaming unless there is a safe route of passage. If it is necessary to stand or walk at the outboard or inboard edge of the deck load having less than 24 inches (.61 m) of bulwark, rail, coaming, or other protection, those employees shall be provided with protection against falling from the deck load.

#### § 1918.34 Other decks.

(a) Cargo shall not be worked on decks that were not designed to support the load being worked.

(b) Grated decks shall be properly placed, supported, maintained and designed to support employees.

#### § 1918.35 Open hatches.

Open weather deck hatches around which employees must work that are not protected to a height of 24 inches (.61 m) by coamings shall be guarded by taut lines or barricades at a height of 36 to 42 inches (.91 to 1.07 m) above the deck, except on the side on which cargo is being worked. Any portable stanchions or uprights used shall be supported or secured to prevent accidental dislodgement.

#### § 1918.36 Weather deck rails.

Removable weather deck rails shall be kept in place except when cargo operations require them to be removed,

in which case they shall be replaced as soon as such cargo operations are completed.

#### § 1918.37 Barges.

(a) Walking shall be prohibited along the sides of covered lighters or barges with coamings or cargo more than five feet (1.52 m) high unless a three-foot (.91 m) clear walkway or a grab rail or taut handline is provided.

(b) Walking or working shall be prohibited on the decks of barges to be loaded unless the walking or working surfaces have been determined by visual inspection to be structurally sound and maintained properly. If, while discharging a barge, an unsound deck surface is discovered, work shall be discontinued and shall not be resumed until means have been taken to ensure a safe work surface.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40944, June 30, 2000]

### Subpart E—Opening and Closing Hatches

#### § 1918.41 Coaming clearances.

(a) *Weather decks.* If a deck load (such as lumber or other smooth sided deck cargo) more than five feet (1.52 m) high is stowed within three feet (.91 m) of the hatch coaming and employees handling hatch beams and hatch covers are not protected by a coaming at least 24-inch (.61 m) high, a taut handline shall be provided along the side of the deckload. The requirements of § 1918.35 are not intended to apply in this situation.

(b) *Intermediate decks.* (1) There shall be a three-foot (.91 m) working space between the stowed cargo and the coaming at both sides and at one end of the hatches with athwartship hatch beams, and at both ends of those hatches with fore and aft hatch beams, before intermediate deck hatch covers and hatch beams are removed or replaced. Exception: The three-foot (.91 m) clearance is not required on the covered portion of a partially open hatch, nor is it required when lower decks have been filled to hatch beam height with cargo of such a nature as to provide a safe surface upon which employees may work.