

(B) While handling bulk commodities or cargoes by means of clamshell bucket or magnet;

(C) While used to handle or hold hoses in connection with transfer of bulk liquids, or other hose-handled products; or

(D) While the crane is used exclusively to handle cargo or equipment whose total actual gross weight is marked on the unit or units hoisted, and the total actual gross weight never exceeds 11,200 lbs., and the load is less than the rated capacity of the crane at the maximum outreach possible at the time.

(2) [Reserved]

[62 FR 40202, July 25, 1997, as amended at 65 FR 40945, June 30, 2000]

§ 1918.67 Notifying the ship's officers before using certain equipment.

(a) The employer shall notify the officer in charge of the vessel before bringing aboard ship internal combustion or electric powered tools, equipment or vehicles.

(b) The employer shall also notify the officer in charge of the vessel before using the ship's electric power for the operation of any electric tools or equipment.

§ 1918.68 Grounding.

The frames of portable electrical equipment and tools, other than double insulated tools and battery operated tools, shall be grounded through a separate equipment conductor run with or enclosing the circuit conductors.

§ 1918.69 Tools.

(a) *General.* Employers shall not issue or permit the use of visibly unsafe tools.

(b) *Portable electric tools.* (1) Portable hand-held electric tools shall be equipped with switches of a type that must be manually held in a closed position in order to operate the tool.

(2) All portable, power-driven circular saws shall be equipped with guards above and below the base plate or shoe. The upper guard shall cover the saw to the depth of the teeth, except for the minimum arc required to permit the base to be tilted for bevel cuts. The lower guard shall cover the saw to the depth of the teeth, except

for the minimum arc required to allow proper retraction and contact with the work. When the tool is withdrawn from the work, the lower guard shall automatically and instantly return to the covering position.

[62 FR 40202, July 25, 1997, as amended at 65 FR 40946, June 30, 2000]

§§ 1918.70–1918.80 [Reserved]

Subpart H—Handling Cargo

§ 1918.81 Slinging.

(a) Drafts shall be safely slung before being hoisted. Loose dunnage or debris hanging or protruding from loads shall be removed.

(b) Cargo handling bridles, such as pallet bridles, which are to remain attached to the hoisting gear while hoisting successive drafts, shall be attached by shackles, or other positive means shall be taken to prevent them from being accidentally disengaged from the cargo hook.

(c) Drafts of lumber, pipe, dunnage and other pieces, the top layer of which is not bound by the sling, shall be slung in a way that prevents sliders. Double slings shall be used on unstrapped dunnage, unless, due to the size of hatch or deep tank openings, using them is impracticable.

(d) Case hooks shall be used only with cases designed to be hoisted by these hooks.

(e) Bales of cotton, wool, cork, wood pulp, gunny bags or similar articles shall not be hoisted by straps unless the straps are strong enough to support the weight of the bale. At least two hooks, each in a separate strap, shall be used.

(f) Unitized loads bound by bands or straps may be hoisted by the banding or strapping only if the banding or strapping is suitable for hoisting and is strong enough to support the weight of the load.

(g) Additional means to maintain the unitized loads during hoisting shall be employed to ensure safe lifting of such loads having damaged banding or strapping.

(h) Loads requiring continuous manual guidance during handling shall be guided by guide ropes (tag lines) that are long enough to control the load.