

§ 409.87

limitations. The BOD<sub>5</sub> limitation is determined by the addition of the net BOD<sub>5</sub> attributable to the barometric condenser cooling water to that amount of BOD<sub>5</sub> attributable to the treated process waste water. The TSS limitation is that amount of TSS attributable to the treated process waste water, excluding barometric condenser cooling water.

Effluent characteristic	Effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days shall not exceed—
	Metric units (kg/kkg of gross cane)	
BOD <sub>5</sub> .....	1.14	0.63
TSS .....	1.41	0.47
pH .....	( <sup>1</sup> )	( <sup>1</sup> )
	English units (lb/1,000 lb of gross cane)	
BOD <sub>5</sub> .....	1.14	0.63
TSS .....	1.41	0.47
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any cane sugar factory employing waste stabilization where all or a portion of the waste water discharge is stored for the entire grinding season shall meet the following limitations. The BOD<sub>5</sub> limitation is determined by the addition of the net BOD<sub>5</sub> attributable to the barometric condenser cooling water to that amount of BOD<sub>5</sub> attributable to the treated process waste water. The TSS limitation is that amount of TSS attributable to the treated process waste water, excluding barometric condenser cooling water.

Effluent characteristic	Effluent limitations, the total of the daily values for the entire discharge period shall not exceed—
	Metric units (kg/kkg of gross cane)
BOD <sub>5</sub> .....	0.63.
TSS .....	0.47.
pH .....	Within the range 6.0 to 9.0.
	English units (lb/1,000 lb of gross cane)
BOD <sub>5</sub> .....	0.63.
TSS .....	0.47.
pH .....	Within the range 6.0 to 9.0.

40 CFR Ch. I (7-1-06 Edition)

(Secs. 301, 304 (b) and (c), 306 (b) and (c), 307 (c) and (d) of the Federal Water Pollution Control Act, as amended (33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), 1317(c) and 1326(c)), 86 Stat. 816 *et seq.*, Pub. L. 92-500)

[40 FR 8504, Feb. 27, 1975, as amended at 60 FR 33950, June 29, 1995]

**§ 409.87 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations shall be the same as those specified for conventional pollutants (which are defined in § 401.16) in § 409.82 of this subpart for the best practicable control technology currently available (BPT).

[51 FR 24999, July 9, 1986]

**PART 410—TEXTILE MILLS POINT SOURCE CATEGORY**

GENERAL PROVISIONS

- Sec.
- 410.00 Applicability.
- 410.01 General definitions.
- 410.02 Monitoring requirements. [Reserved]

**Subpart A—Wool Scouring Subcategory**

- 410.10 Applicability; description of the wool scouring subcategory.
- 410.11 Specialized definitions.
- 410.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).
- 410.13 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).
- 410.14 Pretreatment standards for existing sources (PSES).
- 410.15 New source performance standards (NSPS).
- 410.16 Pretreatment standards for new sources (PSNS).
- 410.17 Effluent limitations representing the degree of effluent reduction attainable