

§ 411.10

Subpart B—Leaching Subcategory

- 411.20 Applicability; description of the leaching subcategory.
- 411.21 Specialized definitions.
- 411.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 411.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 411.24 Pretreatment standards for existing sources.
- 411.25 Standards of performance for new sources.
- 411.26 Pretreatment standards for new sources.
- 411.27 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the conventional pollutant control technology (BCT).

Subpart C—Materials Storage Piles Runoff Subcategory

- 411.30 Applicability; description of the materials storage piles runoff subcategory.
- 411.31 Specialized definitions.
- 411.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 411.33 [Reserved]
- 411.34 Pretreatment standards for existing sources.
- 411.35 Standards of performance for new sources.
- 411.36 Pretreatment standards for new sources.
- 411.37 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology.

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c), and 307(c) of the Federal Water Pollution Control Act, as amended; 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), and 1317(c); 86 Stat. 816 *et seq.*, Pub. L., 92-500; 91 Stat. 1567, Pub. L. 95-217.

SOURCE: 39 FR 6591, Feb. 20, 1974, unless otherwise noted.

40 CFR Ch. I (7-1-06 Edition)

Subpart A—Nonleaching Subcategory

§ 411.10 Applicability; description of the nonleaching subcategory.

The provisions of this subpart are applicable to discharges resulting from the process in which several mineral ingredients (limestone or other natural sources of calcium carbonate, silica, alumina, and iron together with gypsum) are used in the manufacturing of cement and in which kiln dust is not contracted with water as an integral part of the process and water is not used in wet scrubbers to control kiln stack emissions.

§ 411.11 Specialized definitions.

For the purpose of this subpart:

(a) Except as provided below, the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 411.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

Effluent characteristic	Effluent limitations (maximum for any 1 day)	
	Metric units (kg/kg of product)	
TSS	0.005.	
Temperature (heat)	Not to exceed 3 °C rise above inlet temperature.	
pH	Within the range 6.0 to 9.0.	
English units (lb/1,000 lb of product)		
TSS	0.005.	
Temperature (heat)	Not to exceed 3 °C rise above inlet temperature.	
pH	Within the range 6.0 to 9.0.	

[39 FR 6591, Feb. 20, 1974, as amended at 60 FR 33950, June 29, 1995]