

**§415.673**

**SUBPART BO—ZINC CHLORIDE**

Pollutant or pollutant property	BPT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter (mg/l)	
TSS .....	43	25
Arsenic (T) .....	3.0	1.0
Zinc (T) .....	11.4	3.8
Lead (T) .....	1.8	0.6
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 10.0

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

**§415.673 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

**SUBPART BO—ZINC CHLORIDE**

Pollutant or pollutant property	BAT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter (mg/l)	
Arsenic (T) .....	3.0	1.0
Zinc (T) .....	2.3	0.76
Lead (T) .....	0.18	0.048

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

**§415.674 Pretreatment standards for existing sources (PSES).**

Except as provided in 40 CFR 403.7 and 403.13, any existing source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for existing sources (PSES):

**40 CFR Ch. I (7-1-06 Edition)**

**SUBPART BO—ZINC CHLORIDE**

Pollutant or pollutant property	PSES effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter (mg/l)	
Arsenic (T) .....	3.0	1.0
Zinc (T) .....	2.3	0.76
Lead (T) .....	0.18	0.048

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

**§415.675 New source performance standards (NSPS):**

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

**SUBPART BO—ZINC CHLORIDE**

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter (mg/l)	
TSS .....	28	17
Arsenic (T) .....	3.0	1.0
Zinc (T) .....	2.3	0.76
Lead (T) .....	0.18	0.048
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 10.0.

[49 FR 33428, Aug. 22, 1984; 49 FR 37594, Sept. 25, 1984]

**§415.676 Pretreatment standards for new sources (PSNS).**

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS): The limitations for arsenic (T), zinc (T), and lead (T) are the same as specified in §415.674.

**§415.677 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT).**

Except as provided in 40 CFR 125.30 through 125.32 any existing point source subject to this subpart must

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT): The limitations are the same for TSS and pH as specified in §415.672.

**PART 416 [RESERVED]**

**PART 417—SOAP AND DETERGENT MANUFACTURING POINT SOURCE CATEGORY**

**Subpart A—Soap Manufacturing by Batch Kettle Subcategory**

Sec.

- 417.10 Applicability; description of the soap manufacturing by batch kettle subcategory.
- 417.11 Specialized definitions.
- 417.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 417.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 417.14 Pretreatment standards for existing sources.
- 417.15 Standards of performance for new sources.
- 417.16 Pretreatment standards for new sources.

**Subpart B—Fatty Acid Manufacturing by Fat Splitting Subcategory**

- 417.20 Applicability; description of the fatty acid manufacturing by fat splitting subcategory.
- 417.21 Specialized definitions.
- 417.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 417.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 417.24 Pretreatment standards for existing sources.
- 417.25 Standards of performance for new sources.
- 417.26 Pretreatment standards for new sources.

**Subpart C—Soap Manufacturing by Fatty Acid Neutralization Subcategory**

- 417.30 Applicability; description of the soap manufacturing by fatty acid neutralization subcategory.
- 417.31 Specialized definitions.
- 417.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 417.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 417.34 Pretreatment standards for existing sources.
- 417.35 Standards of performance for new sources.
- 417.36 Pretreatment standards for new sources.

**Subpart D—Glycerine Concentration Subcategory**

- 417.40 Applicability; description of the glycerine concentration subcategory.
- 417.41 Specialized definitions.
- 417.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 417.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 417.44 Pretreatment standards for existing sources.
- 417.45 Standards of performance for new sources.
- 417.46 Pretreatment standards for new sources.

**Subpart E—Glycerine Distillation Subcategory**

- 417.50 Applicability; description of the glycerine distillation subcategory.
- 417.51 Specialized definitions.
- 417.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 417.53 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.
- 417.54 Pretreatment standards for existing sources.
- 417.55 Standards of performance for new sources.