

(c) All washbasins, showers, and bathtubs shall be equipped with adequate plumbing, including hot and cold running water. All toilets must be installed with adequate plumbing for flushing.

(d) At least 1 washbasin must be fitted in each toilet room, except where private or semi-private facilities are provided and washbasins are installed in the sleeping rooms.

(e) Where more than 1 toilet is located in a space or compartment, each toilet must be separated by partitions.

**§ 92.20-30 Messrooms.**

(a) Messrooms must be located as near to the galley as is practicable except where the messroom is equipped with a steam table.

(b) Each messroom must seat the number of persons expected to eat in the messroom at one time.

**§ 92.20-35 Hospital space.**

(a) Each vessel which in the ordinary course of its trade makes voyages of more than 3 days duration between ports and which carries a crew of 12 or more, must be provided with a hospital space. This space must be situated with due regard to the comfort of the sick so that they may receive proper attention in all weathers.

(b) The hospital must be suitably separated from other spaces and must be used for the care of the sick and for no other purpose.

(c) The hospital must be fitted with berths in the ratio of 1 berth to every 12 members of the crew or portion thereof who are not berthed in single occupancy rooms, but the number of berths need not exceed 6.

(d) The hospital must have a toilet, washbasin, and bathtub or shower conveniently situated. Other necessary suitable equipment such as a clothes locker, a table, and a seat shall be provided.

(e) On vessels in which the crew is berthed in single occupancy rooms, a hospital space will not be required, provided that one room is designated and fitted for use as a treatment or isolation room. This room must meet the following standards:

(1) The room must be available for immediate medical use; and

(2) A washbasin with hot and cold running water must be installed either in or immediately adjacent to the space and other required sanitary facilities must be conveniently located.

**§ 92.20-40 Other spaces.**

Each vessel must have—

(a) Sufficient facilities where the crew may wash and dry their own clothes, including at least 1 sink supplied with hot and cold fresh water;

(b) Recreation spaces; and

(c) A space or spaces of adequate size on an open deck to which the crew has access when off duty.

[CGD 95-027, 61 FR 26005, May 23, 1996; 61 FR 32900, June 25, 1996]

**§ 92.20-45 Lighting.**

Each berth must have a light.

**§ 92.20-50 Heating and cooling.**

(a) All manned spaces must be adequately heated and cooled in a manner suitable to the purpose of the space.

(b) The heating and cooling system for accommodations must be capable of maintaining a temperature of 21° C (70° F) under normal operating conditions without curtailing ventilation.

(c) Radiators and other heating apparatus must be so placed and shielded, where necessary, to avoid risk of fire, danger, or discomfort to the occupants. Pipes leading to radiators or heating apparatus must be insulated where those pipes create a hazard to persons occupying the space.

**§ 92.20-55 Insect screens.**

Provisions must be made to protect the crew quarters against the admission of insects.

**§ 92.20-90 Vessels contracted for prior to November 19, 1952.**

(a) Vessels of less than 100 gross tons, contracted for prior to November 19, 1952, must meet the general intent of § 92.20-5 and in addition must meet the following requirements:

(1) Existing structure, arrangements, materials, and facilities, previously accepted or approved will be considered satisfactory so long as they are maintained in a suitable condition to the satisfaction of the Officer in Charge, Marine Inspection.

## § 92.25-1

(2) Minor repairs and alterations may be made to the same standard as the original construction.

(b) Vessels of 100 gross tons and over, contracted for prior to March 4, 1915, must meet the following requirements:

(1) Existing structure, arrangements, materials, and facilities, previously approved will be considered satisfactory so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection.

(2) Minor repairs and alterations may be made to the same standard as the original construction, provided that in no case will a greater departure from the standards of §§ 92.20-5 through 92.20-55 be permitted than presently exists.

(c) Vessels of 100 gross tons and over, contracted for on or after March 4, 1915, but prior to January 1, 1941, must meet the following requirements:

(1) Existing structure, arrangements, materials, and facilities, previously approved will be considered satisfactory so long as they are maintained in a suitable condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standard as the original construction.

(2) Each vessel, which in the ordinary course of its trade makes a voyage of more than 3 days duration between ports and which carries a crew of 12 or more persons, must be provided with a suitable hospital space for the exclusive use of the sick or injured.

(3) The crew spaces must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, arranged, and insulated from undue noise, heat, and odors.

(d) Vessels of 100 gross tons and over, contracted for on or after January 1, 1941, but prior to November 19, 1952, must meet the following requirements:

(1) Existing structure, arrangements, materials, and facilities, previously approved will be considered satisfactory so long as they are maintained in a suitable condition to the satisfaction of the Officer in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standard as the original construction.

(2) Washbasins, showers, and bathtubs if substituted for showers, must be

## 46 CFR Ch. I (10-1-06 Edition)

equipped with adequate plumbing including hot and cold running water.

(3) Each crewmember must have a separate berth, and berths may not be placed more than 2 high.

(4) Each vessel, which in the ordinary course of its trade makes a voyage of more than 3 days duration between ports and which carries a crew of 12 or more persons, must be provided with a suitable hospital space for the exclusive use of the sick or injured. Berths shall be provided in the ratio of 1 berth for each 12 members of the crew or fraction thereof, but the number of berths need not exceed 6.

(5) The crew spaces must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, arranged, and insulated from undue noise, heat, and odors.

### Subpart 92.25—Rails and Guards

#### § 92.25-1 Application.

(a) The provisions of this subpart, with the exception of § 92.25-90, shall apply to all vessels contracted for on or after July 1, 1969. Vessels contracted for prior to July 1, 1969, shall meet the requirements of § 92.25-90.

[CGFR 65-50, 30 FR 16983, Dec. 30, 1965, as amended by CGFR 69-72, 34 FR 17484, Oct. 29, 1969; CGD 80-120, 47 FR 5723, Feb. 8, 1982]

#### § 92.25-5 Where rails required.

(a) All vessels shall have efficient guard rails or bulwarks on decks and bridges. The height of rails or bulwarks shall be at least 39½ inches from the deck except that where this height would interfere with the normal operation of the vessel, a lesser height may be approved by the Commandant. At exposed peripheries of the freeboard and superstructure decks, the rails shall be in at least three courses, including the top. The opening below the lowest course shall not be more than 9 inches. The courses shall not be more than 15 inches apart. In the case of ships with rounded gunwales the guard rail supports shall be placed on the flat of the deck. On other decks and bridges the rails shall be in at least two courses, including the top, approximately evenly spaced. If it can be shown to the satisfaction of the Officer in Charge, Marine Inspection, that the