

§ 96.06-1

J (Electrical Engineering) of this chapter.

[CGFR 66-33, 31 FR 15285, Dec. 6, 1966, as amended by CGFR 68-32, 33 FR 5719, Apr. 12, 1968, CGD 74-125A, 47 FR 15232, Apr. 8, 1982]

Subpart 96.06—Lifesaving Appliances and Arrangements

§ 96.06-1 Installation.

The installation of all lifesaving appliances and arrangements must be in accordance with subchapter W (Lifesaving Appliances and Arrangements) of this chapter.

[CGD 84-069, 61 FR 25289, May 20, 1996]

Subpart 96.07—Anchors, Chains, and Hawsers

§ 96.07-1 Application.

(a) The provisions of this subpart, with the exception of § 96.07-90, shall apply to all vessels contracted for on or after November 19, 1952. Vessels contracted for prior to November 19, 1952, shall meet the requirements of § 96.07-90.

§ 96.07-5 Ocean, coastwise, or Great Lakes service.

(a) Vessels in ocean, coastwise, or Great Lakes service, except unmanned barges, shall be fitted with anchors, chains, and hawsers in general agreement with the Standards established by the American Bureau of Shipping, see Subpart 90.35 of this subchapter.

(b) In addition to the provisions of paragraph (a) of this section, the following requirements and alternatives also apply:

(1) The American Bureau of Shipping rules relating to anchor equipment are mandatory, not a guide.

(2) Vessels under 200 feet (61 meters) in length and with an American Bureau of Shipping equipment number of less than 150 may be equipped with either—

(i) One anchor of the tabular weight and one-half the tabulated length of anchor chain listed in the applicable standard, or

(ii) Two anchors of one-half the tabular weight with the total length of anchor chain listed in the applicable standard provided both anchors are in a position that allows for ready use at

46 CFR Ch. I (10-1-06 Edition)

all times and the windlass is capable of heaving in either anchor.

(c) Tugs, under 200 feet (61 meters) in length, shall have at least one anchor of one-half the tabular weight listed in the applicable standards.

(d) Standards of other recognized classification societies may be used, in lieu of those established by the American Bureau of Shipping, upon approval by the Commandant.

[CGFR 68-32, 33 FR 5720, Apr. 12, 1968, as amended by CGD 87-013, 53 FR 20624, June 6, 1988]

§ 96.07-10 Lakes, bays, and sounds, or river service.

(a) Vessels in lakes, bays, and sounds, or river service shall be fitted with such ground tackle and hawsers as deemed necessary by the Officer in Charge, Marine Inspection, depending upon the size of the vessel and the waters on which it operates.

§ 96.07-90 Vessels contracted for prior to November 19, 1952.

(a) Vessels contracted for prior to November 19, 1952, shall meet the following requirements:

(1) Installations previously accepted or approved shall be considered satisfactory for the same service so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection. If the service of the vessel is changed, the suitability of the equipment will be established by the Officer in Charge, Marine Inspection.

Subpart 96.17—Magnetic Compass and Gyrocompass

§ 96.17-1 When required.

(a) All mechanically propelled vessels in ocean or coastwise service must be fitted with a magnetic compass.

(b) All mechanically propelled vessels of 1,600 gross tons and over in ocean or coastwise service must be fitted with a gyrocompass in addition to the magnetic compass.

(c) Each vessel must have an illuminated repeater for the gyrocompass required under paragraph (b) that is at