

List of substances	Limitations
<p>Sodium diisobutylphenoxy diethoxyethyl sulfonate.. Sodium diisobutylphenoxy monoethoxy ethylsulfonate.. Sodium <i>n</i>-dodecylpolyethoxy (50 moles) sulfate.. Sodium isododecylphenoxy polyethoxy (40 moles) sulfate.. Sodium <i>N</i>-methyl-<i>N</i>-oleyl taurate.. Sodium methyl silicate.. Sodium nitrite.. Sodium polyacrylate.. Sodium bis-tridecylsulfosuccinate.. Sodium xylene sulfonate.. Stearato chromic chloride complex.. Styrene-allyl alcohol copolymers.. Styrene-methacrylic acid copolymer, potassium salt.. Tetraethylenepentamine</p> <p>α-[<i>p</i>-(1,1,3,3-Tetramethylbutyl)phenyl]-<i>omega</i>-hydroxypoly(oxyethylene) mixture of dihydrogen phosphate and monohydrogen phosphate esters and their sodium, potassium, and ammonium salts having a poly(oxyethylene) content averaging 6–9 or 40 moles..</p> <p>α-[<i>p</i>-(1,1,3,3-Tetramethylbutyl)phenyl or <i>p</i>-nonylphenyl]-<i>omega</i>-hydroxypoly (oxyethylene) where nonyl group is a propylene trimer isomer..</p> <p>Tetrasodium <i>N</i>-(1,2-dicarboxyethyl)-<i>N</i>-octadecyl sulfosuccinamate..</p> <p>Toluene..</p> <p>Triethanolamine..</p> <p>Triethylenetetramine</p> <p>Triethylenetetramine monoacetate, partially stearoylated..</p> <p>Urea-formaldehyde chemically modified with: Alcohol (methyl, ethyl, butyl, isobutyl, propyl, or isopropyl). Aminomethylsulfonic acid. Diaminobutane. Diaminopropane. Diethylenetriamine. <i>N,N</i>-Dioleylethylenediamine. Diphenylamine. <i>N,N</i>-Distearoylethylenediamine. Ethylenediamine. Guanidine. Imino-bis-butylamine. Imino-bis-ethylamine. Imino-bis-propylamine. <i>N</i>-Oleoyl-<i>N</i>-stearoylethylenediamine. Polyamines made by reacting ethylenediamine or triethylenediamine with dichloroethane or dichloropropane. Tetraethylenepentamine. Triethylenetetramine.</p> <p>Xylene..</p> <p>Xylene sulfonic acid-formaldehyde condensate, sodium salt..</p> <p>Zinc stearate..</p>	<p>Polymerization cross-linking agent.</p> <p>Polymerization cross-linking agent.</p>

[42 FR 14554, Mar. 15, 1977]

EDITORIAL NOTE: For additional FEDERAL REGISTER citations affecting §176.180, see the List of CFR Sections Affected, which appears in the Finding Aids section of the printed volume and on GPO Access.

§ 176.200 Defoaming agents used in coatings.

The defoaming agents described in this section may be safely used as components of articles intended for use in producing, manufacturing, packing, processing, preparing, treating, packaging, transporting, or holding food, subject to the provisions of this section.

(a) The defoaming agents are prepared as mixtures of substances described in paragraph (d) of this section.

(b) The quantity of any substance employed in the formulation of defoaming agents does not exceed the amount reasonably required to accomplish the intended physical or technical effect in the defoaming agents or any limitation further provided.

Food and Drug Administration, HHS

§ 176.200

(c) Any substance employed in the production of defoaming agents and which is the subject of a regulation in parts 174, 175, 176, 177, 178 and §179.45 of this chapter conforms with any specification in such regulation.

(d) Substances employed in the formulation of defoaming agents include:

(1) Substances generally recognized as safe in food.

(2) Substances subject to prior sanction or approval for use in defoaming agents and used in accordance with such sanction or approval.

(3) Substances identified in this paragraph (d)(3) and subject to such limitations as are provided:

List of substances	Limitations
<p><i>n</i>-Butyl alcohol. tert-Butyl alcohol. Butyl stearate. Castor oil, sulfated, ammonium, potassium, or sodium salt. Cetyl alcohol. Cyclohexane. Cyclohexanol. Diethylene glycol monolaurate. Diethylene glycol monostearate. Dimers and trimers of unsaturated C₁₈ fatty acids derived from:</p>	<p>For use only at levels not to exceed 0.1% by weight of total coating solids.</p>
<p> Animal and vegetable fats and oils. Tall oil. Dimethylpolysiloxane. α-(Dinonylphenyl)-ω-hydroxy-poly(oxy-1,2-ethanediyl), containing 7 to 24 moles of ethylene oxide per mole of dinonylphenol (CAS Reg. No. 9014-93-1). Dipropylene glycol. Ethyl alcohol. Fats and oils derived from animal, marine, or vegetable sources:</p>	<p>For use only in defoaming agents for the production of styrene-butadiene coatings at a level not to exceed 0.05 percent by weight of the finished coating.</p>
<p> Fatty acids derived from animal, marine, or vegetable fats and oils, and salts of such acids, single or mixed, as follows: Aluminum.. Ammonium.. Calcium.. Magnesium.. Potassium.. Sodium.. Zinc..</p>	<p>For use as preservative of defoamer only.</p>
<p>Formaldehyde Glycerol mono-12-hydroxystearate. Glycerol monostearate. Hexane. Hexylene glycol (2-methyl-2,4-pentanediol). Isobutyl alcohol. Isopropyl alcohol. Kerosene. Lecithin hydroxylated. Methyl alcohol. Methylcellulose. Methyl esters of fatty acids derived from animal, marine, or vegetable fats and oils. Methyl oleate. Methyl palmitate. Mineral oil. Mustardseed oil, sulfated, ammonium, potassium, or sodium salt. Myristyl alcohol. Naphtha. β-Naphthol Nonylphenol. Odorless light petroleum hydrocarbons Oleic acid, sulfated, ammonium, potassium, or sodium salt. Parachlorometacresol Peanut oil, sulfated, ammonium, potassium, or sodium salt. Petrolatum. Pine oil. Polyacrylic acid, sodium salt</p>	<p>For use as preservative of defoamer only.</p> <p>As defined in § 178.3650 of this chapter.</p> <p>For use as preservative of defoamer only.</p>
<p>Polyethylene.</p>	<p>As a stabilizer and thickener in defoaming agents containing dimethylpolysiloxane.</p>

List of substances	Limitations
Polyethylene, oxidized. Polyethylene glycol (200) dilaurate. Polyethylene glycol (400) dioleate. Polyethylene glycol (600) dioleate. Polyethylene glycol (400) esters of coconut oil fatty acids. Polyethylene glycol (400) monooleate. Polyethylene glycol (600) monooleate. Polyethylene glycol (600) monoricinoleate. Polyethylene glycol (400) monostearate. Polyoxybutylene-polyoxypropylene-polyoxyethylene glycol (min. mol. wt. 3,700). Polyoxyethylated (min. 3 mols) cetyl alcohol. Polyoxyethylated (min. 5 mols) oleyl alcohol. Polyoxyethylated (min. 1.5 mols) tridecyl alcohol. Polyoxyethylene (min. 15 mols) ester of rosin. Polyoxyethylene (min. 8 mols) monooleate. Polyoxyethylene (40) stearate. Polyoxypropylated (min. 20 mols) butyl alcohol. Polyoxypropylene glycol (min. mol. wt. 200). Polyoxypropylene (min. 20 mols) oleate butyl ether. Polyoxypropylene-polyoxyethylene glycol (min. mol. wt. 1,900). Polyoxypropylene (min. 40 mols) stearate butyl ether. Potassium pentachlorophenate Potassium trichlorophenate Propylene glycol monoester of soybean oil fatty acids. Propylene glycol monoester of tallow fatty acids. Ricebran oil, sulfated, ammonium, potassium, or sodium salt. Rosins and rosin derivatives Silica. Sodium 2-mercaptobenzothiazole Sodium pentachlorophenate Sodium trichlorophenate Sperm oil, sulfated, ammonium, potassium, or sodium salt. Stearyl alcohol. Tall oil fatty acids. Tallow fatty acids, hydrogenated or sulfated. Tallow, sulfated, ammonium, potassium, or sodium salt. Triethanolamine. Triisopropanolamine. Waxes, petroleum.	For use as preservative of defoamer only. Do. As provided in § 178.3870 of this chapter. For use as preservative of defoamer only. Do. Do.

(e) The defoaming agents are used as follows:

(1) The quantity of defoaming agent or agents used shall not exceed the amount reasonably required to accomplish the intended effect, which is to prevent or control the formation of foam.

(2) The defoaming agents are used in the preparation and application of coatings for paper and paperboard.

[42 FR 14554, Mar. 15, 1977, as amended at 62 FR 39772, July 24, 1997]

§ 176.210 Defoaming agents used in the manufacture of paper and paperboard.

Defoaming agents may be safely used in the manufacture of paper and paperboard intended for use in packaging, transporting, or holding food in accordance with the following prescribed conditions:

(a) The defoaming agents are prepared from one or more of the substances named in paragraph (d) of this section, subject to any prescribed limitations.

(b) The defoaming agents are used to prevent or control the formation of foam during the manufacture of paper and paperboard prior to and during the sheet-forming process.

(c) The quantity of defoaming agent or agents added during the manufacturing process shall not exceed the amount necessary to accomplish the intended technical effect.

(d) Substances permitted to be used in the formulation of defoaming agents include substances subject to prior sanctions or approval for such use and employed subject to the conditions of such sanctions or approvals, substances generally recognized as safe for use in food, substances generally recognized as safe for use in paper and paperboard,