

§211.72

production and control records or other records are instituted only by authorized personnel. Input to and output from the computer or related system of formulas or other records or data shall be checked for accuracy. The degree and frequency of input/output verification shall be based on the complexity and reliability of the computer or related system. A backup file of data entered into the computer or related system shall be maintained except where certain data, such as calculations performed in connection with laboratory analysis, are eliminated by computerization or other automated processes. In such instances a written record of the program shall be maintained along with appropriate validation data. Hard copy or alternative systems, such as duplicates, tapes, or microfilm, designed to assure that backup data are exact and complete and that it is secure from alteration, inadvertent erasures, or loss shall be maintained.

[43 FR 45077, Sept. 29, 1978, as amended at 60 FR 4091, Jan. 20, 1995]

§211.72 Filters.

Filters for liquid filtration used in the manufacture, processing, or packing of injectable drug products intended for human use shall not release fibers into such products. Fiber-releasing filters may not be used in the manufacture, processing, or packing of these injectable drug products unless it is not possible to manufacture such drug products without the use of such filters. If use of a fiber-releasing filter is necessary, an additional non-fiber-releasing filter of 0.22 micron maximum mean porosity (0.45 micron if the manufacturing conditions so dictate) shall subsequently be used to reduce the content of particles in the injectable drug product. Use of an asbestos-containing filter, with or without subsequent use of a specific non-fiber-releasing filter, is permissible only upon submission of proof to the appropriate bureau of the Food and Drug Administration that use of a non-fiber-releasing filter will, or is likely to, compromise the safety or effectiveness of the injectable drug product.

21 CFR Ch. I (4-1-07 Edition)

Subpart E—Control of Components and Drug Product Containers and Closures

§211.80 General requirements.

(a) There shall be written procedures describing in sufficient detail the receipt, identification, storage, handling, sampling, testing, and approval or rejection of components and drug product containers and closures; such written procedures shall be followed.

(b) Components and drug product containers and closures shall at all times be handled and stored in a manner to prevent contamination.

(c) Bagged or boxed components of drug product containers, or closures shall be stored off the floor and suitably spaced to permit cleaning and inspection.

(d) Each container or grouping of containers for components or drug product containers, or closures shall be identified with a distinctive code for each lot in each shipment received. This code shall be used in recording the disposition of each lot. Each lot shall be appropriately identified as to its status (i.e., quarantined, approved, or rejected).

§211.82 Receipt and storage of untested components, drug product containers, and closures.

(a) Upon receipt and before acceptance, each container or grouping of containers of components, drug product containers, and closures shall be examined visually for appropriate labeling as to contents, container damage or broken seals, and contamination.

(b) Components, drug product containers, and closures shall be stored under quarantine until they have been tested or examined, as appropriate, and released. Storage within the area shall conform to the requirements of §211.80.

§211.84 Testing and approval or rejection of components, drug product containers, and closures.

(a) Each lot of components, drug product containers, and closures shall be withheld from use until the lot has been sampled, tested, or examined, as appropriate, and released for use by the quality control unit.

(b) Representative samples of each shipment of each lot shall be collected for testing or examination. The number of containers to be sampled, and the amount of material to be taken from each container, shall be based upon appropriate criteria such as statistical criteria for component variability, confidence levels, and degree of precision desired, the past quality history of the supplier, and the quantity needed for analysis and reserve where required by §211.170.

(c) Samples shall be collected in accordance with the following procedures:

(1) The containers of components selected shall be cleaned where necessary, by appropriate means.

(2) The containers shall be opened, sampled, and resealed in a manner designed to prevent contamination of their contents and contamination of other components, drug product containers, or closures.

(3) Sterile equipment and aseptic sampling techniques shall be used when necessary.

(4) If it is necessary to sample a component from the top, middle, and bottom of its container, such sample subdivisions shall not be composited for testing.

(5) Sample containers shall be identified so that the following information can be determined: name of the material sampled, the lot number, the container from which the sample was taken, the date on which the sample was taken, and the name of the person who collected the sample.

(6) Containers from which samples have been taken shall be marked to show that samples have been removed from them.

(d) Samples shall be examined and tested as follows:

(1) At least one test shall be conducted to verify the identity of each component of a drug product. Specific identity tests, if they exist, shall be used.

(2) Each component shall be tested for conformity with all appropriate written specifications for purity, strength, and quality. In lieu of such testing by the manufacturer, a report of analysis may be accepted from the supplier of a component, provided that

at least one specific identity test is conducted on such component by the manufacturer, and provided that the manufacturer establishes the reliability of the supplier's analyses through appropriate validation of the supplier's test results at appropriate intervals.

(3) Containers and closures shall be tested for conformance with all appropriate written procedures. In lieu of such testing by the manufacturer, a certificate of testing may be accepted from the supplier, provided that at least a visual identification is conducted on such containers/closures by the manufacturer and provided that the manufacturer establishes the reliability of the supplier's test results through appropriate validation of the supplier's test results at appropriate intervals.

(4) When appropriate, components shall be microscopically examined.

(5) Each lot of a component, drug product container, or closure that is liable to contamination with filth, insect infestation, or other extraneous adulterant shall be examined against established specifications for such contamination.

(6) Each lot of a component, drug product container, or closure that is liable to microbiological contamination that is objectionable in view of its intended use shall be subjected to microbiological tests before use.

(e) Any lot of components, drug product containers, or closures that meets the appropriate written specifications of identity, strength, quality, and purity and related tests under paragraph (d) of this section may be approved and released for use. Any lot of such material that does not meet such specifications shall be rejected.

[43 FR 45077, Sept. 29, 1978, as amended at 63 FR 14356, Mar. 25, 1998]

§211.86 Use of approved components, drug product containers, and closures.

Components, drug product containers, and closures approved for use shall be rotated so that the oldest approved stock is used first. Deviation from this requirement is permitted if such deviation is temporary and appropriate.