

§ 74.2052

21 CFR Ch. I (4-1-07 Edition)

suitable and that are listed in part 73 of this chapter as safe for use in color additive mixtures for coloring externally applied drugs.

(b) *Specifications.* D&C Yellow No. 11 shall conform to the following specifications and shall be free from impurities, other than those named, to the extent that such other impurities may be avoided by good manufacturing practice:

- Volatile matter (at 135 °C), not more than 1 percent.
- Ethyl alcohol-insoluble matter, not more than 0.4 percent.
- Phthalic acid, not more than 0.3 percent.
- Quinaldine, not more than 0.2 percent.
- Subsidiary colors, not more than 5 percent.
- Lead (as Pb), not more than 20 parts per million.
- Arsenic (as As), not more than 3 parts per million.
- Mercury (as Hg), not more than 1 part per million.
- Total color, not less than 96 percent.

(c) *Uses and restrictions.* D&C Yellow No. 11 may be safely used in externally applied drugs in amounts consistent with good manufacturing practice.

(d) *Labeling.* The label of the color additive and any mixtures prepared therefrom intended solely or in part for coloring purposes shall conform to the requirements of § 70.25 of this chapter.

(e) *Certification.* All batches of D&C Yellow No. 11 shall be certified in accordance with regulations in part 80 of this chapter.

Subpart C—Cosmetics

§ 74.2052 D&C Black No. 2.

(a) *Identity.* The color additive D&C Black No. 2 is a high-purity carbon black prepared by the oil furnace process. It is manufactured by the combustion of aromatic petroleum oil feedstock and consists essentially of pure carbon, formed as aggregated fine particles with a surface area range of 200 to 260 meters (m)²/gram.

(b) *Specifications.* D&C Black No. 2 shall conform to the following specifications and shall be free from impurities other than those named to the extent that such other impurities may be avoided by good manufacturing practice:

(1) Surface area by nitrogen BET (Brunauer, Emmett, Teller) method, 200 to 260 m²/gram.

(2) Weight loss on heating at 950 °C for 7 minutes (predried for 1 hour at 125 °C), not more than 2 percent.

(3) Ash content, not more than 0.15 percent.

(4) Arsenic (total), not more than 3 milligrams per kilogram (mg/kg) (3 parts per million).

(5) Lead (total), not more than 10 mg/kg (10 parts per million).

(6) Mercury (total), not more than 1 mg/kg (1 part per million).

(7) Total sulfur, not more than 0.65 percent.

(8) Total PAHs, not more than 0.5 mg/kg (500 parts per billion).

(9) Benzo[*a*]pyrene, not more than 0.005 mg/kg (5 parts per billion).

(10) Dibenz[*a,h*]anthracene, not more than 0.005 mg/kg (5 parts per billion).

(11) Total color (as carbon), not less than 95 percent.

(c) *Uses and restrictions.* D&C Black No. 2 may be safely used for coloring the following cosmetics in amounts consistent with current good manufacturing practice: Eyeliner, brush-on-brow, eye shadow, mascara, lipstick, blushers and rouge, makeup and foundation, and nail enamel.

(d) *Labeling.* The label of the color additive shall conform to the requirements of § 70.25 of this chapter.

(e) *Certification.* All batches of D&C Black No. 2 shall be certified in accordance with regulations in part 80 of this chapter.

[69 FR 44930, July 28, 2004, as amended at 72 FR 10357, Mar. 8, 2007]

§ 74.2101 FD&C Blue No. 1.

(a) *Identity.* The color additive FD&C Blue No. 1 is principally the disodium salt of ethyl[4-*p*-[ethyl(*m*-sulfobenzyl)amino]-*o*-sulfophenyl]benzylidene]-2,5-cyclohexadien-1-ylidene](*m*-sulfobenzyl)ammonium hydroxide inner salt with smaller amounts of the isomeric disodium salts of ethyl[4-*p*-[ethyl(*p*-sulfobenzyl)amino]-*o*-sulfophenyl]benzylidene]-2,5-cyclohexadien-1-ylidene](*p*-sulfobenzyl)ammonium hydroxide inner salt and ethyl[4-*p*-[ethyl(*o*-sulfobenzyl)amino]-*o*-