

(6) Anticipate heavy congestion of VFR traffic at or above 3,500 feet MSL; and

(7) Use caution to avoid high-speed civil and military aircraft transiting the area to or from Niagara Falls Airport.

(f) These procedures do not relieve pilots from the requirements of § 91.113 of this chapter to see and avoid other aircraft.

(g) Flight following, to and from the area, is available through Buffalo Approach.

[Doc. No. FAA-2002-13235, 68 FR 9795, Feb. 28, 2003]

### Subpart F—Valparaiso, Florida, Terminal Area

#### § 93.80 Applicability.

This subpart prescribes special air traffic rules for aircraft operating in the Valparaiso, Florida, Terminal Area.

[Doc. No. FAA-2002-13235, 68 FR 9795, Feb. 28, 2003]

#### § 93.81 Applicability and description of area.

The Valparaiso, Florida Terminal Area is designated as follows:

(a) North-South Corridor. The North-South Corridor includes the airspace extending upward from the surface up to, but not including, 18,000 feet MSL, bounded by a line beginning at:

Latitude 30°42'51" N., Longitude 86°38'02" W.;  
to  
Latitude 30°43'18" N., Longitude 86°27'37" W.;  
to  
Latitude 30°37'01" N., Longitude 86°27'37" W.;  
to  
Latitude 30°37'01" N., Longitude 86°25'30" W.;  
to  
Latitude 30°33'01" N., Longitude 86°25'30" W.;  
to  
Latitude 30°33'01" N., Longitude 86°25'00" W.;  
to  
Latitude 30°25'01" N., Longitude 86°25'00" W.;  
to  
Latitude 30°25'01" N., Longitude 86°38'12" W.;  
to  
Latitude 30°29'02" N., Longitude 86°38'02" W.;  
to point of beginning.

(b) East-West Corridor—The East-West Corridor is divided into three sections to accommodate the different altitudes as portions of the corridor un-

derlie restricted areas R-2915C, R-2919B, and R-2914B.

(1) The west section would include that airspace extending upward from the surface to but not including 8,500 feet MSL, bounded by a line beginning at: Latitude 30°22'47" N., Longitude 86°51'30" W.; then along the shoreline to Latitude 30°23'46" N., Longitude 86°38'15" W.; to Latitude 30°20'51" N., Longitude 86°38'50" W.; then 3 NM from and parallel to the shoreline to Latitude 30°19'31" N., Longitude 86°51'30" W.; to the beginning.

(2) The center section would include that airspace extending upward from the surface to but not including 18,000 feet MSL, bounded by a line beginning at:

Latitude 30°25'01" N., Longitude 86°38'12" W.;  
to  
Latitude 30°25'01" N., Longitude 86°25'00" W.;  
to  
Latitude 30°25'01" N., Longitude 86°22'26" W.;  
to  
Latitude 30°19'46" N., Longitude 86°23'45" W.;  
then 3 NM from and parallel to the shoreline to Latitude 30°20'51" N., Longitude 86°38'50" W.; to Latitude 30°23'46" N., Longitude 86°38'15" W.; to the beginning.

(3) The east section would include that airspace extending upward from the surface to but not including 8,500 feet MSL, bounded by a line beginning at:

Latitude 30°25'01" N., Longitude 86°22'26" W.;  
to  
Latitude 30°22'01" N., Longitude 86°08'00" W.;  
to  
Latitude 30°19'16" N., Longitude 85°56'00" W.;  
to  
Latitude 30°11'01" N., Longitude 85°56'00" W.;  
then 3 NM from and parallel to the shoreline to Latitude 30°19'46" N., Longitude 86°23'45" W.; to the beginning.

[Amdt. 93-70, 59 FR 46154, Sept. 6, 1994 as amended by Amdt. 93-82, 68 FR 9795, Feb. 28, 2003]

#### § 93.83 Aircraft operations.

(a) *North-South Corridor.* Unless otherwise authorized by ATC (including the Eglin Radar Control Facility), no person may operate an aircraft in flight within the North-South Corridor designated in § 93.81(b)(1) unless—

(1) Before operating within the corridor, that person obtains a clearance from the Eglin Radar Control Facility