

§ 590.515

(e) Incubator reject eggs shall not be brought into the official plant.

[36 FR 9814, May 28, 1971, as amended at 40 FR 20059, May 8, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981]

§ 590.515 Egg cleaning operations.

(a) The following requirements shall be met when washing shell eggs to be presented for breaking:

(1) Shell egg cleaning equipment shall be kept in good repair and shall be cleaned after each day's use or more frequently if necessary.

(2) The temperature of the wash water shall be maintained at 90 °F or higher, and shall be at least 20 °F warmer than the temperature of the eggs to be washed. These temperatures shall be maintained throughout the cleaning cycle.

(3) An approved cleaning compound shall be used in the wash water. (The use of metered equipment for dispensing the compound into solution is recommended.)

(4) Wash water shall be changed approximately every 4 hours or more often if needed to maintain sanitary conditions and at the end of each shift. Remedial measures shall be taken to prevent excess foaming during the egg washing operation.

(5) Replacement water shall be added continuously to the wash water of washers to maintain a continuous overflow. Rinse water and chlorine sanitizing rinse may be used as part of the replacement water. Iodine sanitizing rinse may not be used as part of the replacement water.

(6) Waste water from the egg washing operation shall be piped directly to drains.

(7) The washing operation shall be continuous and shall be completed as rapidly as possible. Eggs shall not be allowed to stand or soak in water. Immersion-type washers shall not be used.

(8) Prewetting shell eggs prior to washing may be accomplished by spraying a continuous flow of water over the eggs in a manner which permits the water to drain away, or by other methods which may be approved by the Administrator.

9 CFR Ch. III (1-1-07 Edition)

(b) Shell eggs shall not be washed in the breaking room or any room where edible products are processed.

[36 FR 9814, May 28, 1971, as amended at 40 FR 20059, May 8, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 60 FR 49170, Sept. 21, 1995]

§ 590.516 Sanitizing and drying of shell eggs prior to breaking.

(a) Immediately prior to breaking, all shell eggs shall be spray rinsed with potable water containing an approved sanitizer of not less than 100 ppm nor more than 200 ppm of available chlorine or its equivalent. Alternative procedures may be approved by the Administrator in lieu of sanitizing shell eggs washed in the plant.

(b) Shell eggs shall be sufficiently dry at time of breaking to prevent contamination or adulteration of the liquid egg product from free moisture on the shell.

[60 FR 49170, Sept. 21, 1995]

§ 590.520 Breaking room facilities.

(a) The breaking room shall have at least 30 foot-candles of light on all working surfaces except that light intensity shall be at least 50 foot-candles at breaking and inspection stations. Lights shall be protected with adequate safety devices.

(b) The surface of the ceiling and walls shall be smooth and made of a water-resistant material.

(c) The floor shall be of water-proof composition, reasonably free from cracks or rough surfaces, sloped for adequate drainage, and the intersections with walls and curbing shall be impervious to water.

(d) Ventilation shall provide for:

(1) A positive flow of outside filtered air through the room;

(2) Air of suitable working temperature during operations.

(e) There shall be provided adequate hand washing facilities which are easily accessible to all breaking personnel, an adequate supply of warm water, clean towels or other facilities for drying hands, odorless soap, and containers for used towels. Hand washing facilities shall be operated by other than hand operated controls.

(f) Containers for packaging egg products are not acceptable as liquid egg buckets.

(g) A suitable container conspicuously identified shall be provided for the disposal of rejected liquid.

(h) Strainers, filters, or centrifugal clarifiers of approved construction shall be provided for the effective removal of shell particles and foreign material, unless specific approval is obtained from the National Supervisor for other mechanical devices.

(i) A separate drawoff room with a filtered positive air ventilation system shall be provided for packaging liquid egg product, except product packaged by automatic, closed packaging systems.

[36 FR 9814, May 28, 1971, as amended at 37 FR 6659, Apr. 1, 1972. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981]

§ 590.522 Breaking room operations.

(a) The breaking room shall be kept in a dust-free clean condition and free from flies, insects, and rodents. The floor shall be kept clean and reasonably dry during breaking operations and free of egg meat and shells.

(b) All breaking room personnel shall wash their hands thoroughly with odorless soap and water each time they enter the breaking room and prior to receiving clean equipment after breaking an inedible egg.

(c) Paper towels or tissues shall be used at breaking tables, and shall not be reused. Cloth towels are not permitted.

(d) Breakers shall use a complete set of clean equipment when starting work and after lunch periods. All table equipment shall be rotated with clean equipment every 2½ hours.

(e) Cups shall not be filled to overflowing.

(f) Each shell egg shall be broken in a satisfactory and sanitary manner and inspected for wholesomeness by smelling the shell or the egg meat and by visual examination at the time of breaking. All egg meat shall be reexamined by a person qualified to perform such functions before being emptied into the tank or churn, except as otherwise approved by the National Supervisor.

(g) Shell particles, meat and blood spots, and other foreign material accidentally falling into the cups or trays shall be removed with a spoon or other approved instrument.

(h) Whenever an inedible egg is broken, the affected breaking equipment shall be cleaned and sanitized.

(i) Inedible and loss eggs as defined in § 590.510 apply to this section.

(j) The contents of any cup or other liquid egg receptacle containing one or more inedible or loss eggs shall be rejected.

(k) Contents of drip trays shall be emptied into a cup and smelled carefully before pouring into liquid egg bucket. Drip trays shall be emptied at least once for each 15 dozen eggs or every 15 minutes.

(l) Edible leakers as defined in § 590.510(c)(2) and checks which are liable to be smashed in the breaking operation shall be broken at a separate station by specially trained personnel.

(m) Ingredients and additives used in, or for, processing egg products, shall be handled in a clean and sanitary manner.

(n) Liquid egg containers shall not pass through the candling room.

(o) Test kits shall be provided and used to determine the strength of the sanitizing solution. (See §§ 590.515(a)(9) and 590.552.)

(p) Leaker trays shall be washed and sanitized whenever they become soiled and at the end of each shift.

(q) Shell egg containers whenever dirty shall be cleaned and drained; and shall be cleaned, sanitized, and drained at the end of each shift.

(r) Belt-type shell egg conveyors shall be cleaned and sanitized approximately every 4 hours in addition to continuous cleaning during operation. When not in use, belts shall be raised to permit air drying.

(s) Cups, knives, racks, separators, trays, spoons, liquid egg pails, and other breaking equipment, except for mechanical egg breaking equipment, shall be cleaned and sanitized at least every 2½ hours. This equipment shall be cleaned at the end of each shift and shall be clean and sanitized immediately prior to use.

(t) Utensils and dismantled equipment shall be drained and air dried on