

(2) Placement in such owner or operator's landfill will not present a risk of contamination of any "underground source of drinking water" (as that term is defined in 40 CFR 270.2).

[45 FR 33232, May 19, 1980, as amended at 47 FR 12318, Mar. 22, 1982; 47 FR 32369, July 26, 1982; 50 FR 18374, Apr. 30, 1985; 50 FR 28750, July 15, 1985; 51 FR 19177, May 28, 1986; 57 FR 54461, Nov. 18, 1992; 58 FR 46050, Aug. 31, 1993; 60 FR 35705, July 11, 1995; 70 FR 34585, June 14, 2005; 71 FR 16912, Apr. 4, 2006; 71 FR 40276, July 14, 2006]

**§ 265.315 Special requirements for containers.**

Unless they are very small, such as an ampule, containers must be either:

(a) At least 90 percent full when placed in the landfill; or

(b) Crushed, shredded, or similarly reduced in volume to the maximum practical extent before burial in the landfill.

[50 FR 16048, Apr. 23, 1985]

**§ 265.316 Disposal of small containers of hazardous waste in overpacked drums (lab packs).**

Small containers of hazardous waste in overpacked drums (lab packs) may be placed in a landfill if the following requirements are met:

(a) Hazardous waste must be packaged in non-leaking inside containers. The inside containers must be of a design and constructed of a material that will not react dangerously with, be decomposed by, or be ignited by the waste held therein. Inside containers must be tightly and securely sealed. The inside containers must be of the size and type specified in the Department of Transportation (DOT) hazardous materials regulations (49 CFR parts 173, 178 and 179), if those regulations specify a particular inside container for the waste.

(b) The inside containers must be overpacked in an open head DOT-specification metal shipping container (49 CFR parts 178 and 179) of no more than 416-liter (110 gallon) capacity and surrounded by, at a minimum, a sufficient quantity of sorbent material, determined to be nonbiodegradable in accordance with § 265.314(f), to completely sorb all of the liquid contents of the inside containers. The metal outer con-

tainer must be full after it has been packed with inside containers and sorbent material.

(c) The sorbent material used must not be capable of reacting dangerously with, being decomposed by, or being ignited by the contents of the inside containers in accordance with § 265.17(b).

(d) Incompatible wastes, as defined in § 260.10 of this chapter, must not be placed in the same outside container.

(e) Reactive waste, other than cyanide- or sulfide-bearing waste as defined in § 261.23(a)(5) of this chapter, must be treated or rendered non-reactive prior to packaging in accordance with paragraphs (a) through (d) of this section. Cyanide- and sulfide-bearing reactive waste may be packaged in accordance with paragraphs (a) through (d) of this section without first being treated or rendered non-reactive.

(f) Such disposal is in compliance with the requirements of 40 CFR part 268. Persons who incinerate lab packs according to the requirements in 40 CFR 268.42(c)(1) may use fiber drums in place of metal outer containers. Such fiber drums must meet the DOT specifications in 49 CFR 173.12 and be overpacked according to the requirements in paragraph (b) of this section.

[46 FR 56596, Nov. 17, 1981, as amended at 55 FR 22686, June 1, 1990; 57 FR 54461, Nov. 18, 1992; 71 FR 40276, July 14, 2006]

**Subpart O—Incinerators**

SOURCE: 46 FR 7680, Jan. 23, 1981, unless otherwise noted.

**§ 265.340 Applicability.**

(a) The regulations of this subpart apply to owners and operators of hazardous waste incinerators (as defined in § 260.10 of this chapter), except as § 265.1 provides otherwise.

(b) *Integration of the MACT standards.* (1) Except as provided by paragraphs (b)(2) and (b)(3) of this section, the standards of this part no longer apply when an owner or operator demonstrates compliance with the maximum achievable control technology (MACT) requirements of part 63, subpart EEE, of this chapter by conducting a comprehensive performance test and submitting to the Administrator a Notification of Compliance

## § 265.341

under §§ 63.1207(j) and 63.1210(d) of this chapter documenting compliance with the requirements of part 63, subpart EEE, of this chapter.

(2) The MACT standards do not replace the closure requirements of § 264.351 or the applicable requirements of subparts A through H, BB and CC of this part.

(3) Section 265.345 generally prohibiting burning of hazardous waste during startup and shutdown remains in effect if you elect to comply with § 270.235(b)(1)(i) of this chapter to minimize emissions of toxic compounds from startup and shutdown.

(c) Owners and operators of incinerators burning hazardous waste are exempt from all of the requirements of this subpart, except § 265.351 (Closure), provided that the owner or operator has documented, in writing, that the waste would not reasonably be expected to contain any of the hazardous constituents listed in part 261, appendix VIII, of this chapter, and such documentation is retained at the facility, if the waste to be burned is:

(1) Listed as a hazardous waste in part 261, subpart D, of this chapter solely because it is ignitable (Hazard Code D), corrosive (Hazard Code C), or both; or

(2) Listed as a hazardous waste in part 261, subpart D, of this chapter solely because it is reactive (Hazard Code R) for characteristics other than those listed in § 261.23(a) (4) and (5), and will not be burned when other hazardous wastes are present in the combustion zone; or

(3) A hazardous waste solely because it possesses the characteristic of ignitability, corrosivity, or both, as determined by the tests for characteristics of hazardous wastes under part 261, subpart C, of this chapter; or

(4) A hazardous waste solely because it possesses the reactivity characteristics described by § 261.23(a) (1), (2), (3), (6), (7), or (8) of this chapter, and will not be burned when other hazardous wastes are present in the combustion zone.

[47 FR 27533, June 24, 1982 and 50 FR 666, Jan. 4, 1985, as amended at 50 FR 49203, Nov. 29, 1985; 56 FR 7208, Feb. 21, 1991; 64 FR 53075, Sept. 30, 1999; 67 FR 6816, Feb. 13, 2002; 70 FR 59575, Oct. 12, 2005]

## 40 CFR Ch. I (7-1-07 Edition)

### § 265.341 Waste analysis.

In addition to the waste analyses required by § 265.13, the owner or operator must sufficiently analyze any waste which he has not previously burned in his incinerator to enable him to establish steady state (normal) operating conditions (including waste and auxiliary fuel feed and air flow) and to determine the type of pollutants which might be emitted. At a minimum, the analysis must determine:

(a) Heating value of the waste;

(b) Halogen content and sulfur content in the waste; and

(c) Concentrations in the waste of lead and mercury, unless the owner or operator has written, documented data that show that the element is not present.

[*Comment:* As required by § 265.73, the owner or operator must place the results from each waste analysis, or the documented information, in the operating record of the facility.]

### §§ 265.342-265.344 [Reserved]

### § 265.345 General operating requirements.

During start-up and shut-down of an incinerator, the owner or operator must not feed hazardous waste unless the incinerator is at steady state (normal) conditions of operation, including steady state operating temperature and air flow.

### § 265.346 [Reserved]

### § 265.347 Monitoring and inspections.

The owner or operator must conduct, as a minimum, the following monitoring and inspections when incinerating hazardous waste:

(a) Existing instruments which relate to combustion and emission control must be monitored at least every 15 minutes. Appropriate corrections to maintain steady state combustion conditions must be made immediately either automatically or by the operator. Instruments which relate to combustion and emission control would normally include those measuring waste feed, auxiliary fuel feed, air flow, incinerator temperature, scrubber flow, scrubber pH, and relevant level controls.