

§ 434.30

NSPS EFFLUENT LIMITATIONS (MG/L)

| Pollutant or pollutant property | Maximum for any 1 day | Average of daily values for 30 consecutive days |
|---------------------------------|-----------------------|---|
| Iron, total | 6.0 | 3.0 |
| TSS | 70 | 35 |
| pH | (¹) | (¹) |

¹ 6.0–9.0 at all times.

Subpart C—Acid or Ferruginous Mine Drainage

§ 434.30 Applicability; description of the acid or ferruginous mine drainage subcategory.

The provisions of this subpart are applicable to acid or ferruginous mine drainage from an active mining area resulting from the mining of coal of any rank including, but not limited to, bituminous, lignite, and anthracite.

§ 434.31 [Reserved]

§ 434.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30–125.32, 40 CFR 401.17, and §§ 434.61, 434.62 and 434.63 of this part, the following limitations establish the concentration or quality of pollutants which may be discharged by a point source subject to the provisions of this subpart after application of the best practicable control technology currently available:

BPT EFFLUENT LIMITATIONS

| Pollutant or pollutant property | Maximum for any 1 day | Average of daily values for 30 consecutive days |
|---------------------------------|-----------------------|---|
| | Concentration in mg/l | |
| Iron, total | 7.0 | 3.5 |
| Manganese, total | 4.0 | 2.0 |
| TSS | 70.0 | 35.0 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0 at all times.

40 CFR Ch. I (7–1–07 Edition)

§ 434.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

Except as provided in 40 CFR 125.30–125.32, 40 CFR 401.17, and §§ 434.61, 434.62 and 434.63 of this part, the following limitations establish the concentration or quality of pollutants which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

BPT EFFLUENT LIMITATIONS

| Pollutant or pollutant property | Maximum for any 1 day | Average of daily values for 30 consecutive days |
|---------------------------------|-----------------------|---|
| | Concentration in mg/l | |
| Iron, total | 7.0 | 3.5 |
| Manganese, total | 4.0 | 2.0 |

§ 434.34 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best conventional pollutant control technology (BCT). [Reserved]

§ 434.35 New source performance standards (NSPS).

Except as provided in 40 CFR 401.17, and §§ 434.61, 434.62 and 434.63 of this part, the following new source performance standards shall be achieved for any discharge from a new source subject to this subpart:

NSPS EFFLUENT LIMITATIONS

| Pollutant or pollutant property | Maximum for any 1 day | Average of daily values for 30 consecutive days |
|---------------------------------|-----------------------|---|
| | Concentration in mg/l | |
| Iron, total | 6.0 | 3.0 |
| Manganese, total | 4.0 | 2.0 |
| TSS | 70.0 | 35.0 |
| pH | (¹) | (¹) |

¹ Within the range 6.0 to 9.0 at all times.