

§ 471.82

40 CFR Ch. I (7-1-07 Edition)

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.002	0.0007
Copper .....	0.007	0.004
Cyanide .....	0.001	0.0004
Zinc .....	0.005	0.002
Oil and grease .....	0.071	0.043
TSS .....	0.146	0.069
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(k) *Alkaline cleaning rinse.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.744	0.304
Copper .....	3.21	1.69
Cyanide .....	0.490	0.203
Zinc .....	2.47	1.03
Oil and grease .....	33.8	20.3
TSS .....	69.3	33.0
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(l) *Sawing or grinding spent emulsions.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc sawed or ground with emulsions	
Chromium .....	0.011	0.005
Copper .....	0.045	0.024
Cyanide .....	0.007	0.003
Zinc .....	0.035	0.015
Oil and grease .....	0.476	0.286
TSS .....	0.976	0.464
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(m) *Electrocoating rinse.*

SUBPART H—BPT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc electrocoated	
Chromium .....	1.01	0.412
Copper .....	4.35	2.29
Cyanide .....	0.664	0.275
Zinc .....	3.35	1.40
Oil and grease .....	45.8	27.5
TSS .....	93.9	44.7
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(n) *Degreasing spent solvents—Subpart H—BPT.* There shall be no discharge of process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

**§ 471.82 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT):

(a) *Rolling spent neat oils—Subpart H—BAT.* There shall be no discharge of process wastewater pollutants.

(b) *Rolling spent emulsions.*

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with emulsions	
Chromium .....	0.0005	0.0002
Copper .....	0.002	0.0009
Cyanide .....	0.0003	0.0001
Zinc .....	0.002	0.0006

(c) *Rolling contact cooling water.*

**Environmental Protection Agency**

**§ 471.82**

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with contact cooling water	
Chromium .....	0.020	0.009
Copper .....	0.069	0.033
Cyanide .....	0.011	0.004
Zinc .....	0.055	0.023

*(d) Drawing spent emulsions.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc drawn with emulsions	
Chromium .....	0.002	0.0009
Copper .....	0.008	0.004
Cyanide .....	0.001	0.0005
Zinc .....	0.006	0.003

*(e) Direct chill casting contact cooling water.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc cast by the direct chill method	
Chromium .....	0.019	0.008
Copper .....	0.065	0.031
Cyanide .....	0.010	0.004
Zinc .....	0.052	0.021

*(f) Stationary casting contact cooling water—Subpart H—BAT.* There shall be no discharge of process wastewater pollutants.

*(g) Heat treatment contact cooling water.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc heat treated	
Chromium .....	0.029	0.012
Copper .....	0.098	0.047
Cyanide .....	0.016	0.006
Zinc .....	0.078	0.032

*(h) Surface treatment spent baths.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc surface treated	
Chromium .....	0.033	0.014
Copper .....	0.114	0.054
Cyanide .....	0.018	0.007
Zinc .....	0.091	0.038

*(i) Surface treatment rinse.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc surface treated	
Chromium .....	0.133	0.054
Copper .....	0.457	0.219
Cyanide .....	0.072	0.029
Zinc .....	0.365	0.151

*(j) Alkaline cleaning spent baths.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.002	0.0006
Copper .....	0.005	0.002
Cyanide .....	0.0007	0.0003
Zinc .....	0.004	0.002

*(k) Alkaline cleaning rinse.*

**SUBPART H—BAT**

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc alkaline cleaned	
Chromium .....	0.626	0.254
Copper .....	2.17	1.03
Cyanide .....	0.338	0.135
Zinc .....	1.73	0.710

*(l) Sawing or grinding spent emulsions.*

§ 471.83

40 CFR Ch. I (7-1-07 Edition)

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc sawed or ground with emulsions	
Chromium .....	0.009	0.004
Copper .....	0.031	0.015
Cyanide .....	0.005	0.002
Zinc .....	0.025	0.010

(m) *Electrocoating rinse.*

SUBPART H—BAT

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc electrocoated	
Chromium .....	0.085	0.035
Copper .....	0.293	0.140
Cyanide .....	0.046	0.019
Zinc .....	0.234	0.096

(n) *Degreasing spent solvents—Subpart H—BAT.* There shall be no discharge or process wastewater pollutants.

[50 FR 34270, Aug. 23, 1985; 51 FR 2888, Jan. 22, 1986]

§ 471.83 New source performance standards (NSPS).

Any new source subject to this subpart must achieve the following new source performance standards (NSPS):

(a) *Rolling spent neat oils—Subpart H—NSPS.* There shall be no discharge of process wastewater pollutants.

(b) *Rolling spent emulsions.*

SUBPART H—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with emulsions	
Chromium .....	0.0005	0.0002
Copper .....	0.002	0.0009
Cyanide .....	0.0003	0.0001
Zinc .....	0.002	0.0006
Oil and grease .....	0.014	0.014
TSS .....	0.021	0.017
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) *Rolling contact cooling water.*

SUBPART H—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc rolled with contact cooling water	
Chromium .....	0.020	0.009
Copper .....	0.069	0.037
Cyanide .....	0.011	0.004
Zinc .....	0.055	0.023
Oil and grease .....	0.536	0.536
TSS .....	0.804	0.643
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(d) *Drawing spent emulsions.*

SUBPART H—NSPS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc drawn with emulsions	
Chromium .....	0.002	0.0009
Copper .....	0.008	0.004
Cyanide .....	0.001	0.0005
Zinc .....	0.006	0.003
Oil and grease .....	0.058	0.058
TSS .....	0.087	0.070
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times

(e) *Direct chill casting contact cooling water.*

SUBPART H—NSPS

Pollutant or pollutant property	Maximum for any one day	Maximum for monthly average
	mg/off-kg (pounds per million off-pounds) of zinc cast by the direct chill method	
Chromium .....	0.019	0.008
Copper .....	0.065	0.031
Cyanide .....	0.010	0.004
Zinc .....	0.052	0.021
Oil and grease .....	0.505	0.505
TSS .....	0.758	0.606
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(f) *Stationary casting contact cooling water—Subpart H—NSPS.* There shall be no discharge of process wastewater pollutants.

(g) *Heat treatment contact cooling water.*