

## § 745.61

- 745.228 Accreditation of training programs: public and commercial buildings, bridges and superstructures. [Reserved]
- 745.229 Certification of individuals and firms engaged in lead-based paint activities: public and commercial buildings, bridges and superstructures. [Reserved]
- 745.230 Work practice standards for conducting lead-based paint activities: public and commercial buildings, bridges and superstructures. [Reserved]
- 745.233 Lead-based paint activities requirements.
- 745.235 Enforcement.
- 745.237 Inspections.
- 745.238 Fees for accreditation and certification of lead-based paint activities.
- 745.239 Effective dates.

### Subparts M–P [Reserved]

#### Subpart Q—State and Indian Tribal Programs

- 745.320 Scope and purpose.
- 745.323 Definitions.
- 745.324 Authorization of State or Tribal programs.
- 745.325 Lead-based paint activities: State and Tribal program requirements.
- 745.326 Pre-renovation notification: State and Tribal program requirements.
- 745.327 State or Indian Tribal lead-based paint compliance and enforcement programs.
- 745.339 Effective dates.

AUTHORITY: 15 U.S.C. 2605, 2607, 2681–2692 and 42 U.S.C. 4852d.

SOURCE: 61 FR 9085, Mar. 6, 1996, unless otherwise noted.

### Subparts A–C [Reserved]

#### Subpart D—Lead-Based Paint Hazards

SOURCE: 66 FR 1237, Jan. 5, 2001, unless otherwise noted.

##### § 745.61 Scope and applicability.

(a) This subpart identifies lead-based paint hazards.

(b) The standards for lead-based paint hazards apply to target housing and child-occupied facilities.

(c) Nothing in this subpart requires the owner of property(ies) subject to these standards to evaluate the property(ies) for the presence of lead-based paint hazards or take any action to control these conditions if one or more of them is identified.

## 40 CFR Ch. I (7–1–07 Edition)

### § 745.63 Definitions.

The following definitions apply to part 745.

*Arithmetic mean* means the algebraic sum of data values divided by the number of data values (e.g., the sum of the concentration of lead in several soil samples divided by the number of samples).

*Chewable surface* means an interior or exterior surface painted with lead-based paint that a young child can mouth or chew. A chewable surface is the same as an “accessible surface” as defined in 42 U.S.C. 4851b(2)). Hard metal substrates and other materials that cannot be dented by the bite of a young child are not considered chewable.

*Common area group* means a group of common areas that are similar in design, construction, and function. Common area groups include, but are not limited to hallways, stairwells, and laundry rooms.

*Concentration* means the relative content of a specific substance contained within a larger mass, such as the amount of lead (in micrograms per gram or parts per million by weight) in a sample of dust or soil.

*Deteriorated paint* means any interior or exterior paint or other coating that is peeling, chipping, chalking or cracking, or any paint or coating located on an interior or exterior surface or fixture that is otherwise damaged or separated from the substrate.

*Dripline* means the area within 3 feet surrounding the perimeter of a building.

*Friction surface* means an interior or exterior surface that is subject to abrasion or friction, including, but not limited to, certain window, floor, and stair surfaces.

*Impact surface* means an interior or exterior surface that is subject to damage by repeated sudden force such as certain parts of door frames.

*Interior window sill* means the portion of the horizontal window ledge that protrudes into the interior of the room.

*Lead-based paint hazard* means hazardous lead-based paint, dust-lead hazard or soil-lead hazard as identified in § 745.65.

*Loading* means the quantity of a specific substance present per unit of surface area, such as the amount of lead in micrograms contained in the dust collected from a certain surface area divided by the surface area in square feet or square meters.

*Mid-yard* means an area of a residential yard approximately midway between the dripline of a residential building and the nearest property boundary or between the driplines of a residential building and another building on the same property.

*Play area* means an area of frequent soil contact by children of less than 6 years of age as indicated by, but not limited to, such factors including the following: the presence of play equipment (e.g., sandboxes, swing sets, and sliding boards), toys, or other children's possessions, observations of play patterns, or information provided by parents, residents, care givers, or property owners.

*Residential building* means a building containing one or more residential dwellings.

*Room* means a separate part of the inside of a building, such as a bedroom, living room, dining room, kitchen, bathroom, laundry room, or utility room. To be considered a separate room, the room must be separated from adjoining rooms by built-in walls or archways that extend at least 6 inches from an intersecting wall. Half walls or bookcases count as room separators if built-in. Movable or collapsible partitions or partitions consisting solely of shelves or cabinets are not considered built-in walls. A screened in porch that is used as a living area is a room.

*Soil sample* means a sample collected in a representative location using ASTM E1727, "Standard Practice for Field Collection of Soil Samples for Lead Determination by Atomic Spectrometry Techniques," or equivalent method.

*Weighted arithmetic mean* means the arithmetic mean of sample results weighted by the number of subsamples in each sample. Its purpose is to give influence to a sample relative to the surface area it represents. A single surface sample is comprised of a single subsample. A composite sample may contain from two to four subsamples of

the same area as each other and of each single surface sample in the composite. The weighted arithmetic mean is obtained by summing, for all samples, the product of the sample's result multiplied by the number of subsamples in the sample, and dividing the sum by the total number of subsamples contained in all samples. For example, the weighted arithmetic mean of a single surface sample containing 60  $\mu\text{g}/\text{ft}^2$ , a composite sample (three subsamples) containing 100  $\mu\text{g}/\text{ft}^2$ , and a composite sample (4 subsamples) containing 110  $\mu\text{g}/\text{ft}^2$  is 100  $\mu\text{g}/\text{ft}^2$ . This result is based on the equation  $[60+(3*100)+(4*110)]/(1+3+4)$ .

*Window trough* means, for a typical double-hung window, the portion of the exterior window sill between the interior window sill (or stool) and the frame of the storm window. If there is no storm window, the window trough is the area that receives both the upper and lower window sashes when they are both lowered. The window trough is sometimes referred to as the window "well."

*Wipe sample* means a sample collected by wiping a representative surface of known area, as determined by ASTM E1728, "Standard Practice for Field Collection of Settled Dust Samples Using Wipe Sampling Methods for Lead Determination by Atomic Spectrometry Techniques, or equivalent method, with an acceptable wipe material as defined in ASTM E 1792, "Standard Specification for Wipe Sampling Materials for Lead in Surface Dust."

#### § 745.65 Lead-based paint hazards.

(a) *Paint-lead hazard*. A paint-lead hazard is any of the following:

(1) Any lead-based paint on a friction surface that is subject to abrasion and where the lead dust levels on the nearest horizontal surface underneath the friction surface (e.g., the window sill, or floor) are equal to or greater than the dust-lead hazard levels identified in paragraph (b) of this section.

(2) Any damaged or otherwise deteriorated lead-based paint on an impact surface that is caused by impact from a related building component (such as a door knob that knocks into a wall or a door that knocks against its door frame).