

§ 74.1711

impurities may be avoided by current good manufacturing practice:

Sum of volatile matter at 135 °C (275 °F) and chlorides and sulfates (calculated as sodium salts), not more than 15 percent.

Matter insoluble in both water and chloroform, not more than 0.2 percent.

Total sulfonated quinaldines, sodium salts, not more than 0.2 percent.

Total sulfonated phthalic acids, sodium salts, not more than 0.2 percent.

2-(2-Quinoliny)-1*H*-indene-1,3 (2*H*)-dione, not more than 4 parts per million.

Sum of sodium salts of the monosulfonates of 2-(2-quinoliny)-1*H*-indene-1,3 (2*H*)-dione, not less than 75 percent.

Sum of sodium salts of the disulfonates of 2-(2-quinoliny)-1*H*-indene-1,3 (2*H*)-dione, not more than 15 percent.

2-(2,3-Dihydro-1,3-dioxo-1*H*-indene-2-yl)-6, 8-quinolinedisulfonic acid, disodium salt, not more than 3 percent.

Diethyl ether soluble matter other than that specified, not more than 2 parts per million, using added 2-(2-quinoliny)-1*H*-indene-1,3 (2*H*)-dione for calibration.

Lead (as Pb), not more than 20 parts per million.

Arsenic (as As), not more than 3 parts per million.

Mercury (as Hg), not more than 1 part per million.

Total color, not less than 85 percent.

(c) *Uses and restrictions.* The color additive D&C Yellow No. 10 may be safely used for coloring drugs generally in amounts consistent with current good manufacturing practice.

(d) *Labeling.* The label of the color additive and any mixtures prepared therefrom and intended solely or in part for coloring purposes shall conform to the requirements of § 70.25 of this chapter.

(e) *Certification.* All batches of D&C Yellow No. 10 shall be certified in accordance with regulations in part 80 of this chapter.

[48 FR 39219, Aug. 30, 1983, as amended at 49 FR 8432, Mar. 7, 1984]

§ 74.1711 D&C Yellow No. 11.

(a) *Identity.* (1) The color additive D&C Yellow No. 11 is principally 2-(2-quinoliny)-1,3-indandione.

(2) Color additive mixtures, for drug use made with D&C Yellow No. 11 may contain only those diluents that are suitable and that are listed in part 73 of this chapter as safe for use in color

21 CFR Ch. I (4–1–08 Edition)

additive mixtures for coloring externally applied drugs.

(b) *Specifications.* D&C Yellow No. 11 shall conform to the following specifications and shall be free from impurities, other than those named, to the extent that such other impurities may be avoided by good manufacturing practice:

Volatile matter (at 135 °C), not more than 1 percent.

Ethyl alcohol-insoluble matter, not more than 0.4 percent.

Phthalic acid, not more than 0.3 percent.

Quinaldine, not more than 0.2 percent.

Subsidiary colors, not more than 5 percent.

Lead (as Pb), not more than 20 parts per million.

Arsenic (as As), not more than 3 parts per million.

Mercury (as Hg), not more than 1 part per million.

Total color, not less than 96 percent.

(c) *Uses and restrictions.* D&C Yellow No. 11 may be safely used in externally applied drugs in amounts consistent with good manufacturing practice.

(d) *Labeling.* The label of the color additive and any mixtures prepared therefrom intended solely or in part for coloring purposes shall conform to the requirements of § 70.25 of this chapter.

(e) *Certification.* All batches of D&C Yellow No. 11 shall be certified in accordance with regulations in part 80 of this chapter.

Subpart C—Cosmetics

§ 74.2052 D&C Black No. 2.

(a) *Identity.* The color additive D&C Black No. 2 is a high-purity carbon black prepared by the oil furnace process. It is manufactured by the combustion of aromatic petroleum oil feedstock and consists essentially of pure carbon, formed as aggregated fine particles with a surface area range of 200 to 260 meters (m)²/gram.

(b) *Specifications.* D&C Black No. 2 shall conform to the following specifications and shall be free from impurities other than those named to the extent that such other impurities may be avoided by good manufacturing practice:

(1) Surface area by nitrogen BET (Brunauer, Emmett, Teller) method, 200 to 260 m²/gram.