

§51.1547

(3) *U.S. Commercial.* A total of 20 percent for potatoes in any lot which fail to meet the requirements for the grade: *Provided*, That included in this tolerance not more than the following percentages shall be allowed for the defects listed:

(i) 10 percent for potatoes which fail to meet the requirements for U.S. No. 2 grade, including therein not more than:

(ii) 6 percent for external defects;

(iii) 6 percent for internal defects; or,

(iv) 3 percent for potatoes which are affected by freezing, southern bacterial wilt, ring rot, late blight, soft rot or wet breakdown, including therein not more than 1 percent for potatoes which are frozen or affected by soft rot or wet breakdown. See §51.1547.

(4) *U.S. No. 2.* A total of 10 percent for potatoes in any lot which fail to meet the requirements for the grade: *Provided*, That included in this tolerance not more than the following percentages shall be allowed for the defects listed:

(i) 6 percent for external defects;

(ii) 6 percent for internal defects; or,

(iii) 3 percent for potatoes which are affected by freezing, southern bacterial wilt, ring rot, late blight, soft rot or wet breakdown, including therein not more than 1 percent for potatoes which are frozen or affected by soft rot or wet breakdown. See §51.1547.

(b) *For off-size.* (1) Not more than 3 percent of the potatoes in any lot may be smaller than the required or specified minimum size except that a tolerance of 5 percent shall be allowed for potatoes packed to meet a minimum size of 2¼ inches or larger in diameter or 5 ounces or more in weight. In addition, not more than 10 percent may be larger than any required or specified maximum size. See §51.1547.

(2) When a percentage of the potatoes is specified to be of a certain size and larger, individual samples shall have not less than one-half of the percentage specified: *Provided*, That the average for the entire lot is not less than the percentage specified.

[35 FR 18258, Dec. 1, 1970. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981; amended at 56 FR 7553, Feb. 25, 1991]

7 CFR Ch. I (1-1-08 Edition)

APPLICATION OF TOLERANCES

§ 51.1547 Application of tolerances.

Individual samples shall have not more than double the tolerances specified, except that at least one defective and one off-size potato may be permitted in any sample: *Provided*, That en route or at destination one-tenth of the samples may contain three times the tolerance permitted for potatoes which are frozen or affected by soft rot or wet breakdown: *And provided further*, That the averages for the entire lot are within the tolerances specified for the grade.

SAMPLES FOR GRADE AND SIZE DETERMINATION

§ 51.1548 Samples for grade and size determination.

Individual samples shall consist of at least 20 pounds. When individual packages contain at least 20 pounds, each individual sample is drawn from one package; when packages contain less than 20 pounds, a sufficient number of adjoining packages are opened to provide at least a 20-pound sample. The number of such individual samples drawn for grade and size determination will vary with the size of the lot.

SKINNING

§ 51.1549 Skinning.

(a) The following definitions provide a basis for describing lots of potatoes as to the degree of skinning whenever description may be appropriate:

(1) "Practically no skinning" means that not more than 5 percent of the potatoes in the lot have more than one-tenth of the skin missing or "feathered";

(2) "Slightly skinned" means that not more than 10 percent of the potatoes in the lot have more than one-fourth of the skin missing or "feathered";

(3) "Moderately skinned" means that not more than 10 percent of the potatoes in the lot have more than one-half of the skin missing or "feathered"; and

(4) "Badly skinned" means that more than 10 percent of the potatoes in the lot have more than one-half of the skin missing or "feathered".