

## § 412.40

accumulation, design treatment volume, total design volume, and approximate number of days of storage capacity;

(6) Records of the date, time, and estimated volume of any overflow.

(c) *Recordkeeping requirements for the land application areas.* Each CAFO must maintain on-site a copy of its site-specific nutrient management plan. Each CAFO must maintain on-site for a period of five years from the date they are created a complete copy of the information required by § 412.4 and 40 CFR 122.42(e)(1)(ix) and the records specified in paragraphs (c)(1) through (c)(10) of this section. The CAFO must make these records available to the Director and, in an authorized State, the Regional Administrator, or his or her designee, for review upon request.

(1) Expected crop yields;

(2) The date(s) manure, litter, or process waste water is applied to each field;

(3) Weather conditions at time of application and for 24 hours prior to and following application;

(4) Test methods used to sample and analyze manure, litter, process waste water, and soil;

(5) Results from manure, litter, process waste water, and soil sampling;

(6) Explanation of the basis for determining manure application rates, as provided in the technical standards established by the Director.

(7) Calculations showing the total nitrogen and phosphorus to be applied to each field, including sources other than manure, litter, or process wastewater;

(8) Total amount of nitrogen and phosphorus actually applied to each field, including documentation of calculations for the total amount applied;

(9) The method used to apply the manure, litter, or process wastewater;

(10) Date(s) of manure application equipment inspection.

### Subpart D—Swine, Poultry, and Veal Calves

#### § 412.40 Applicability.

This subpart applies to operations defined as concentrated animal feeding operations (CAFOs) under 40 CFR 122.23 and includes the following animals: swine; chickens; turkeys; and veal

## 40 CFR Ch. I (7–1–08 Edition)

calves. This subpart does not apply to such CAFOs with less than the following capacities: 2,500 swine each weighing 55 lbs. or more; 10,000 swine each weighing less than 55 lbs.; 30,000 laying hens or broilers if the facility uses a liquid manure handling system; 82,000 laying hens if the facility uses other than a liquid manure handling system; 125,000 chickens other than laying hens if the facility uses other than a liquid manure handling system; 55,000 turkeys; and 1,000 veal calves.

#### §§ 412.41–412.42 [Reserved]

#### § 412.43 Effluent limitations attainable by the application of the best practicable control technology currently available (BPT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BPT:

(a) *For CAFO production areas.* (1) The CAFO shall attain the same limitations and requirements as § 412.31(a)(1) through (a)(2).

(2) The CAFO shall attain the limitations and requirements of this paragraph as of the date of permit coverage.

(b) *For CAFO land application areas.* (1) The CAFO shall attain the same limitations and requirements as § 412.31(b)(1) and (b)(2).

(2) The CAFO shall attain the limitations and requirements of this paragraph by February 27, 2009.

[68 FR 7269, Feb. 12, 2003, as amended at 71 FR 6984, Feb. 10, 2006; 72 FR 40250, July 24, 2007]

#### § 412.44 Effluent limitations attainable by the application of the best conventional pollutant control technology (BCT).

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BCT:

(a) *For CAFO production areas:* the CAFO shall attain the same limitations and requirements as § 412.43(a).

(b) For CAFO land application areas: the CAFO shall attain the same limitations and requirements as § 412.43(b).

**§ 412.45 Effluent limitations attainable by the application of the best available technology economically achievable (BAT).**

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the application of BAT:

(a) For CAFO production areas: the CAFO shall attain the same limitations and requirements as § 412.43(a).

(b) For CAFO land application areas: the CAFO shall attain the same limitations and requirements as § 412.43(b).

**§ 412.46 New source performance standards (NSPS).**

Any new source subject to this subpart must achieve the following effluent limitations representing the application of NSPS:

(a) For CAFO production areas. There must be no discharge of manure, litter, or process wastewater pollutants into waters of the U.S. from the production area, subject to paragraphs (a)(1) through (a)(3) of this section.

(1) Waste management and storage facilities designed, constructed, operated, and maintained to contain all manure, litter, and process wastewater including the runoff and the direct precipitation from a 100-year, 24-hour rainfall event and operated in accordance with the additional measures and records required by § 412.47(a) and (b), will fulfill the requirements of this section.

(2) The production area must be operated in accordance with the additional measures required by § 412.47(a) and (b).

(3) Provisions for upset/bypass, as provided in 40 CFR 122.41(m)–(n), apply to a new source subject to this provision.

(b) For CAFO land application areas: the CAFO shall attain the same limitations and requirements as § 412.43(b)(1).

(c) The CAFO shall attain the limitations and requirements of this paragraph as of the date of permit coverage.

(d) Voluntary superior environmental performance standards. Any new source

CAFO subject to this subpart may request the Director to establish alternative NPDES permit limitations based upon a demonstration that site-specific innovative technologies will achieve overall environmental performance across all media which is equal to or superior to the reductions achieved by baseline standards as provided by § 412.46(a). The quantity of pollutants discharged from the production area must be accompanied by an equivalent or greater reduction in the quantity of pollutants released to other media from the production area (e.g., air emissions from housing and storage) and/or land application areas for all manure, litter, and process wastewater at on-site and off-site locations. The comparison of quantity of pollutants must be made on a mass basis where appropriate. The Director has the discretion to request supporting information to supplement such a request.

(e) Any source subject to this subpart that commenced discharging after April 14, 1993, and prior to April 14, 2003, which was a new source subject to the standards specified in § 412.15, revised as of July 1, 2002, must continue to achieve those standards for the applicable time period specified in 40 CFR 122.29(d)(1). Thereafter, the source must achieve the standards specified in § 412.43(a) and (b).

**§ 412.47 Additional measures.**

(a) Each CAFO subject to this subpart must implement the requirements of § 412.37(a).

(b) Each CAFO subject to this subpart must comply with the record-keeping requirements of § 412.37(b).

(c) Each CAFO subject to this subpart must comply with the record-keeping requirements of § 412.37(c).

**PART 413—ELECTROPLATING POINT SOURCE CATEGORY**

GENERAL PROVISIONS

Sec.

- 413.01 Applicability and compliance dates.
- 413.02 General definitions.
- 413.03 Monitoring requirements.
- 413.04 Standards for integrated facilities.