

Environmental Protection Agency

§ 420.74

(d) *Pipe and tube mills, carbon and specialty.*

SUBPART G

Pollutant or pollutant property	BPT effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.212	0.0795
O&G	0.0530
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0

§ 420.73 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable (BAT).

The Agency has determined that there are not significant quantities of toxic pollutants in hot forming wastewaters after compliance with applicable BPT limitations. Accordingly, since the BPT level of treatment provides adequate control, the Agency is not promulgating more stringent BAT limitations.

§ 420.74 New source performance standards (NSPS).

The discharge of wastewater pollutants from any new source subject to this subpart shall not exceed the standards set forth below.

(a) *Primary mills, carbon and specialty—(1) Without scarfing.*

SUBPART G

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0150	0.00563
O&G	0.00373
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(2) *With scarfing.*

SUBPART G

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0234	0.00876
O&G	0.00584
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(b) *Section mills—(1) Carbon.*

SUBPART G

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0334	0.0125
O&G	0.00834
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(2) *Specialty.*

SUBPART G

Pollutant or pollutant property	New source performance standards	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kkg (pounds per 1,000 lb) of product	
TSS	0.0217	0.00813
O&G	0.00542
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

(c) *Flat mills—(1) Hot strip and sheet mills, carbon and specialty.*