

§ 421.137

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from smelting	
Antimony247	.110
Arsenic178	.073
Lead036	.017
Zinc131	.054
Ammonia (as N)000	.000

§ 421.137 [Reserved]

Subpart N—Primary Antimony Subcategory

SOURCE: 50 FR 38345, Sept. 20, 1985, unless otherwise noted.

§ 421.140 Applicability: Description of the primary antimony subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of antimony at primary antimony facilities.

§ 421.141 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.142 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available:

(a) Sodium Antimonate Autoclave Wastewater.

40 CFR Ch. I (7–1–08 Edition)

BPT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony contained in sodium antimonate product	
Antimony	44.840	20.000
Arsenic	32.650	14.530
Mercury	3.906	1.562
Total suspended solids	640.600	304.700
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Fouled anolyte.

BPT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony	44.840	20.000
Arsenic	32.650	14.530
Mercury	3.906	1.562
Total suspended solids	640.600	304.700
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Cathode Antimony Wash Water.

BPT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony	89.680	40.000
Arsenic	65.310	29.060
Mercury	7.812	3.125
Total suspended solids	1,281.000	609.300
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

§ 421.143 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall

Environmental Protection Agency

§ 421.146

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Sodium Antimonate Autoclave Wastewater.

BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony contained in sodium antimonate product	
Antimony	30.150	13.440
Arsenic	21.720	9.687
Mercury	2.344	0.937

(b) Fouled Anolyte.

BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg pounds per million pounds of antimony metal produced by electrowinning	
Antimony	30.150	13.440
Arsenic	21.720	9.687
Mercury	2.344	0.937

(c) Cathode Antimony Wash Water

BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant of pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony	60.310	26.870
Arsenic	43.430	19.370
Mercury	4.687	1.875

§ 421.144 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Sodium Antimonate Autoclave Wastewater.

NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony contained in sodium antimonate product	
Antimony	30.150	13.440
Arsenic	21.720	9.687
Mercury	2.344	0.937
Total suspended solids	234.400	187.500
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(b) Fouled Anolyte.

NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony	30.150	13.440
Arsenic	21.720	9.687
Mercury	2.344	0.937
Total suspended solids	234.400	187.500
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

(c) Cathode Antimony Wash Water.

NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony	60.310	26.870
Arsenic	43.430	19.370
Mercury	4.687	1.875
Total suspended solids	468.700	375.000
pH	(¹)	(¹)

¹ Within the range of 7.5 to 10.0 at all times.

§ 421.145 [Reserved]

§ 421.146 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment