

Environmental Protection Agency

§ 421.53

methods of analysis set forth in 40 CFR part 401 apply to this subpart.

(b) The term *product* means electrolytically refined copper.

§ 421.52 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart must achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

EFFLUENT LIMITATIONS

Effluent characteristic	Maximum for any 1 day	Average of Daily values for 30 consecutive days shall not exceed
	(Metric units, kg/kg of product; English units, pounds per 1,000 lb of product)	
Total suspended solids	0.100	0.050
Copper	0.0017	0.0008
Cadmium	0.00006	0.00003
Lead	0.0006	0.0026
Zinc	0.0012	0.0003
pH	(¹)	(¹)

¹ Within the range of 6.0 to 9.0.

§ 421.53 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Subpart E—Casting Contact Cooling.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of copper cast	
Arsenic692	.309
Copper638	.304

BAT EFFLUENT LIMITATIONS—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Nickel274	.184

(b) Subpart E—Anode and Cathode Rinse.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of cathode copper production	
Arsenic000	.000
Copper000	.000
Nickel000	.000

(c) Subpart E—Spent Electrolyte.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of copper cathode production	
Arsenic068	.031
Copper063	.030
Nickel027	.018

(d) Subpart E—Casting Wet Air Pollution Control.

BAT EFFLUENT LIMITATIONS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of casting production	
Arsenic000	.000
Copper000	.000
Nickel000	.000

(e) Subpart E—By-Product Recovery.