

the maximum extent feasible the potential for bypass of existing interim constant controls.

(ii) Upon application for a waiver under subpart H, the smelter shall submit to the issuing agency for its approval and to EPA proposed maintenance and operation measures for compliance with the requirements of paragraph (i).

(iii) The remainder of this subpart shall apply except that: (A) The emission limitations required under this subpart shall be based only on existing constant control equipment as upgraded through the improved maintenance and operation required by this paragraph, and (B) bypass of existing controls shall not constitute excess emissions, provided the maintenance and operation requirements and emission limitations prescribed by the NSO are satisfied.

(2) After any denial of a waiver by the issuing Agency, or any disapproval by EPA of a waiver granted by the issuing agency, the NSO shall be amended consistent with the requirements of this subpart and § 57.702.

**§ 57.305 Compliance monitoring and reporting.**

(a) *Monitoring.* (1) Each NSO shall require compliance with the control system performance requirements established pursuant to this subpart to be determined through the use of continuous monitors for measuring SO<sub>2</sub> concentration.

(i) Such monitors must be installed, operated and maintained in accordance with the performance specifications and other requirements contained in appendix D to 40 CFR part 52 or part 60. The monitors must take and record at least one measurement of SO<sub>2</sub> concentration from the effluent of each control system in each 15-minute period. Failure of the monitors to record at least 95% of the 15-minute periods in any 30-day period shall constitute a violation of the NSO.

(ii) The sampling point shall be located at least 8 stack diameters (diameter measured at sampling point) downstream and 2 diameters upstream from any flow disturbance such as a bend, expansion, constriction, or flame,

unless another location is approved by the Administrator.

(iii) The sampling point for monitoring emissions shall be in the duct at the centroid of the cross section if the cross sectional area is less than 4.645m<sup>2</sup> (50 ft<sup>2</sup>) or at a point no closer to the wall than 0.914m (3 ft) if the cross sectional area is 4.645m<sup>2</sup> (50 ft<sup>2</sup>) or more. The monitor sample point shall be in an area of small spatial concentration gradient and shall be representative of the concentration in the duct.

(iv) The measurement system(s) installed and used pursuant to this paragraph shall be subject to the manufacturer's recommended zero adjustment and calibration procedures at least once per 24-hour operating period unless the manufacturer specifies or recommends calibration at shorter intervals, in which case such specifications or recommendations shall be followed. Records of these procedures shall be made which clearly show instrument readings before and after zero adjustment and calibration.

(2) Each NSO shall require the monitoring of any ducts or flues used to bypass gases, required under this subpart to be treated by constant controls, around the smelter's sulfur dioxide constant control system(s) for ultimate discharge to the atmosphere. Such monitoring shall be adequate to disclose the time of the bypass, its duration, and the approximate volume and SO<sub>2</sub> concentration of gas bypassed.

(b) *Reporting.* (1) Each NSO shall require that the smelter maintain a record of all measurements required under paragraph (a) of this section. Results shall be summarized monthly and shall be submitted to the issuing agency within 15 days after the end of each month. The smelter owner shall retain a record of such measurements for one year after the NSO period terminates.

(2) Each NSO shall require that the smelter maintain a record of all measurements and calculations required under § 57.303(b). Results shall be summarized on a monthly basis and shall be submitted to the issuing agency at 6-month intervals. The smelter owner shall retain a record of such measurements and calculations for at least one year after the NSO terminates.

**Environmental Protection Agency**

**§ 57.402**

(3) The report required under § 57.304(b) shall accompany the report required under paragraph (b)(1) of this section.

(c) *Quality assurance and continuous data*—(1) *Quality assurance.* Each NSO shall require that the smelter submit a plan for quality assurance to the issuing agency for approval and that all monitoring performed by continuous monitors shall be verified for quality assurance by the smelter. Such plans must follow current EPA guidelines for quality assurance, in order to be approvable.

(2) *Continuous data.* Manual source testing methods equivalent to 40 CFR part 60, appendix A shall be used to determine compliance if the continuous monitoring system malfunctions.

**Subpart D—Supplementary Control System Requirements**

**§ 57.401 General requirements.**

Except as provided in subpart E, each NSO shall require the smelter owner to prevent all violations of the NAAQS in the smelter's designated liability area (DLA) through the operation of an approved supplementary control system (SCS).

**§ 57.402 Elements of the supplementary control system.**

Each supplementary control system shall contain the following elements:

(a) *Air quality monitoring network.* An approvable SCS shall include the use of appropriate ambient air quality monitors to continuously measure the concentration of sulfur dioxide in the air in the smelter's DLA.

(1) The monitors shall be located at all points of expected SO<sub>2</sub> concentrations necessary to anticipate and prevent possible violations of NAAQS anywhere in the smelter's DLA. The determination of the locations where such concentrations may occur shall take into account all recorded or probable meteorological and operating conditions (including bypassing of control equipment), as well as the presence of other sources of SO<sub>2</sub> significantly affecting SO<sub>2</sub> concentrations in the DLA.

(2) The number and location of sites shall be based on dispersion modeling, measured ambient air quality data,

meteorological information, and the results of the continuing review required by paragraph (f) of this section. The system shall include the use of at least 7 fixed monitors unless the issuing agency determines, on the basis of a demonstration by the smelter owner, that the use of fewer monitors would not limit coverage of points of high SO<sub>2</sub> concentration or otherwise reduce the capability of the smelter owner to prevent any violations of the NAAQS in the smelter's DLA.

(3) All monitors shall be continuously operated and maintained and shall meet the performance specifications contained in 40 CFR part 53. The monitors shall be capable of routine real time measurement of maximum expected SO<sub>2</sub> concentrations for the averaging times of SO<sub>2</sub> NAAQS.

(b) *Meteorological network.* The SCS must have a meteorological assessment capability adequate to predict and identify local conditions requiring emission curtailment to prevent possible violations of the NAAQS. The meteorological assessment capability shall provide all forecast and current information necessary for successful use of the SCS operational manual required by paragraph (e) of this section.

(c) *Designated liability area.* The system shall be required to prevent all violations of the NAAQS within the smelter's DLA. The DLA of any smelter is the area within which the smelter's emissions may cause or significantly contribute to violations of the NAAQS for SO<sub>2</sub> when the smelter is operating at its maximum production capacity under any recorded or probable meteorological conditions. The boundaries of that area shall be specified in the NSO.

(1) Unless an acceptable demonstration is made under paragraph (c)(2) of this section, the DLA shall be a circle with a center point at the smelter's tallest stack and a minimum radius as given in the following table:

**RADIUS FOR SO<sub>2</sub> EMISSIONS AT MAXIMUM PRODUCTION CAPACITY<sup>1</sup>**

Emissions rate in tons per hour	Emission rate in grains per sec.	Radius in kilometers
16 or less .....	4,000 or less .....	11
24 .....	6,000 .....	16