

Environmental Protection Agency

§ 63.494

part of the Precompliance Report as required under § 63.506(e)(3). The Administrator will specify appropriate reporting and recordkeeping requirements as part of the review of the Precompliance Report.

(f) Owners or operators of affected sources complying with § 63.489(d), shall comply with paragraph (f)(1) or (f)(2) of this section, as appropriate.

(1) Submit reports of the times of all periods recorded under § 63.491(e)(3) when the batch front-end process vent is diverted away from the control device through a bypass line, with the next Periodic Report.

(2) Submit reports of all occurrences recorded under § 63.491(e)(4) in which the seal mechanism is broken, the bypass line damper or valve position has changed, or the key to unlock the bypass line damper or valve was checked out, with the next Periodic Report.

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38065, June 19, 2000]

§ 63.493 Back-end process provisions.

Owners and operators of new and existing affected sources shall comply with the requirements in §§ 63.494 through 63.500. Owners and operators of affected sources whose only elastomer products are latex products, liquid rubber products, or products produced in a gas-phased reaction process are not subject to the provisions of §§ 63.494 through 63.500. If latex or liquid rubber products are produced in an affected source that also produces another elastomer product, the provisions of §§ 63.484 through 63.500 do not apply to the back-end operations dedicated to the production of one or more latex products or to the back-end operations during the production of a latex product. Section 63.494 contains residual organic HAP limitations. Compliance with these residual organic HAP limitations may be achieved by using either stripping technology, or by using control or recovery devices. If compliance with these limitations is achieved using stripping technology, the procedures to determine compliance are specified in § 63.495. If compliance with these limitations is achieved using control or recovery devices, the procedures to determine compliance are specified in § 63.496, and associated

monitoring requirements are specified in § 63.497. Recordkeeping requirements are contained in § 63.498, and reporting requirements in § 63.499. Section 63.500 contains a limitation on carbon disulfide emissions from affected sources that produce styrene butadiene rubber using an emulsion process. Table 8 to this subpart contains a summary of compliance alternative requirements for these sections.

[65 FR 38065, June 19, 2000]

§ 63.494 Back-end process provisions—residual organic HAP limitations.

(a) The monthly weighted average residual organic HAP content of all grades of elastomer processed, measured after the stripping operation [or the reactor(s), if the plant has no stripper(s)] as specified in § 63.495(d), shall not exceed the limits provided in paragraphs (a)(1) through (a)(4) of this section, as applicable. Owners or operators of affected sources shall comply with the requirements of this paragraph using either stripping technology or control or recovery devices.

(1) For styrene butadiene rubber produced by the emulsion process:

(i) A monthly weighted average of 0.40 kg styrene per megagram (Mg) latex for existing affected sources; and

(ii) A monthly weighted average of 0.23 kg styrene per Mg latex for new sources;

(2) For polybutadiene rubber and styrene butadiene rubber produced by the solution process:

(i) A monthly weighted average of 10 kg total organic HAP per Mg crumb rubber (dry weight) for existing affected sources; and

(ii) A monthly weighted average of 6 kg total organic HAP per Mg crumb rubber (dry weight) for new sources.

(3) For ethylene-propylene rubber produced by the solution process:

(i) A monthly weighted average of 8 kg total organic HAP per Mg crumb rubber (dry weight) for existing affected sources; and

(ii) A monthly weighted average of 5 kg total organic HAP per Mg crumb rubber (dry weight) for new sources.

(4) There are no back-end process operation residual organic HAP limitations for neoprene, Hypalon™, nitrile-butadiene rubber, butyl rubber,

halobutyl rubber, epichlorohydrin elastomer, and polysulfide rubber. There are also no back-end process operation residual organic HAP limitations for latex products, liquid rubber products, products produced in a gas-phased reaction process, styrene butadiene rubber produced by any process other than a solution or emulsion process, polybutadiene rubber produced by any process other than a solution process, or ethylene-propylene rubber produced by any process other than a solution process.

(5) For EPPU that produce both an elastomer product with a residual organic HAP limitation listed in this section, and a product listed in paragraphs (a)(5) (i) through (iv) of this section, only the residual HAP content of the elastomer product with a residual organic HAP limitation shall be used in determining the monthly average residual organic HAP content.

- (i) Resins;
- (ii) Liquid rubber products;
- (iii) Latexes from which crumb rubber is not coagulated; or
- (iii) Elastomer products listed in paragraph (a)(4) of this section.

(b) If an owner or operator complies with the residual organic HAP limitations in paragraph (a) of this section using stripping technology, compliance shall be demonstrated in accordance with § 63.495. The owner or operator shall also comply with the recordkeeping provisions in § 63.498, and the reporting provisions in § 63.499.

(c) If an owner or operator complies with the residual organic HAP limitations in paragraph (a) of this section using control or recovery devices, compliance shall be demonstrated using the procedures in § 63.496. The owner or operator shall also comply with the monitoring provisions in § 63.497, the recordkeeping provisions in § 63.498, and the reporting provisions in § 63.499.

(d) If the owner or operator complies with the residual organic HAP limitations in paragraph (a) of this section using a flare, the owner or operator of an affected source shall comply with the requirements in § 63.504(c).

[62 FR 46925, Sept. 5, 1996, as amended at 65 FR 38065, June 19, 2000]

§ 63.495 Back-end process provisions—procedures to determine compliance using stripping technology.

(a) If an owner or operator complies with the residual organic HAP limitations in § 63.494(a) using stripping technology, compliance shall be demonstrated using the periodic sampling procedures in paragraph (b) of this section, or using the stripper parameter monitoring procedures in paragraph (c) of this section. The owner or operator shall determine the monthly weighted average residual organic HAP content for each month in which any portion of the back-end of an elastomer production process is in operation. A single monthly weighted average shall be determined for all back-end process operations at the affected source.

(b) If the owner or operator is demonstrating compliance using periodic sampling, this demonstration shall be in accordance with paragraphs (b)(1) through (b)(5) of this section.

(1) The location of the sampling shall be in accordance with paragraph (d) of this section.

(2) The frequency of the sampling shall be in accordance with paragraphs (b)(2)(i) or (b)(2)(ii) of this section.

(i) If a stripper operated in batch mode is used, at least one representative sample is to be taken from every batch of elastomer produced, at the location specified in paragraph (d) of this section, and identified by elastomer type and by the date and time the batch is completed.

(ii) If a stripper operated in continuous mode is used, at least one representative sample is to be taken each operating day. The sample is to be taken at the location specified in paragraph (d) of this section, and identified by elastomer type and by the date and time the sample was taken.

(3) The residual organic HAP content in each sample is to be determined using the Methods specified in paragraph (e) of this section.

(4) The quantity of material (weight of latex or dry crumb rubber) represented by each sample shall be recorded. Acceptable methods of determining this quantity are production records, measurement of stream characteristics, and engineering calculations.