

(2) *Continuous Monitoring of Total Hydrocarbon Emissions.* (i) The owner or operator of a secondary lead smelter shall install, operate, and maintain a total hydrocarbon continuous monitoring system and comply with all of the requirements for continuous monitoring systems found in subpart A, General Provisions.

(ii) Prior to or in conjunction with the initial compliance test to determine compliance with § 63.543 (c), (d), or (e), the owner or operator shall conduct a performance evaluation for the total hydrocarbon continuous monitoring system according to § 63.8(e) of the General Provisions. The monitor shall meet the performance specifications of Performance Specification 8, 40 CFR Part 60, Appendix B.

(iii) Allowing the 3-hour average total hydrocarbon concentration to exceed the applicable total hydrocarbon emission limit under § 63.543 shall constitute a violation of the applicable emission standard for total hydrocarbons under § 63.543 (c), (d), or (e).

(k) The owner or operator of a secondary lead smelter who uses pressurized dryer breaching seals in order to comply with the requirements of § 63.544(g) shall equip each seal with an alarm that will “sound” or “go off” if the pressurized dryer breaching seal malfunctions.

[62 FR 32216, June 13, 1997, as amended at 63 FR 45011, Aug. 24, 1998]

§ 63.549 Notification requirements.

(a) The owner or operator of a secondary lead smelter shall comply with all of the notification requirements of § 63.9 of subpart A, General Provisions.

(b) The owner or operator of a secondary lead smelter shall submit the fugitive dust control standard operating procedures manual required under § 63.545(a) and the standard operating procedures manual for baghouses required under § 63.548(a) to the Administrator or delegated authority along with a notification that the smelter is seeking review and approval of these plans and procedures. Owners or operators of existing secondary lead smelters shall submit this notification no later than July 23, 1997. The owner or operator of a secondary lead smelter that commences construction or recon-

struction after June 9, 1994, shall submit this notification no later than 180 days before startup of the constructed or reconstructed secondary lead smelter, but no sooner than June 13, 1997. An affected source that has received a construction permit from the Administrator or delegated authority on or before June 23, 1995, shall submit this notification no later than July 23, 1997.

§ 63.550 Recordkeeping and reporting requirements.

(a) The owner or operator of a secondary lead smelter shall comply with all of the recordkeeping requirements under § 63.10 of the General Provisions. In addition, each owner or operator of a secondary lead smelter shall maintain for a period of 5 years, records of the information listed in paragraphs (a)(1) through (a)(6) of this section.

(1) An identification of the date and time of all bag leak detection system alarms, their cause, and an explanation of the corrective actions taken.

(2) If an owner or operator chooses to demonstrate continuous compliance with the total hydrocarbon emission standards under § 63.543 (c), (d), or (e) by employing the method allowed in § 63.548(j)(1), the records shall include the output from the continuous temperature monitor, an identification of periods when the 3-hour average temperature fell below the minimum established under § 63.548(j)(1), and an explanation of the corrective actions taken.

(3) If an owner or operator chooses to demonstrate continuous compliance with the total hydrocarbon emission standard under § 63.543 (c), (d), or (e) by employing the method allowed in § 63.548(j)(2), the records shall include the output from the total hydrocarbon continuous monitoring system, an identification of the periods when the 3-hour average total hydrocarbon concentration exceeded the applicable standard and an explanation of the corrective actions taken.

(4) Any recordkeeping required as part of the practices described in the standard operating procedures manual required under § 63.545(a) for the control of fugitive dust emissions.

(5) Any recordkeeping required as part of the practices described in the

standard operating procedures manual for baghouses required under § 63.548(a).

(6) Records of the pressure drop and water flow rate for wet scrubbers used to control metal hazardous air pollutant emissions from process fugitive sources.

(b) The owner or operator of a secondary lead smelter shall comply with all of the reporting requirements under § 63.10 of the General Provisions. The submittal of reports shall be no less frequent than specified under § 63.10(e)(3) of the General Provisions. Once a source reports a violation of the standard or excess emissions, the source shall follow the reporting format required under § 63.10(e)(3) until a request to reduce reporting frequency is approved.

(c) In addition to the information required under § 63.10 of the General Provisions, reports required under paragraph (b) of this section shall include the information specified in paragraphs (c)(1) through (c)(6) of this section.

(1) The reports shall include records of all alarms from the bag leak detection system specified in § 63.548(e).

(2) The reports shall include a description of the procedures taken following each bag leak detection system alarm pursuant to § 63.548(f) (1) and (2).

(3) The reports shall include the information specified in either paragraph (c)(3)(i) or (c)(3)(ii) of this section, consistent with the monitoring option selected under § 63.548(h).

(i) A record of the temperature monitor output, in 3-hour block averages, for those periods when the temperature monitored pursuant to § 63.548(j)(1) fell below the level established in § 63.548(j)(1).

(ii) A record of the total hydrocarbon concentration, in 3-hour block averages, for those periods when the total hydrocarbon concentration being monitored pursuant to § 63.548(j)(2) exceeds the relevant limits established in § 63.543 (c), (d), and (e).

(4) The reports shall contain a summary of the records maintained as part of the practices described in the standard operating procedures manual for baghouses required under § 63.548(a), including an explanation of the periods when the procedures were not followed and the corrective actions taken.

(5) The reports shall contain an identification of the periods when the pressure drop and water flow rate of wet scrubbers used to control process fugitive sources dropped below the levels established in § 63.548(i), and an explanation of the corrective actions taken.

(6) The reports shall contain a summary of the fugitive dust control measures performed during the required reporting period, including an explanation of the periods when the procedures outlined in the standard operating procedures manual pursuant to § 63.545(a) were not followed and the corrective actions taken. The reports shall not contain copies of the daily records required to demonstrate compliance with the requirements of the standard operating procedures manuals required under §§ 63.545(a) and 63.548(a).

§ 63.551 Implementation and enforcement.

(a) This subpart can be implemented and enforced by the U.S. EPA, or a delegated authority such as the applicable State, local, or Tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or Tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if this subpart is delegated to a State, local, or Tribal agency.

(b) In delegating implementation and enforcement authority of this subpart to a State, local, or Tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or Tribal agency.

(c) The authorities that cannot be delegated to State, local, or Tribal agencies are as specified in paragraphs (c)(1) through (4) of this section.

(1) Approval of alternatives to the requirements in §§ 63.541, 63.543 through 63.544, 63.545(a) and (c) through (e), and 63.546.

(2) Approval of major alternatives to test methods for under § 63.7(e)(2)(ii) and (f), as defined in § 63.90, and as required in this subpart.