

Remote group alarm means an audible and visual alarm that alerts when an alarm condition exists but does not identify that condition.

Secondary barrier means the liquid resisting outer boundary of a cargo containment system when the cargo containment system includes two boundaries.

Semi-membrane tank is a cargo tank that is not self-supporting and that can expand and contract due to thermal, hydrostatic, and pressure loadings. It consists of flat surfaces, supported through insulation by the adjacent hull structure, and shaped corners that connect the flat surfaces.

Service space means a space outside the cargo area that is used for a galley, pantry containing cooking appliances, locker or store room, workshop except those in machinery spaces, and similar spaces and trunks to those spaces.

Shut-off valve is a valve that closes a pipeline and provides nominal metal to metal contact between the valve operating parts, including the disc and gate, and the valve body.

Specific gravity (ρ) means the ratio of the density of the cargo at the design temperature to the density of water at 4 °C (39 °F).

Tank cover is the structure protecting those parts of the cargo containment system that protrude through the weather deck and providing continuity to the deck structure.

Tank dome means the uppermost portion of the cargo tank. For below deck cargo containment systems, it means the uppermost portion of the cargo tank that protrudes through the weather deck or through the tank cover.

Toxic cargoes includes the following liquefied gases from Table 4 (follows §154.1872):

Acetaldehyde
Ammonia, anhydrous
Dimethylamine
Ethylamine
Ethyl chloride
Ethylene oxide
Methyl bromide
Methyl chloride
Sulfur dioxide
Vinyl chloride

Vapor pressure means the absolute equilibrium pressure of the saturated

vapor above the liquid, expressed in kPa (psia), at a specific temperature.

Void space means an enclosed space in the cargo area outside of the cargo containment system, except a hold space, ballast space, fuel oil tank, cargo pump or compressor room, or any space used by personnel.

1974 Safety Convention stands for the International Convention on Safety of Life at Sea, 1974, done at London, November 1, 1974.

§ 154.9 Issuance of documents.

The Coast Guard issues an endorsed Certificate of Inspection to a U.S. flag vessel or an endorsed Certificate of Compliance to a foreign flag vessel that meets this part.

§ 154.12 Existing gas vessel: Endorsements and requirements.

(a) Except an existing gas vessel under paragraph (b), (c), or (d) of this section, an existing gas vessel must meet subpart C of this part if the owner desires a document endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872).

(b) If an existing gas vessel is issued a document by the Coast Guard before November 1, 1987 that is endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872), and the owner desires the same endorsement on a re-issued document, the vessel must—

(1) Continue to meet the same design and construction standards under which the Coast Guard issued the original document; and

(2) Meet paragraph (e) of this section.

(c) If an existing gas vessel is issued a document by the Coast Guard before November 1, 1987 that is endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872), and the owner desires an endorsement for a different cargo listed in that table, the vessel must—

(1) Continue to meet the same design and construction standards under which the Coast Guard issued the original document;

(2) Meet paragraph (e) of this section;

(3) Meet subpart D for the different cargo; and

(4) Meet any additional requirements of this part that the Commandant (G-

§ 154.15

46 CFR Ch. I (10–1–08 Edition)

MSO) determines to be necessary for safety.

(d) If an existing gas vessel does not meet paragraph (b) or (c) of this section and the owner desires a document endorsed for the carriage of a cargo listed in Table 4 (follows §154.1872), the vessel must—

(1) Have a letter from the Coast Guard dated before November 1, 1987 stating that—

(i) Review of the vessel’s plans for the carriage of that cargo is completed; or

(ii) The vessel’s IMO Certificate endorsed for the carriage of that cargo is accepted;

(2) Meet the plans that were reviewed and marked “Examined” or “Approved” by the Coast Guard, or meet the standards under which the IMO Certificate was issued;

(3) Meet paragraph (e) of this section; and

(4) Meet any additional requirements of this part that the Commandant (G-MSO) determines to be necessary for safety.

(e) If the owner of a vessel desires any document endorsement described in paragraph (b), (c), or (d) of this section, the existing gas vessel must meet the requirements in each of the following:

- (1) Section 154.310 (d) and (e).
- (2) Section 154.320 (b) and (c).
- (3) Section 154.330 (a) through (e).
- (4) Section 154.340(d).
- (5) Section 154.345 (a), (b)(1) through (b)(5), (b)(7) and (c).
- (6) Section 154.476(a).
- (7) Section 154.519(a)(2).
- (8) Section 154.534.
- (9) Section 154.538.
- (10) Section 154.540 (c) and (d).
- (11) Section 154.556.
- (12) Section 154.558.
- (13) Section 154.560.
- (14) Section 154.562.
- (15) Section 154.703.
- (16) Section 154.705.
- (17) Section 154.706.
- (18) Section 154.707.
- (19) Section 154.708.
- (20) Section 154.709.
- (21) Section 154.904.
- (22) Section 154.906.
- (23) Section 154.908(a), unless the space is separated from the accommo-

modation, service, or control space by a steel door that—

(i) Is watertight when tested with a firehose at not less than 207 kPa gauge (30 psig);

(ii) Has a means to self-close and does not have latches or other devices designed to hold it open; and

(iii) Has an audible and visual alarm on both sides of the door which is actuated when the door is open.

(24) Section 154.910.

(25) Section 154.912.

(26) Sections 154.1110 through 154.1130, except §§154.1115(b), 154.1120(b), and 154.1125 (c) and (f).

(27) Section 154.1145, except an existing gas vessel with a cargo carrying capacity of less than 2500 m³ (88,200 ft³) may have only one self-contained dry chemical storage unit if that unit—

(i) is installed before November 1, 1987; and

(ii) Has the capacity to meet §154.1145 (d) and (e), and §154.1170(e).

(28) Section 154.1150 (a) and (b).

(29) Section 154.1155.

(30) Section 154.1160.

(31) Section 154.1165 (a), (b), (d), and (f).

(32) Section 154.1170 (b) through (f).

(33) Section 154.1200 (a), (b)(1), and (b)(2).

(34) Section 154.1205(f).

(35) Section 154.1325.

(36) Section 154.1335(e).

(37) Section 154.1350 (e), (f), (i), (o), and (u).

§ 154.15 U.S. flag vessel: Endorsement application.

(a) A person who desires the endorsement required under § 154.1801 for a U.S. flag vessel must submit an application for an endorsement of the vessel’s Subchapter D Certificate of Inspection under the procedures in §91.55–15 of this chapter.

(b) The person requesting an endorsement under paragraph (a) of this section must submit to the Coast Guard, if requested—

(1) Calculations for hull design required by §172.175 of this chapter;

(2) The plans and information listed in §§54.01–18, 56.01–10, 91.55–5 (a), (b), (d), (g), and (h), and 110.25–1 of this chapter;