

§ 154.1730

- (1) Be specially approved by the Commandant (G-MSO); and
- (2) Be marked "For (Alkylene or Ethylene) Oxide Transfer Only."
- (c) Ethylene oxide must be maintained at less than 30 °C (86 °F).
- (d) Cargo tank relief valves for tanks containing ethylene oxide must be set at 539 kPa gauge (78.2 psig) or higher.
- (e) The vapor space of a cargo tank carrying ethylene oxide must be maintained at a nitrogen concentration of 45% by volume.
- (f) A vessel must have a method for jettisoning ethylene oxide that meets §§ 154.356 and 154.1872.

[CGD 74-289, 44 FR 26009, May 3, 1979, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

§ 154.1730 Ethylene oxide: Loading and off loading.

- (a) The master shall ensure that before ethylene oxide is loaded into a cargo tank:
 - (1) The tank is thoroughly clean, dry, and free of rust;
 - (2) The hold spaces are inerted with an inert gas that meets § 154.1710(b)(1); and
 - (3) The cargo tank vapor space is inerted with nitrogen.
- (b) Ethylene oxide must be off loaded by a deepwell pump or inert gas displacement.
- (c) Ethylene oxide must not be carried in deck tanks.

§ 154.1735 Methyl acetylene-propadiene mixture.

- (a) The composition of the methyl acetylene-propadiene mixture at loading must be within the following limits or specially approved by the Commandant (G-MSO):
 - (1) One composition is:
 - (i) Maximum methyl acetylene and propadiene molar ratio of 3 to 1;
 - (ii) Maximum combined concentration of methyl acetylene and propadiene of 65 mole percent;
 - (iii) Minimum combined concentration of propane, butane, and isobutane of 24 mole percent, of which at least one-third (on a molar basis) must be butanes and one-third propane; and
 - (iv) Maximum combined concentration of propylene and butadiene of 10 mole percent.

46 CFR Ch. I (10-1-08 Edition)

- (2) A second composition is:
 - (i) Maximum methyl acetylene and propadiene combined concentration of 30 mole percent;
 - (ii) Maximum methyl acetylene concentration of 20 mole percent;
 - (iii) Maximum propadiene concentration of 20 mole percent;
 - (iv) Maximum propylene concentration of 45 mole percent;
 - (v) Maximum butadiene and butylenes combined concentration of 2 mole percent;
 - (vi) A minimum saturated C₄ hydrocarbon concentration of 4 mole percent; and
 - (vii) A minimum propane concentration of 25 mole percent.
- (b) A vessel carrying a methyl acetylene-propadiene mixture must have a refrigeration system without vapor compression or have a refrigeration system with the following features:
 - (1) A vapor compressor that does not raise the temperature and pressure of the vapor above 60 °C (140 °F) and 1.72 MPa gauge (250 psig) during its operation and that does not allow vapor to stagnate in the compressor while it continues to run.
 - (2) Discharge piping from each compressor stage or each cylinder in the same stage of a reciprocating compressor that has:
 - (i) Two temperature actuated shutdown switches set to operate at 60 °C (140 °F) or less;
 - (ii) A pressure actuated shutdown switch set to operate at 1.72 MPa gauge (250 psig) or less; and
 - (iii) A safety relief valve set to relieve at 1.77 MPa gauge (256 psig) or less.
 - (3) A relief valve that vents to a mast meeting § 154.805 and that does not relieve into the compressor suction line.
 - (4) An alarm that sounds in the cargo control station and in the wheelhouse when any of the high pressure or high temperature switches under paragraphs (b)(2)(i) and (b)(2)(ii) of this section operate.
- (c) A vessel carrying a methyl acetylene-propadiene mixture must have separate cargo piping, vent piping, and refrigeration equipment for methyl acetylene-propadiene that are segregated from other cargo piping,

vent piping and refrigeration equipment on the vessel.

[CGD 74-289, 44 FR 26009, May 3, 1979; 44 FR 59234, Oct. 15, 1979; CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

§ 154.1740 Vinyl chloride: Inhibiting and inerting.

When a vessel is carrying vinyl chloride, the master shall ensure that:

- (a) Section 154.1818 is met; or
- (b) Section 154.1710 is met, and the oxygen content of inert gas is less than 0.1% by volume.

§ 154.1745 Vinyl chloride: Transferring operations.

A vessel carrying vinyl chloride must meet the requirements of § 151.50-34(g) through (k) of this chapter.

[CGD 95-012, 60 FR 48051, Sept. 18, 1995]

§ 154.1750 Butadiene or vinyl chloride: Refrigeration system.

A refrigeration system for butadiene or vinyl chloride must not use vapor compression unless it:

- (a) Avoids any stagnation points where uninhibited liquid can accumulate; or
- (b) Has inhibited liquid from the cargo tank added to the vapor upstream of the condenser.

§ 154.1755 Nitrogen.

Except for deck tanks and their piping systems, cargo containment systems and piping systems carrying nitrogen must be specially approved by the Commandant (G-MSO).

[CGD 74-289, 44 FR 26009, May 3, 1979, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

§ 154.1760 Liquid ammonia.

The master shall ensure that no person sprays liquid ammonia into a cargo tank containing more than 8% oxygen by volume.

Subpart E—Operations

§ 154.1800 Special operating requirements under Part 35 of this chapter.

Each vessel must meet the requirements of Part 35 of this chapter except § 35.30-20.

§ 154.1801 Certificates, letters, and endorsements: U.S. flag vessels.

No person may operate a U.S. flag vessel unless the vessel has a Certificate of Inspection, issued under Subchapter D of this chapter, which is endorsed with the name of the cargo that it is allowed to carry.

§ 154.1802 Certificates, letters and endorsements: Foreign flag vessels.

(a) No person may operate on the navigable waters of the United States a foreign flag vessel, whose flag administration issues IMO Certificates, unless the vessel has:

(1) An IMO Certificate issued by the flag administration that is endorsed with the name of the cargo that it is allowed to carry, and, except when entering United States waters to be examined as required by § 154.150, a Certificate of Compliance¹ issued by the Coast Guard endorsed under this part with the name of the cargo that it is allowed to carry; or

(2) Special approval under § 154.30.

(b) No person may operate on the navigable waters of the United States a foreign flag vessel, whose flag administration does not issue IMO Certificates, unless the vessel has:

(1) Except when entering United States waters to be examined as required by § 154.150, a Certificate of Compliance¹ issued by the Coast Guard endorsed under this part with the name of the cargo it is allowed to carry; or

(2) Special approval under § 154.30.

(c) No person may operate on the navigable waters of the United States a foreign flag vessel unless the vessel has onboard the following plans and information which except for the certificates under paragraph (c)(1) of this section, are in English:

(1) The vessel's Cargo Ship Safety Construction Certificate and Cargo Ship Safety Equipment Certificate issued under the International Convention for Safety of Life at Sea, 1974.

(2) A description and schematic plan of the arrangement for inerting cargo

¹Until the Certificate of Compliance form is developed, the Letter of Compliance with a Subchapter O endorsement for the carriage of liquefied gases will serve the purpose of the endorsed Certificate of Compliance.