

**§ 154.1820**

**46 CFR Ch. I (10-1-08 Edition)**

certification from the shipper that the product is inhibited.

(b) The certification required by this section must contain the following information:

(1) The name and concentration of the inhibitor.

(2) The date the inhibitor was added.

(3) The expected duration of the inhibitor's effectiveness.

(4) Any temperature limitations qualifying the inhibitor's effective lifetime.

(5) The action to be taken if the time of the voyage exceeds the inhibitor's lifetime.

**§ 154.1820 Shipping document.**

No person may operate a vessel without carrying a shipping document in the wheelhouse that lists for each cargo on board:

(a) The cargo tank in which the cargo is stowed;

(b) The name of the shipper;

(c) The location of the loading terminal;

(d) The cargo name as listed in Table 4; and

(e) The approximate quantity of the cargo.

**§ 154.1822 Shipping document: Copy for transfer terminal.**

While a vessel is moored at a transfer terminal, the master shall ensure that at least one copy of the shipping document is given to the terminal's person in charge of cargo transfer.

**§ 154.1824 Obstruction of pumproom ladderways.**

The master shall ensure that each cargo pumproom access is unobstructed.

**§ 154.1826 Opening of cargo tanks and cargo sampling.**

(a) The master shall ensure that each cargo tank opening is fully closed at all times.

(b) The master may authorize the opening of a cargo tank:

(1) During tank cleaning; and

(2) To sample a cargo that Table 4 allows to be carried in a containment system having a restricted gauging system if:

(i) The cargo tank is not being filled during sampling;

(ii) The vent system has relieved any pressure in the tank; and

(iii) The person sampling the cargo wears protective clothing.

(c) The master shall ensure that cargoes requiring closed gauging as listed in Table 4 are sampled only through the controlled sampling arrangement of the cargo tank.

**§ 154.1828 Spaces containing cargo vapor: Entry.**

(a) No person may enter a cargo handling space without the permission of the master or without following a safety procedure established by the master.

(b) Before allowing anyone to enter a cargo handling space, the master shall ensure that:

(1) The space is free of toxic vapors and has an oxygen concentration of at least 19.5 percent oxygen by volume; or

(2) Those entering the space wear protective equipment with breathing apparatus and an officer closely supervises the entire operation in the space.

**§ 154.1830 Warning sign.**

(a) The master shall ensure that a vessel transferring cargo, while fast to a dock or while at anchor in port, displays a warning sign:

(1) At the gangway facing the shore so that the sign may be seen from the shore; and

(2) Facing outboard towards the water so that the sign may be seen from the water.

(b) Except as provided in paragraph (e) of this section, each warning sign must have the following words:

(1) Warning.

(2) Dangerous Cargo.

(3) No Visitors.

(4) No Smoking.

(5) No Open Lights.

(c) Each letter in the words on the sign must:

(1) Be block style;

(2) Be black on a white background;

(3) Be 7.6 cm (3 in.) high;

(4) Be 5.1 cm (2 in.) wide, except for "M" and "W" which must be 7.6 cm (3 in.) wide, and the letter "I" which may be 1.3 cm (½ in.) wide; and

(5) Have 1.3 cm (½ in.) stroke width.