

(c) Interbarrier spaces must have an eductor or pump for removing liquid cargo and returning it to the cargo tanks or to an emergency jettisoning system meeting §154.356.

(d) Spaces in the cargo containment portion of the vessel, except ballast spaces and gas-safe spaces, must not connect to pumps in the main machinery space.

[CGD 74-289, 44 FR 26009, May 3, 1979, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

§ 154.355 Bow and stern loading piping.

(a) Bow and stern loading piping must:

- (1) Meet §154.310;
 - (2) Be installed in an area away from the accommodation, service, or control space on type IG hulls;
 - (3) Be clearly marked;
 - (4) Be segregated from the cargo piping by a removable spool piece in the cargo area or by at least two shut-off valves in the cargo area that have means of locking to meet §154.1870(a);
 - (5) Have a means for checking for cargo vapor between the two valves under paragraph (a)(4) of this section;
 - (6) Have fixed inert gas purging lines; and
 - (7) Have fixed vent lines for purging with inert gas to meet §154.1870(b).
- (b) Entrances, forced or natural ventilation intakes, exhausts, and other openings to accommodation, service, or control spaces that face the bow or stern loading area must meet §154.330.

§ 154.356 Cargo emergency jettisoning piping.

Emergency jettisoning piping must:

- (a) Meet §154.355(a);
- (b) Be designed to allow cargo discharge without the outer hull steel temperature falling below the minimum temperatures under §§154.170 and 154.172; and
- (c) Be specially approved by the Commandant (G-MSO).

[CGD 74-289, 44 FR 26009, May 3, 1979, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

CARGO CONTAINMENT SYSTEMS

§ 154.401 Definitions.

As used in §§154.440 and 154.447:

“ σ_Y ” means the minimum yield strength of the tank material, including weld metal, at room temperature.

“ σ_B ” means minimum tensile strength of the tank material, including weld metals, at room temperature.

§ 154.405 Design vapor pressure (P_o) of a cargo tank.

(a) The design vapor pressure (P_o) of a cargo tank must be equal to or greater than the MARVS.

(b) The P_o of a cargo tank must be equal to or greater than the vapor pressure of the cargo at 45 °C (113 °F) if:

- (1) The cargo tank has no temperature control for the cargo; and
- (2) The vapor pressure of the cargo results solely from ambient temperature.

(c) The P_o of a cargo tank may be exceeded under harbor conditions if specially approved by the Commandant (G-MSO).

[CGD 74-289, 44 FR 26009, May 3, 1979, as amended by CGD 82-063b, 48 FR 4782, Feb. 3, 1983]

§ 154.406 Design loads for cargo tanks and fixtures: General.

(a) Calculations must show that a cargo tank and its fixtures are designed for the following loads:

- (1) Internal pressure head.
- (2) External pressure load.
- (3) Dynamic loads resulting from the motion of the vessel.
- (4) Transient or stationary thermal loads if the design temperature is colder than -55 °C (-67 °F) or causes thermal stresses in cargo tank supports.
- (5) Sloshing loads, if the cargo tank is designed for partial loads.
- (6) Loads resulting from vessel's deflection.
- (7) Tank weight, cargo weight, and corresponding support reaction.
- (8) Insulation weight.
- (9) Loads of a pipe tower and any other attachments to the cargo tank.
- (10) Vapor pressure loads in harbor conditions allowed under §154.405.
- (11) Gas pressurization if the cargo tank is designed for gas pressurization as a means of cargo transfer.