

§ 25.212 Narrowband analog transmissions, digital transmissions, and video transmissions in the GSO Fixed-Satellite Service.

(a) Except as otherwise provided by this part, criteria for unacceptable levels of interference caused by other satellite networks shall be established on the basis of nominal operating conditions and with the objective of minimizing orbital separations between satellites.

(b) Emissions with an occupied bandwidth of less than 2 MHz are not protected from interference from wider bandwidth transmissions if the r.f. carrier frequency of the narrowband signal is within ± 1 MHz of one of the frequencies specified in § 25.211(a).

(c) In the 14.0–14.5 GHz band, an earth station with an antenna equivalent diameter of 1.2 meters or greater may be routinely licensed for transmission of narrowband analog services with bandwidths up to 200 kHz if the maximum input power spectral density into the antenna does not exceed -8 dBW/4 kHz and the maximum transmitted satellite carrier EIRP density does not exceed 13 dBW/4 kHz. Such earth stations may be routinely licensed for transmission of narrowband and/or wideband digital services, including digital video services, if the maximum input spectral power density into the antenna does not exceed -14 dBW/4 kHz and the maximum transmitted satellite carrier EIRP density does not exceed $+6.0$ dBW/4 kHz. Antennas with a smaller major or minor axis in the 14 GHz band are subject to the provisions of § 25.220, which may include power reduction requirements.

(d)(1) For earth stations licensed before March 10, 2005 in the 5925–6425 MHz band, an earth station with an equivalent diameter of 4.5 meters or greater may be routinely licensed for transmission of SCPC services if the maximum power densities into the antenna do not exceed $+0.5$ dBW/4 kHz for analog SCPC carriers with bandwidths up to 200 kHz, and do not exceed -2.7 dBW/4 kHz for narrow and/or wideband digital SCPC carriers.

(2) For earth stations licensed after March 10, 2005 in the 5925–6425 MHz band, an earth station with an equivalent diameter of 4.5 meters or greater

may be routinely licensed for transmission of SCPC services if the maximum power densities into the antenna do not exceed $+0.5$ dBW/4 kHz for analog SCPC carriers with bandwidths up to 200 kHz, and do not exceed $-2.7 - 10\log(N)$ dBW/4 kHz for narrow and/or wideband digital SCPC carriers. For digital SCPC using frequency division multiple access (FDMA) or time division multiple access (TDMA) technique, N is equal to one. For digital SCPC using code division multiple access (CDMA) technique, N is the maximum number of co-frequency simultaneously transmitting earth stations in the same satellite receiving beam.

(3) Antennas with an equivalent diameter smaller than 4.5 meters in the 5925–6425 MHz band are subject to the provisions of § 25.220 of this chapter, which may include power reduction requirements.

(e) Each applicant for authorization for transmissions in the fixed-satellite service proposing to use transmitted satellite carrier EIRP densities, and/or maximum antenna input power densities in excess of those specified in paragraph (c) of this section in the 14.0–14.5 GHz band, or in paragraph (d) of this section in the 5925–6425 MHz band, respectively, must comply with the procedures set forth in § 25.220.

(f) In the 24.75–25.25 GHz band, an earth station that meets the antenna gain pattern requirements set forth in §§ 25.209(a) and (b) of this part may be routinely licensed if the maximum power density into the antenna does not exceed 3.5 dBW/MHz.

[58 FR 13421, Mar. 11, 1993, as amended at 62 FR 5931, Feb. 10, 1997; 62 FR 51378, Oct. 1, 1997; 70 FR 32256, June 2, 2005; 70 FR 33376, June 8, 2005; 72 FR 50030, Aug. 29, 2007]

§ 25.213 Inter-Service coordination requirements for the 1.6/2.4 GHz mobile-satellite service.

(a) Protection of the radio astronomy service in the 1610.6–1613.8 MHz band against interference from 1.6/2.4 GHz Mobile-Satellite Service systems.

(1) *Protection zones.* All 1.6/2.4 GHz Mobile Satellite Service systems shall be capable of determining the position of the user transceivers accessing the space segment through either internal

radiodetermination calculations or external sources such as LORAN-C or the Global Positioning System. During periods of radio astronomy observations, land mobile earth stations shall not operate when located within geographic protection zones defined by the radio observatory coordinates and separation distances as follows:

(i) In the band 1610.6–1613.8 MHz, within a 160 km radius of the following radio astronomy sites:

Observatory	Latitude (DMS)	Longitude (DMS)
Arecibo, PR	18 20 46	66 45 11
Green Bank Telescope, WV	38 25 59	79 50 24
	38 26 09	79 49 42
Very Large Array, NM	34 04 43	107 37 04
Owens Valley, CA	37 13 54	118 17 36
Ohio State, OH	40 15 06	83 02 54

(ii) In the band 1610.6–1613.8 MHz, within a 50 km radius of the following sites:

Observatory	Latitude (DMS)	Longitude (DMS)
Pile Town, NM	34 18 04	108 07 07
Los Alamos, NM	35 46 30	106 14 42
Kitt Peak, AZ	31 57 22	111 36 42
Ft. Davis, TX	30 38 06	103 56 39
N. Liberty, IA	41 46 17	91 34 26
Brewster, WA	48 07 53	119 40 55
Owens Valley, CA	37 13 54	118 16 34
St. Croix, VI	17 45 31	64 35 03
Mauna Kea, HI	19 48 16	155 27 29
Hancock, NH	42 56 01	71 59 12

(iii) Out-of-band emissions of a mobile earth station licensed to operate within the 1610.0–1626.5 MHz band shall be attenuated so that the power flux density it produces in the 1610.6–1613.8 MHz band at any radio astronomy site listed in paragraph (a)(1) (i) or (ii) of this section shall not exceed the emissions of a mobile earth station operating within the 1610.6–1613.8 MHz band at the edge of the protection zone applicable for that site. As an alternative, a mobile earth station shall not operate during radio astronomy observations within the 1613.8–1615.8 MHz band within 100 km of the radio astronomy sites listed in paragraph (a)(1)(i) of this section, and within 30 km of the sites listed in paragraph (a)(1)(ii) of this section, there being no restriction on a mobile earth station operating within the 1615.8–1626.5 MHz band.

(iv) For airborne mobile earth stations operating in the 1610.0–1626.5 MHz

band, the separation distance shall be the larger of the distances specified in paragraph (a)(1) (i), (ii) or (iii) of this section, as applicable, or the distance, d, as given by the formula:

$$d \text{ (km)} = 4.1 \text{ square root of (h)}$$

where h is the altitude of the aircraft in meters above ground level.

(v) Smaller geographic protection zones may be used in lieu of the areas specified in paragraphs (a)(1) (i), (ii), (iii), and (iv) of this section if agreed to by the Mobile-Satellite Service licensee and the Electromagnetic Spectrum Management Unit (ESMU), National Science Foundation, Washington, D.C. upon a showing by the Mobile-Satellite Service licensee that the operation of a mobile earth station will not cause harmful interference to a radio astronomy observatory during periods of observation.

(vi) The ESMU shall notify Mobile-Satellite Service space station licensees authorized to operate mobile earth terminals in the 1610.0–1626.5 MHz band of periods of radio astronomy observations. The mobile-satellite systems shall be capable of terminating operations within the frequency bands and protection zones specified in paragraphs (a)(1) (i) through (iv) of this section, as applicable, after the first position fix of the mobile earth terminal either prior to transmission or, based upon its location within the protection zone at the time of initial transmission of the mobile earth terminal. Once the mobile-satellite system determines that a mobile earth terminal is located within an RAS protection zone, the mobile-satellite system shall immediately initiate procedures to relocate the mobile earth terminal operations to a non-RAS frequency.

(vii) A beacon-actuated protection zone may be used in lieu of fixed protection zones in the 1610.6–1613.8 MHz band if a coordination agreement is reached between a mobile-satellite system licensee and the ESMU on the specifics of beacon operations.

(viii) Additional radio astronomy sites, not located within 100 miles of the 100 most populous urbanized areas as defined by the United States Census Bureau at the time, may be afforded

similar protection one year after notice to the mobile-satellite system licensees by issuance of a public notice by the Commission.

(2) Mobile-Satellite Service space stations transmitting in the 1613.8–1626.5 MHz band shall take whatever steps necessary to avoid causing harmful interference to the radio astronomy facilities listed in paragraphs (a)(1)(i) and (ii) of this section during periods of observation.

(3) Mobile-Satellite Service space stations operating in the 2483.5–2500 MHz frequency band shall limit spurious emission levels in the 4990–5000 MHz band so as not to exceed –241 dB (W/m²/Hz) at the surface of the Earth.

(4) The Radioastronomy Service shall avoid scheduling radio astronomy observations during peak MSS/RDSS traffic periods to the greatest extent practicable.

(b) If a Mobile-Satellite Service space station operator in the 2496–2500 MHz band intends to operate at powers levels that exceed the PFD limits in § 25.208(v), or if actual operations routinely exceed these PFD limits, we require the Mobile-Satellite Service operator to receive approval from each operational BRS system in the affected geographical region.

[59 FR 53329, Oct. 21, 1994, as amended at 61 FR 9945, Mar. 12, 1996; 67 FR 61816, Oct. 2, 2002; 71 FR 35188, June 19, 2006]

§ 25.214 Technical requirements for space stations in the satellite digital audio radio service.

(a) Definitions.

(1) *Allocated bandwidth.* The term “allocated bandwidth” refers to the entry in the Table of Frequency Allocations of a given frequency band for the purpose of its use by one or more terrestrial or space radiocommunication services under specified conditions. This term shall be applied to the 2310–2360 MHz band for satellite DARS.

(2) *Frequency Assignment.* The term “frequency assignment” refers to the authorization given by the Commission for a radio station to use a radio frequency or radio frequency channel under specified conditions. This term shall be applied to the two frequency

bands (A) 2320.0–2332.5 MHz and (B) 2332.5–2340.0 MHz for satellite DARS.

(b) Each system authorized under this section will be conditioned upon construction, launch and operation milestones as outlined in § 25.144(b). The failure to meet any of the milestones contained in an authorization will result in its cancellation, unless such failure is due to circumstances beyond the licensee’s control or unless otherwise determined by the Commission upon proper showing by the licensee in any particular case.

(c) Frequency assignments will be made for each satellite DARS system as follows:

(1) Exclusive satellite DARS licenses are limited to the 2320–2345 MHz band segment of the allocated bandwidth for satellite DARS;

(2) Two, 12.5 MHz frequency assignments are available for satellite DARS: 2320.0–2332.5 MHz and 2332.5–2345.0 MHz;

(3) Satellite DARS licensees may reduce their assigned bandwidth occupancy to provide telemetry beacons in their exclusive frequency assignments;

(4) Each licensee may employ cross polarization within its exclusive frequency assignment and/or may employ cross polarized transmissions in frequency assignments of other satellite DARS licensees under mutual agreement with those licensees. Licensees who come to mutual agreement to use cross-polarized transmissions shall apply to the Commission for approval of the agreement before coordination is initiated with other administrations by the licensee of the exclusive frequency assignment; and

(5) Feeder uplink networks are permitted in the following Fixed-Satellite Service frequency bands: 7025–7075 MHz and 6725–7025 MHz (101° W.L. orbital location only).

[62 FR 11106, Mar. 11, 1997]

§ 25.215 Technical requirements for space stations in the Direct Broadcast Satellite Service.

In addition to § 25.148(f), space station antennas operating in the Direct Broadcast Satellite Service must be designed to provide a cross-polarization isolation such that the ratio of the on-axis co-polar gain to the cross-polar